

Page 1/8

Revision: 12.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 66 (replaces version 65)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Quick Seal Grey

· Article number: 34502

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture

Sealant Adhesive

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

KENT (United Kingdom) Ltd Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- Signal word Void
- · Hazard statements Void
- · Additional information:

Contains trimethoxyvinylsilane. May produce an allergic reaction.

Safety data sheet available on request.

Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

- 2.3 Other hazards Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released during curing.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· Description: Mixture of the substances listed below with harmless additions.

Dangerous components	5.	
	Titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] substance with a Community workplace exposure limit	0-<3%
	3-(trimethoxysilyl)propylamine ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315	<3%
	trimethoxyvinylsilane ♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H332; Skin Sens. 1B, H317	<1%

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 66 (replaces version 65) Revision: 12.01.2023

Trade name: Quick Seal Grey

CAS: 870-08-6
EINECS: 212-791-1
Substance with a Community workplace exposure limit.
Substance identified as having endocrine disrupting properties (II).

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· After inhalation Take affected persons into the open air and position comfortably

After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact Rinse opened eye for several minutes under running water.

After swallowing

Rinse out mouth.

In case of persistent symptoms consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up: Collect mechanically.
- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and containers: Store in cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Protect from heat and direct sunlight.

Store in cool, dry conditions in well sealed containers.

Protect from humidity and keep away from water.

10-35°C

· Storage class 11

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 66 (replaces version 65) Revision: 12.01.2023

Trade name: Quick Seal Grey

(Contd. of page 2)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

13463-67-7 Titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

WEL Long-term value: 10* 4** mg/m3 *total inhalable **respirable

870-08-6 dioctyltin oxide

WEL Short-term value: 0.2 mg/m3 Long-term value: 0.1 mg/m3 as Šn; Sk

Regulatory information WEL: EH40/2020

DNELs

471-34-1 Calcium carbonate

Inhalative Long term systemic effect 10 mg/m3 (Worker) Long term local effect 4.26 mg/m3 (Worker)

13822-56-5 3-(trimethoxysilyl)propylamine

8.3 mg/kg bw/day (Worker) Acute systemic effect Dermal Long term systemic effect | 8.3 mg/kg/dy (Worker) Inhalative | Long term systemic effect | 58 mg/m3/1h (Worker) Acute systemic effect 58 mg/m3 (Worker)

1333-86-4 Carbon black

Inhalative Long term systemic effect 2 mg/m³ (Worker) Long term local effect 2 mg/m3 (Worker)

2768-02-7 trimethoxyvinylsilane

Long term systemic effect 3.9 mg/kg bw/day (Worker) Dermal Inhalative Long term systemic effect 27.6 mg/m3 (Worker)

52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate

Acute systemic effect 2 mg/kg bw/day (Worker) Long term systemic effect 0.5 mg/kg bw/day (Worker) Inhalative Long term systemic effect 0.68 mg/kg (Worker)

PNECs

13463-67-7 Titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

PNEC 0.184 mg/l (Aqua (freshwater))

0.193 mg/l (Aqua (intermittent))

0.0184 mg/l (Aqua (marine water))

1,000 mg/kg (Freshwater sediment)

100 mg/kg (Marine water sediment)

100 mg/l (Sewage treatment plant)

100 mg/kg (Soil)

13822-56-5 3-(trimethoxysilyl)propylamine

PNEC 0.33 mg/l (Aqua (freshwater))

0.033 mg/l (Aqua (marine water))

0.26 mg/kg (Freshwater sediment)

13 mg/l (Sewage treatment plant)

0.04 mg/kg (Soil)

2768-02-7 trimethoxyvinylsilane

PNEC 0.34 mg/l (Aqua (freshwater))

3.4 mg/l (Aqua (intermittent))

0.034 mg/l (Aqua (marine water))

0.27 mg/l (Freshwater sediment)

110 mg/l (Sewage treatment plant)

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 66 (replaces version 65) Revision: 12.01.2023

Trade name: Quick Seal Grey

(Contd. of page 3)

0.046 mg/kg (Soil)

52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate

PNEC 0.018 mg/l (Aqua (freshwater))

0.0018 mg/l (Agua (marine water)) 29 mg/kg (Freshwater sediment)

2.9 mg/kg (Marine water sediment)

5.9 mg/kg (Soil)

· Ingredients with biological limit values:

Additional Occupational Exposure Limit Values for possible hazards during processing:

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released during curing.

67-56-1 methanol

WEL | Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

· Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures Wash hands during breaks and at the end of the work.

· Breathing equipment: Not necessary if room is well-ventilated.

· Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 5 > 240 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Safety glasses (EN 166)

· Body protection: Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information

Physical state Solid · Colour: Grey · Odour: Mild

· Odour threshold: Not determined. Melting point/freezing point: Not determined Boiling point or initial boiling point and boiling range Not determined Not determined.

· Flammability

Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 66 (replaces version 65) Revision: 12.01.2023

Trade name: Quick Seal Grey

ash point: Accomposition temperature: A Mixture is Associty: Another application and is a point at 23 °C: A Mixture is A M	ined. on-polar/aprotic. ble. 00 Pas
Mixture is scosity: nematic viscosity namic at 23 °C: blubility atter: untition coefficient n-octanol/water (log value) pour pressure: pour pressure: pour density and/or relative density pour density pour density pour density portant information popearance: porm: portant information on protection of health and point information on protection of health and point product is polyent content: product is polyent content: product is polyent content: product is polyent content: product is polyent content on the polyent information on protection of health and polyent content in the product is polyent content in the pro	on-polar/aprotic. ble. 00 Pas
nematic viscosity nematic viscosity namic at 23 °C: noubility ater: urition coefficient n-octanol/water (log value) nour pressure: nousity and/or relative density noity at 20 °C noity and/or relative density not determ not density not determ not applicate density not determ not applicate density not density not applicate norm: nopearance: norm: nopearance: norm: not applicate normation on protection of health and note of the product is not applicate density not determ not applicate density not applica	ble. 00 Pas
nematic viscosity namic at 23 °C: namic at 23 °C: not blubility ater: urition coefficient n-octanol/water (log value) not detern not applicate and/or relative density ensity at 20 °C native density nour density not detern not applicate and not applicate pour density not detern not applicate not density not applicate not applicate not density not applicate not appli	00 Pas
contamic at 23 °C: Colubility Colubility Contain Coefficient n-octanol/water (log value) Contain Coefficient n-octanol/water (log value) Consity and/or relative density Consity at 20 °C Collative density Colla	00 Pas
olubility ater: ater: artition coefficient n-octanol/water (log value) appour pressure: ansity and/or relative density ansity at 20 °C alative density appour density Cother information appearance: arm: apportant information on protection of health and avironment, and on safety. alf-inflammability: apportant content: apport content: apport content: apport on a condition apporation rate formation with regard to physical hazard classes apposites and application application apposites and application application apposites apposites apposites and application applicat	
ater: Intrition coefficient n-octanol/water (log value) Intrition coefficient n-octanol/water (log value) Inpour pressure: Insity and/or relative density Insity at 20 °C Insi	ined.
artition coefficient n-octanol/water (log value) Inpour pressure: Inpour pressure: Insity and/or relative density Insity at 20 °C Insity at 20	ined.
pour pressure: prosity and/or relative density prosity at 20 °C plative density prour density prour density provident information properance: promition properance: promition properant information on protection of health and prironment, and on safety. product is pr	ined.
ensity and/or relative density ensity at 20 °C elative density epour den	
ensity at 20 °C elative density nour density not determ not applicate 2 Other information pearance: prim: portant information on protection of health and evironment, and on safety. elf-inflammability: product is plosive properties: product is plosive properties: product is plosive product is pro	ble.
elative density pour density Popur density Not application page arance: Pasty Portant information on protection of health and evironment, and on safety. Elf-inflammability: Product is plosive properties: Product is plosive properties: Product is plosive properties: Product is playent content: Paganic solvents: Product is playent condition Paporation rate Formation with regard to physical hazard classes Product is playent classes Product is playent condition Product is product is playent content: Product is product is product is product is playent content. Product is product is product is product is playent content. Product is pr	
Appour density 2 Other information Opearance: Operation	
2 Other information opearance: prom: Pasty portant information on protection of health and ovironment, and on safety. Iff-inflammability: Product is plosive properties: Product is olvent content: ganic solvents: NIL VOC or ange in condition raporation rate Not applicate formation with regard to physical hazard classes replosives Void or angeling gases Void or angeling gase Void or angeling gase Void or ang	ined.
ppearance: prm: portant information on protection of health and protection of health and protection of health and product is plf-inflammability: product is plosive properties: product is plosive properties: product is pr	ble.
ppearance: prm: portant information on protection of health and protection of health and protection of health and product is plf-inflammability: product is plosive properties: product is plosive properties: product is pr	
prim: Pasty portant information on protection of health and evironment, and on safety. elf-inflammability: Product is explosive properties: Product is elf-inflammability: Product is explosive properties: Product is explosive properties: NIL VOC enange in condition exporation rate Not applicate formation with regard to physical hazard classes explosives Void exposols Void exidising gases Void exidising gases Void exposols Void exposo	
portant information on protection of health and evironment, and on safety. elf-inflammability: Product is plosive properties: Product is explosive properties: Product is explosive properties: Product is explosive properties: Product is explosive series of the explosive series of the explosive series explosive	
vironment, and on safety. elf-inflammability: Product is plosive properties: Product is ploent content: ganic solvents: NIL VOC pange in condition raporation rate Not applicate promation with regard to physical hazard classes plosives Void pange in condition void prosols Void prosols Void pages Void page	
elf-inflammability: Product is plosive properties: Product is ploent content: Product is playent content: Product is product is playent content: Product is product is playent content: Product is playent content: Product is playent content: Product is playent content: Product is playent is playent content: Product is playent is playent content: Product is playent is playent content. Product is playent is playent is playent in the product is playent in the product is playent in the playent is playent in the playe	
rplosive properties: Product is plyent content: rganic solvents: Product is plyent content: Rganic solvents: Range in condition Raporation rate Product is plyent content: Not applicate to physical hazard classes Replosives R	not selfigniting
olivent content: reganic solvents: nange in condition reporation rate formation with regard to physical hazard classes replosives r	
rganic solvents: nange in condition raporation rate formation with regard to physical hazard classes rplosives rammable gases rosols r	iot explosive.
nange in condition raporation rate Not application with regard to physical hazard classes replosives replosiv	
raporation rate Not application with regard to physical hazard classes replosives ammable gases void recosols void recosol	
formation with regard to physical hazard classes void cammable gases void crosols void cidising gases void cases under pressure void cammable liquids void cammable solids void cammable solids void cammable solids	hle
rplosives Void fammable gases Void for crosols Void for c	
ammable gases Void erosols Void kidising gases Void ases under pressure Void ammable liquids Void ammable solids Void	
erosols Void kidising gases Void ases under pressure Void ammable liquids Void ammable solids Void	
kidising gases Void ases under pressure Void ammable liquids Void ammable solids Void	
ases under pressure Void ammable liquids Void ammable solids Void	
ammable liquids Void ammable solids Void	
ammable solids Void	
in-reactive substances and mixtures Vola	
rophoric liquids Void	
• •	
elf-heating substances and mixtures Void	
ubstances and mixtures, which emit flammable gases	
contact with water Void	
xidising liquids Void	
xidising solids Void	
rganic peroxides Void	
orrosive to metals Void esensitised explosives Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

GE

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 66 (replaces version 65) Revision: 12.01.2023

Trade name: Quick Seal Grey

(Contd. of page 5)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

40460 67 7 T	itamicum diassida fim .	and a farm and initial 4 0/ or many of mortials with a graduation of interest of 40 cm.
		powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]
Oral	LD50	>20,000 mg/kg (Rat)
Dermal	LD50	>10,000 mg/kg (rbt)
	ErC 50	61 mg/l (Algae) (EPA 600/9-78-018, 72 hr)
13822-56-5 3	-(trimethoxysilyl)pro	pylamine
	OECD 437	<3 (Bovine Cornea) (OCED Test No. 437)
1333-86-4 Ca	rbon black	
Oral	LD50	10,000 mg/kg (Rat)
2768-02-7 trii	methoxyvinylsilane	
Oral	LD50	7,120 mg/kg (Rat)
Sensitisation	OECD Test No.406	Not a skin sensitiser (Guinea pig)
	OECD Test No. 405	(Rabbit) (Acute Eye irritation / corrosion: Non irritant)
870-08-6 dio	ctyltin oxide	
Oral	LD50	2,500 mg/kg (Rat)
52829-07-9 B	is 2,2,6,6-tetramethy	/l-4-piperidyl) sebacate
Oral	LD50	>2,000 mg/kg (Rat) (OECD 423)
Dermal	LD50	>3.170 mg/kg (Rat) (OECD 402)

[·] Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation

No classification is proposed, based on conclusive negative data. By analogy to another tested similar product:

No irritation after contact to the eyes. (H319 is void).

3-(trimethoxysilyl)propylamine CAS 13822-56-5

OECD 437 Bovine Corneal Opacity and Permeability (BCOP) test

Corneal / Bovine / Exposure time 10 mins; Product score <3 Non-irritant

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data.

May cause sensitisation in susceptible persons.

Trimethoxyvinylsilane CAS 2768-02-7

OECD Test No. 406 Skin sensitisation

Dermal / Guinea pig: Not a skin sensitiser

Based on available data, the classification criteria are not met.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

· Endocrine disrupting properties	
870-08-6 dioctyltin oxide	List II

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic toxic	· Aquatic toxicity:		
471-34-1 Calciu	um carbonate		
EC50	>1,000 mg/l (Activated sludge) (OECD 209 3 hrs)		
EC50 (72 hr)	>200 mg/l (Algae)		
	>14 mg/l (Desmodesmus subspicatus) (OECD 202)		
NOEC	1,000 mg/l (Activated sludge) (OECD 209 3 hrs)		
NOELR	14 mg/l (Desmodesmus subspicatus) (OECD 201 72 hrs)		
	(Contd. on page 7)		

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 66 (replaces version 65) Revision: 12.01.2023

Trade name: Quick Seal Grey

13463-67-7 Titar	(Contd. of p nium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]
LC50 (48 hr)	5.5 mg/l (Crustacea)
LC50 (96 hr)	>100 mg/l (Oncorhynchus mykiss) (= OECD 203)
13822-56-5 3-(tri	imethoxysilyl)propylamine
EC50 (48 hr)	331 mg/l (Daphnia magna) (OECD 202)
EC50 (72 hr)	>1,000 mg/l (Desmodesmus subspicatus) (EU Method C.3 (Algal Inhibition test))
LC50 (96 hr)	>934 mg/l (Danio rerio (Zebra fish; semistatic)) (OECD 203)
1333-86-4 Carbo	n black
EC50 (24 hr)	>5,600 mg/l (Daphnia magna) (OECD 202)
LC50 (96 hr)	>1,000 mg/l (Brachydanio rerio) (OECD 203)
2768-02-7 trimet	thoxyvinylsilane
EC10	1,000 (Pseudomonas Putida) (5 hours)
EC50 (48 hr)	169 mg/l (Daphnia magna)
EC50 (72 hr)	210 mg/l (Selenastrum capricornutum)
	>957 mg/l (Desmodesmus subspicatus) (EU Method C.3)
LC50 (96 hr)	191 mg/l (Oncorhynchus mykiss)
NOEC (72 hr)	25 mg/l (Selenastrum capricornutum)
NOEC (21 days)	28 mg/l (Daphnia magna) (Reproduction)
52829-07-9 Bis 2	2,2,6,6-tetramethyl-4-piperidyl) sebacate
EC50 (24 hr)	17 mg/l (Daphnia magna) (OECD 202)
EC50	1.9 mg/l (Algae (Scenedesmus subspicatus)) (DIR 92/69/EC)
EC50 (72 hr)	0.705 mg/l (Pseudokirchneriella subcapitata)
LC50	5,290 ug/l (Fish)
	0.013 ug/l (Oncorhynchus mykiss) (OECD 203)
LC50 (48 hr)	8.58 mg/l (Daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- * 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 66 (replaces version 65) Revision: 12.01.2023

Trade name: Quick Seal Grey

	(0)	Contd. of page 7
· 14.4 Packing group · ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
Transport/Additional information:	Not dangerous according to the above specifications.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

· Department issuing data specification sheet: Environment protection department

Abbreviations and acronyms:

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

GHS. Globally Hallmonised system of classification and Ladering of Grenica EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

1 CEC. 1 - Existence Services 6.0 servent.

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

LDSO. Lethal dose, 30 Percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B

Data compared to the previous version altered. *