

Page 1/10

Revision: 17.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 9 (replaces version 8)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: PLASTIC PREP
- · Article number: 34699
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

- · Application of the substance / the mixture Priming
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079 SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms







GHS02

GHS07

GHS09

· Signal word Danger

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

(Contd. of page 1)

· Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Propan-2-ol

Acetone

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P280 Wear protective gloves / eye protection. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· Description: Mixture of the substances listed below with harmless additions.

Dangerous components:		
CAS: 68476-85-7 EINECS: 270-704-2	Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)). § Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Application of the state of the		25-50%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	Propan-2-ol ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49 Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066		10-25%
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44	n-hexane ♦ Flam. Liq. 2, H225; ♦ Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C ≥ 5 %	<1%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

Aliphatic hydrocarbons ≥30%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· After inhalation

Take affected persons into the open air and position comfortably

In case of unconsciousness bring patient into stable side position for transport.

- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- After swallowing

Rinse out mouth.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

(Contd. of page 2)

In case of persistent symptoms consult doctor.

- * 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

· Additional information

Cool endangered containers with water spray jet.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on flames or red-hot objects.

Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Store container in a well ventilated position.

Keep container tightly sealed.

Storage class 2 B

7.3 Specific end use(s) No further relevant information available.

GB

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection 8.1 Control parameters Components with limit values that require monitoring at the workplace: 68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)). WEL Short-term value: 2180 mg/m³, 1250 ppm Long-term value: 1750 mg/m³, 1000 ppm Carc (if LPG contains > 0.1% of buta-1.3-diene) 67-63-0 Propan-2-ol WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm 67-64-1 Acetone WEL | Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm 110-54-3 n-hexane WEL Long-term value: 72 mg/m³, 20 ppm Regulatory information WEL: EH40/2020 DNELs Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Oral Long term systemic effect | 699 mg/kg bw/day (Consumer) Dermal Long term systemic effect 699 mg/kg bw/day (Consumer) 773 mg/kg bw/day (Worker) Inhalative Long term systemic effect 608 mg/m3 (Consumer) 2,035 mg/m3 (Worker) 67-63-0 Propan-2-ol Oral Long term systemic effect | 26 mg/kg/day (Consumer) Long term systemic effect 319 mg/kg/day (Consumer) Dermal 888 mg/kg bw/day (Worker) Inhalative Long term systemic effect 89 mg/m³ (Consumer) 500 mg/m3 (Worker) 67-64-1 Acetone Dermal Long term systemic effect 186 mg/kg bw/day (Worker) Inhalative Long term systemic effect 1,210 mg/m3 (Worker) Acute local effect 2,420 mg/m3 (Worker) PNECs 67-63-0 Propan-2-ol PNEC | 140.9 mg/l (Aqua (freshwater)) 140.9 mg/l (Aqua (intermittent)) 140.9 mg/l (Aqua (marine water)) 552 mg/kg (Freshwater sediment) 552 mg/kg (Marine water sediment) 2,251 mg/l (Sewage treatment plant) (Assessment factor 1) 28 mg/kg (Soil) 67-64-1 Acetone PNEC 10.6 mg/l (Aqua (freshwater)) 21 mg/l (Aqua (intermittent)) 1.06 mg/l (Aqua (marine water)) 30.4 mg/kg (Freshwater sediment) 3.04 mg/kg (Marine water sediment) 29.5 mg/kg (Soil) Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Keep away from foodstuffs, beverages and food.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

(Contd. of page 4)

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment:

Only during spraying without adequate removal by suction.

Filter AX / P (EN 14387)

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Not applicable, as aerosol

Mixture is non-soluble (in water).

Not applicable.

Not determined.

1.4 Vol %

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Safety glasses (EN 166)

Body protection: Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information

· Physical state Aerosol Colour: Colourless Odour: Characteristic · Odour threshold: Not determined. Not determined

· Melting point/freezing point:

Boiling point or initial boiling point and boiling range

· Flammability

Lower and upper explosion limit · Lower:

· Upper: 10.9 Vol % · Flash point: Not applicable, as aerosol

Ignition temperature: 365 °C

Decomposition temperature: Not determined. · pH

· Viscosity: Kinematic viscosity Not determined

dynamic: Not determined.

Solubility

· Water: Not miscible / difficult to mix Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure: Density and/or relative density

Density Not determined

· Relative density Not determined.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

Maria de la companya della companya della companya della companya de la companya della companya	(Contd. of pag
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health and	
environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Not determined.
Solvent content:	
Organic solvents:	650 g/l VOC
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container: May burst if
	heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gas	ses
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	LD/LC50 values that are relevant for classification:		
Hydrocarl	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5,840 mg/kg (Rat)	
Dermal	LD50	>2,920 mg/kg (Rabbit)	
Inhalative	LC50 (4 hr)	>25.2 mg/l (Rat)	
67-63-0 Propan-2-ol			
Oral	LD50	5,840 mg/kg (Rat)	
Dermal	LD50	13,400 mg/kg (Rabbit)	
67-64-1 Acetone			
Oral	LD50	5,800 mg/kg (Rat)	
		(Contd. on page	

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

(Contd. of page 6)
Dermal LD50 20,000 mg/kg (Rabbit)

Skin corrosion/irritation Causes skin irritation.

- Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic toxici	tv:	
<u> </u>	oleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).	
EC50 (96 hr)	12.32 mg/l (Algae) ((Q)SAR calculation method)	
LC50 (48 hr)	69.43 mg/l (Daphnia magna) ((Q)SAR calculation method)	
LC50 (96 hr)	49.47 mg/l (Fish) ((Q)SAR calulation method)	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
EL50 (48 hr)	3 mg/l (Daphnia magna)	
EL50 (72 hr)	30-100 mg/l (Pseudokirchneriella subcapitata)	
LL50	11.4 mg/l (Oncorhynchus mykiss) (96 hr)	
LOEC (21 days)) 0.32 mg/l (Daphnia magna)	
NOEC (21 days)	s) 0.17 mg/l (Daphnia magna)	
NOELR	3 mg/l (Pseudokirchneriella subcapitata) (72 hr)	
67-63-0 Propan-2-ol		
EC50 (48 hr)	13,299 mg/l (Daphnia magna)	
LC50 (24 hr)	9,714 mg/l (Daphnia magna)	
LC50 (96 hr)	4,200 mg/l (FSH) (dynamic)	
	9,640 mg/l (Pimephales promelas)	
LOEC (8 days)	1,000 mg/l (Algae)	
67-64-1 Acetone		
EC50	61,150 mg/l (Activated sludge) (30 mins)	
EC50 (48 hr)	39 mg/l (Daphnia magna)	
LC50 (96 hr)	8,300 mg/l (Fish)	
	5,540 mg/l (Oncorhynchus mykiss)	
NOEC (28 days)	2,212 mg/l (Daphnia magna)	

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- · Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

(Contd. of page 7)

· Uncleaned packagings:

instruments

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN number or ID number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
IMDG	AEROSOLS, MARINE POLLUTANT
IATA	AEROSOLS, MARINE POLLUTANT AEROSOLS. flammable
	AEROSOLS, Ilaminable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG	
Class	2.2.0000
	2.2 Gases.
Label IATA	2.1
Class	2.2 Gases.
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
	VOIU
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Hydrocarbon
Marine pollutant:	C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
-	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Kemler Number:	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.

Not applicable.

(Contd. on page 9)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

	(Contd. of page
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations
- · Technical instructions (air):

Class	Share in %
1	0.5
NK	32.0

- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects. H411

EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing data specification sheet: Environment protection department

Abbreviations and acronyms:

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 9 (replaces version 8) Revision: 17.01.2023

Trade name: PLASTIC PREP

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
: Aerosols – Category 3
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Data compared to the previous version altered. (Contd. of page 9)

Data compared to the previous version altered. *