

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Z43**

Article number: 50040

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Lubricant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS09

Signal word *Danger*

Hazard-determining components of labelling:

pentane

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

Trade name: Z43

(Contd. of page 1)

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P280 Wear protective gloves / eye protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 68476-85-7 EINECS: 270-704-2	Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)). Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-75%
CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30	pentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	10-25%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes isoalkanes, cyclic Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****After inhalation**

Take affected persons into the open air and position comfortably
 In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing

Rinse out mouth.
 Do not induce vomiting; instantly call for medical help.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
 Carbon monoxide and carbon dioxide

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

Trade name: Z43

(Contd. of page 2)

5.3 Advice for firefighters**Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on flames or red-hot objects.

7.2 Conditions for safe storage, including any incompatibilities**Storage****Requirements to be met by storerooms and containers:**

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.**Further information about storage conditions:**

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Storage class 2 B**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:****68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).**WEL Short-term value: 2180 mg/m³, 1250 ppmLong-term value: 1750 mg/m³, 1000 ppm

Carc (if LPG contains > 0.1% of buta-1.3-diene)

109-66-0 pentaneWEL Long-term value: 1800 mg/m³, 600 ppm**Regulatory information** WEL: EH40/2020

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

Trade name: Z43

(Contd. of page 3)

· DNELs**109-66-0 pentane**

Dermal	Long term systemic effect	432 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	3,000 mg/m ³ (Worker)

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

Oral	Long term systemic effect	149 mg/kg bw/day (Consumer)
Dermal	Long term systemic effect	149 mg/kg/day (Consumer) 300 mg/kg/day (Worker)
Inhalative	Long term systemic effect	447 mg/m ³ (Consumer) 2,085 mg/m ³ (Worker)

· PNECs**109-66-0 pentane**

PNEC	0.23 mg/l (Aqua (freshwater))
	1.2 mg/kg (Freshwater sediment)
	3.6 mg/l (Sewage treatment plant)
	0.55 mg/kg (Soil)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Take off immediately all contaminated clothing
Wash hands during breaks and at the end of the work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· Breathing equipment:

Only during spraying without adequate removal by suction.

Short term filter device:

Filter AX (EN 14387)

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Safety glasses (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

GB

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

Trade name: Z43

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Physical state	Aerosol
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	Not applicable, as aerosol
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable, as aerosol
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Partly miscible
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C	0.715 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	558 g/l VOC
· Change in condition	
· Evaporation rate	Not applicable.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container. May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

GB
(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

Trade name: Z43

(Contd. of page 5)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

109-66-0 pentane

Oral	LD50	2,001 mg/kg (Rat)
Dermal	LD50	2,001 mg/kg (Rat)

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

Inhalative	LC50 (4 hr)	>23 mg/l (Rat)
	IC50	<10 (Algae)

- **Skin corrosion/irritation** Causes skin irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).

EC50 (96 hr)	12.32 mg/l (Algae) ((Q)SAR calculation method)
LC50 (48 hr)	69.43 mg/l (Daphnia magna) ((Q)SAR calculation method)
LC50 (96 hr)	49.47 mg/l (Fish) ((Q)SAR calculation method)

109-66-0 pentane

EC50	10.7 mg/l (Pseudokirchneriella subcapitata) (72 hours)
EC50 (48 hr)	2.7 mg/l (Daphnia magna)
LC50 (96 hr)	4.26 mg/l (Oncorhynchus mykiss)
NOEC (72 hr)	7.51 mg/l (Pseudokirchneriella subcapitata)

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

EC50 (48 hr)	3 mg/l (Daphnia magna)
LC50 (96 hr)	<10 mg/l (Fish)
	>13.4 mg/l (Oncorhynchus mykiss)
NOEC	1.53 mg/l (Oncorhynchus mykiss) (28 days)
NOEC (21 days)	1 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** Biodegradable
- **12.3 Bioaccumulative potential** Does not accumulate in organisms
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

Trade name: Z43

(Contd. of page 6)

12.7 Other adverse effects· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations**13.1 Waste treatment methods**· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN number or ID number**· **ADR, IMDG, IATA** UN1950**14.2 UN proper shipping name**

· ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· IMDG	AEROSOLS, MARINE POLLUTANT
· IATA	AEROSOLS, flammable

14.3 Transport hazard class(es)· **ADR**· **Class** 2 5F Gases.· **Label** 2.1· **IMDG**· **Class** 2.1 Gases.· **Label** 2.1· **IATA**· **Class** 2.1 Gases.· **Label** 2.1**14.4 Packing group**· **ADR, IMDG, IATA** Void**14.5 Environmental hazards:**· **Marine pollutant:** Product contains environmentally hazardous substances: pentane· **Special marking (ADR):** Symbol (fish and tree)· **Special marking (ADR):** Symbol (fish and tree)**14.6 Special precautions for user**

Warning: Gases.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

Trade name: Z43

(Contd. of page 7)

· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations**
- **Technical instructions (air):**

Class	Share in %
NK	25.0

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 55 (replaces version 54)

Revision: 17.01.2023

Trade name: Z43

(Contd. of page 8)

· **Department issuing data specification sheet:** Environment protection department

· **Abbreviations and acronyms:**

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 : Aerosols – Category 3
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **Data compared to the previous version altered.** *

GB