

Page 1/9

Revision: 17.01.2023

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 58 (replaces version 57)

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- · Trade name: SL 85
- · Article number: 83688
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

- · Application of the substance / the mixture Lubricant
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

**KY11 8US** 

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079 SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

# SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3

H336 May cause drowsiness or dizziness.

#### 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms







GHS02

GHS07

GHS09

- · Signal word Danger
- Hazard-determining components of labelling:
- Hazard statements

H222 Extremely flammable aerosol.

(Contd. on page 2)

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 58 (replaces version 57) Revision: 17.01.2023

Trade name: SL 85

(Contd. of page 1)

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- Labelling of packages where the contents do not exceed 125 ml
- · Hazard pictograms







GHS02

GHS07

GHS09

#### · Signal word Danger

· Hazard-determining components of labelling:

pentane

#### Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

#### 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

#### **SECTION 3: Composition/information on ingredients**

# 3.2 Mixtures

· Description: Mixture of the substances listed below with harmless additions.

Dangerous components:			
	butane, pure   Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%	
	pentane <b>③</b> Flam. Liq. 2, H225; <b>③</b> Asp. Tox. 1, H304; <b>⑤</b> Aquatic Chronic 2, H411; <b>①</b> STOT SE 3, H336, EUH066	25-50%	
	Propane liquefied      Flam. Gas 1A, H220	5-10%	

Additional information For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact

Instantly wash with water and soap and rinse thoroughly.

Generally the product is not skin irritating.

- · After eye contact Rinse opened eye for several minutes under running water.
- After swallowing In case of persistent symptoms consult doctor.
- \* 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 58 (replaces version 57) Revision: 17.01.2023

Trade name: SL 85

(Contd. of page 2)

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

# Suitable extinguishing agents

Carbon dioxide

Water haze

Fire-extinguishing powder

Alcohol-resistant foam

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

#### 6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

#### Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on flames or red-hot objects.

#### 7.2 Conditions for safe storage, including any incompatibilities

- · Storage
- Requirements to be met by storerooms and containers:

Store in cool location.

- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Protect from heat and direct sunlight.

Store container in a well ventilated position.

- · Storage class 2 B
- · 7.3 Specific end use(s) No further relevant information available.

GE

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 58 (replaces version 57) Revision: 17.01.2023

Trade name: SL 85

(Contd. of page 3)

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Components with limit values that require monitoring at the workplace:

### 106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

#### 109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

# Regulatory information WEL: EH40/2020

#### DNELs

#### 109-66-0 pentane

Dermal Long term systemic effect 432 mg/kg bw/day (Worker)
Inhalative Long term systemic effect 3,000 mg/m3 (Worker)

#### PNECs

#### 109-66-0 pentane

PNEC 0.23 mg/l (Aqua (freshwater))

1.2 mg/kg (Freshwater sediment)

3.6 mg/l (Sewage treatment plant)

0.55 mg/kg (Soil)

Additional information: The lists that were valid during the compilation were used as basis.

#### 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures Wash hands during breaks and at the end of the work.
- Breathing equipment:

Only during spraying without adequate removal by suction.

Filter AX / P (EN 14387)

Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye/face protection



Safety glasses (EN 166)

Body protection: Use protective suit.

#### SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- **General Information**
- Physical state Aerosol

(Contd. on page 5)

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 58 (replaces version 57) Revision: 17.01.2023

Trade name: SL 85

(Contd. of page 4) · Colour: Copper coloured · Odour: Characteristic · Odour threshold: Not determined. Melting point/freezing point: Not determined Boiling point or initial boiling point and boiling range Not applicable, as aerosol Flammability Not applicable. Lower and upper explosion limit · Lower: 1 4 Vol % · Upper: 10.9 Vol % · Flash point: Not applicable, as aerosol Ignition temperature: 285 °C Decomposition temperature: Not determined. ·pH Mixture is non-polar/aprotic. Viscosity: · Kinematic viscosity Not determined. · dynamic: Not determined. · Solubility · Water: Not miscible / difficult to mix · Partition coefficient n-octanol/water (log value) Not determined · Vapour pressure at 20 °C: 2100 hPa · Density and/or relative density Density at 20 °C 0.68 g/cm3 · Relative density Not determined. · Vapour density Not determined 9.2 Other information · Appearance: Form: Aerosol Important information on protection of health and environment, and on safety. Self-inflammability: Product is not selfigniting. Explosive properties: Not determined. · Solvent content: 410 G/L VOC Organic solvents: · Change in condition Evaporation rate Not applicable. · Information with regard to physical hazard classes · Explosives Void Flammable gases Void · Aerosols Extremely flammable aerosol. Pressurised container: May burst if heated. · Oxidising gases Void Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

#### SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 58 (replaces version 57) Revision: 17.01.2023

Trade name: SL 85

(Contd. of page 5)

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:				
106-97-8 butane, pure				
Inhalative	Inhalative LC50 (4 hr) 658 mg/l (Rat)			
	ErC 50	19.37 mg/l (Algae) (96 hr)		
109-66-0 pentane				
Oral	LD50	2,001 mg/kg (Rat)		
Dermal	LD50	2,001 mg/kg (Rat)		
74-98-6 Propane liquefied				
	ErC 50	19.37 mg/l (Algae) (96 hr)		
0=0= <i>:</i>	•	Ad I I I I I I I I I I I I I I I I I I I		

- STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

# 12.1 Toxicity

· Aquatic toxicity:			
106-97-8 butane, pure			
EC50 (48 hr)	69.43 mg/l (Daphnia magna)		
LC50 (96 hr)	49.9 mg/l (Fish)		
109-66-0 pentane			
EC50	10.7 mg/l (Pseudokirchneriella subcapitata) (72 hours)		
EC50 (48 hr)	2.7 mg/l (Daphnia magna)		
LC50 (96 hr)	4.26 mg/l (Oncorhynchus mykiss)		
NOEC (72 hr) 7.51 mg/l (Pseudokirchneriella subcapitata)			
74-98-6 Propa	74-98-6 Propane liquefied		
EC50 (48 hr)	69.43 mg/l (Daphnia magna)		
LC50 (96 hr)	49.9 mg/l (Fish)		

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Remark: Toxic for fish
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Also poisonous for fish and plankton in water bodies.

(Contd. on page 7)

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 58 (replaces version 57) Revision: 17.01.2023

Trade name: SL 85

Toxic for aquatic organisms

(Contd. of page 6)

# SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

· **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

· **IMDG** AEROSOLS

· IATA AEROSOLS, flammable

### 14.3 Transport hazard class(es)

· ADR





 • Class
 2 5F Gases.

 • Label
 2.1

· IMDG



 • Class
 2 Gases.

 • Label
 2.1

·IATA



 • Class
 2.1 Gases.

 • Label
 2.1

14.4 Packing group

· ADR, IMDG, IATA Void

14.5 Environmental hazards:

· Marine pollutant: No

· Special marking (ADR): Symbol (fish and tree)

14.6 Special precautions for user

F-D,S-U

· Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE

AEROSOLS: Category C, Clear of living quarters.

Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for

division 1.4.

Warning: Gases.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

(Contd. on page 8)

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 58 (replaces version 57) Revision: 17.01.2023

Trade name: SL 85

	(Contd. of page
	For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk according	g to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

# SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations
- · Technical instructions (air):

Class	Share in %
NK	57.0

- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

# Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways. H304

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

# · Department issuing data specification sheet: Environment protection department

### Abbreviations and acronyms:

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

(Contd. on page 9)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 58 (replaces version 57) Revision: 17.01.2023

Trade name: SL 85

(Contd. of page 8)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
: Aerosols – Category 3
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\*\*Data compared to the previous version altered.\*\*

Data compared to the previous version altered. \*