

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 19 (replaces version 18)

Revision: 17.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **ASSEMBLY ADHESIVE BLACK**

Article number: 84535

1.2 Relevant identified uses of the substance or mixture and uses advised against
FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture

Sealant
Adhesive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd
Forsyth House
Pitreavie Drive
Pitreavie Business Park
Dunfermline
Fife
KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Additional information:

Contains trimethoxyvinylsilane. May produce an allergic reaction.

Safety data sheet available on request.

2.3 Other hazards Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released during curing.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 13822-56-5 EINECS: 237-511-5 Reg.nr.: 01-2119510159-45	3-(trimethoxysilyl)propylamine ☞ Eye Dam. 1, H318; ☞ Skin Irrit. 2, H315	<3%
CAS: 68424-38-4 EINECS: 270-299-2 Reg.nr.: 01-2119648083-41	Fatty acids, C16-18, sodium salts Aquatic Chronic 3, H412	<3%
CAS: 2768-02-7 EINECS: 220-449-8 Reg.nr.: 01-2119513215-52	trimethoxyvinylsilane ☞ Flam. Liq. 3, H226; ☞ Acute Tox. 4, H332; Skin Sens. 1B, H317	<1%

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 19 (replaces version 18)

Revision: 17.01.2023

Trade name: ASSEMBLY ADHESIVE BLACK

(Contd. of page 1)

<0.5%

CAS: 870-08-6

dioctyltin oxide

EINECS: 212-791-1

 Substance with a Community workplace exposure limit.
 Substance identified as having endocrine disrupting properties (II).

 · **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

 · **After inhalation** Take affected persons into the open air and position comfortably

 · **After skin contact** Instantly wash with water and soap and rinse thoroughly.

 · **After eye contact** Rinse opened eye for several minutes under running water.

· **After swallowing**

Rinse out mouth.

In case of persistent symptoms consult doctor.

 · **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

 · **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents**

Use fire fighting measures that suit the environment.

CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

· 5.3 Advice for firefighters

· **Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

 · **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation

 · **6.2 Environmental precautions:** No special measures required.

· **6.3 Methods and material for containment and cleaning up:**

Allow to solidify. Collect mechanically.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

 · **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

 · **Information about protection against explosions and fires:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

 · **Requirements to be met by storerooms and containers:** Store in cool location.

 · **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed containers.

Store container in a well ventilated position.

Protect from humidity and keep away from water.

10-35°C

 · **Storage class** 11

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 19 (replaces version 18)

Revision: 17.01.2023

Trade name: ASSEMBLY ADHESIVE BLACK

(Contd. of page 2)

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

870-08-6 dioctyltin oxide

WEL	Short-term value: 0.2 mg/m ³ Long-term value: 0.1 mg/m ³ as Sn; Sk
-----	--

Regulatory information WEL: EH40/2020

DNELs

471-34-1 Calcium carbonate

Inhalative	Long term systemic effect	10 mg/m ³ (Worker)
	Long term local effect	4.26 mg/m ³ (Worker)

13822-56-5 3-(trimethoxysilyl)propylamine

Dermal	Acute systemic effect	8.3 mg/kg bw/day (Worker)
	Long term systemic effect	8.3 mg/kg/dy (Worker)
Inhalative	Long term systemic effect	58 mg/m ³ /1h (Worker)
	Acute systemic effect	58 mg/m ³ (Worker)

52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate

Dermal	Acute systemic effect	2 mg/kg bw/day (Worker)
	Long term systemic effect	0.5 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	0.68 mg/kg (Worker)

2768-02-7 trimethoxyvinylsilane

Dermal	Long term systemic effect	3.9 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	27.6 mg/m ³ (Worker)

1333-86-4 Carbon black

Inhalative	Long term systemic effect	2 mg/m ³ (Worker)
	Long term local effect	2 mg/m ³ (Worker)

PNECs

13822-56-5 3-(trimethoxysilyl)propylamine

PNEC	0.33 mg/l (Aqua (freshwater))
	0.033 mg/l (Aqua (marine water))
	0.26 mg/kg (Freshwater sediment)
	13 mg/l (Sewage treatment plant)
	0.04 mg/kg (Soil)

52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate

PNEC	0.018 mg/l (Aqua (freshwater))
	0.0018 mg/l (Aqua (marine water))
	29 mg/kg (Freshwater sediment)
	2.9 mg/kg (Marine water sediment)
	5.9 mg/kg (Soil)

2768-02-7 trimethoxyvinylsilane

PNEC	0.34 mg/l (Aqua (freshwater))
	3.4 mg/l (Aqua (intermittent))
	0.034 mg/l (Aqua (marine water))
	0.27 mg/l (Freshwater sediment)
	110 mg/l (Sewage treatment plant)
	0.046 mg/kg (Soil)

Ingredients with biological limit values:

Additional Occupational Exposure Limit Values for possible hazards during processing:

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released during curing.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 19 (replaces version 18)

Revision: 17.01.2023

Trade name: ASSEMBLY ADHESIVE BLACK

(Contd. of page 3)

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm
 Long-term value: 266 mg/m³, 200 ppm
 Sk

· **Additional information:** The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Wash hands during breaks and at the end of the work.
- **Breathing equipment:** Not necessary if room is well-ventilated.
- **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Wear suitable gloves tested to EN 374
 Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Safety glasses (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information**

- | | |
|---|-------------------------------|
| · Physical state | Solid |
| · Colour: | Black |
| · Odour: | Mild |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Not determined |
| · Boiling point or initial boiling point and boiling range | Not determined |
| · Flammability | Not determined. |
| · Lower and upper explosion limit | |
| · Lower: | Not determined. |
| · Upper: | Not determined. |
| · Flash point: | Not applicable |
| · Decomposition temperature: | Not determined. |
| · pH | Mixture is non-polar/aprotic. |
| · Viscosity: | |
| · Kinematic viscosity | Not applicable. |
| · dynamic at 20 °C: | 6000 - 14000 mPas |
| · Solubility | |
| · Water: | Unsoluble |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure: | Not applicable. |

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 19 (replaces version 18)

Revision: 17.01.2023

Trade name: ASSEMBLY ADHESIVE BLACK

(Contd. of page 4)

· Density and/or relative density	
· Density at 23 °C	1.48 g/cm ³
· Relative density	Not determined.
· Vapour density	Not applicable.

· 9.2 Other information	
· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Solvent content:	
· Organic solvents:	nil VOC
· Change in condition	
· Evaporation rate	Not applicable.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

13822-56-5 3-(trimethoxysilyl)propylamine		
	OECD 437	<3 (Bovine Cornea) (OCED Test No. 437)
52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate		
Oral	LD50	>2,000 mg/kg (Rat) (OECD 423)
Dermal	LD50	>3,170 mg/kg (Rat) (OECD 402)
2768-02-7 trimethoxyvinylsilane		
Oral	LD50	7,120 mg/kg (Rat)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 19 (replaces version 18)

Revision: 17.01.2023

Trade name: ASSEMBLY ADHESIVE BLACK

(Contd. of page 5)

Sensitisation	OECD Test No.406	Not a skin sensitiser (Guinea pig)
	OECD Test No. 405	(Rabbit) (Acute Eye irritation / corrosion: Non irritant)
1333-86-4 Carbon black		
Oral	LD50	10,000 mg/kg (Rat)
870-08-6 dioctyltin oxide		
Oral	LD50	2,500 mg/kg (Rat)

· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

· **Serious eye damage/irritation**

No classification is proposed, based on conclusive negative data. By analogy to another tested similar product:

No irritation after contact to the eyes. (H319 is void).

3-(trimethoxysilyl)propylamine CAS 13822-56-5

OECD 437 Bovine Corneal Opacity and Permeability (BCOP) test

Corneal / Bovine / Exposure time 10 mins; Product score <3 Non-irritant

Based on available data, the classification criteria are not met.

· **Respiratory or skin sensitisation**

OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data.

May cause sensitisation in susceptible persons.

Trimethoxyvinylsilane CAS 2768-02-7

OECD Test No. 406 Skin sensitisation

Dermal / Guinea pig: Not a skin sensitiser

Based on available data, the classification criteria are not met.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

870-08-6 dioctyltin oxide

List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

471-34-1 Calcium carbonate

EC50	>1,000 mg/l (Activated sludge) (OECD 209 3 hrs)
EC50 (72 hr)	>200 mg/l (Algae)
	>14 mg/l (Desmodesmus subspicatus) (OECD 202)
NOEC	1,000 mg/l (Activated sludge) (OECD 209 3 hrs)
NOELR	14 mg/l (Desmodesmus subspicatus) (OECD 201 72 hrs)

13822-56-5 3-(trimethoxysilyl)propylamine

EC50 (48 hr)	331 mg/l (Daphnia magna) (OECD 202)
EC50 (72 hr)	>1,000 mg/l (Desmodesmus subspicatus) (EU Method C.3 (Algal Inhibition test))
LC50 (96 hr)	>934 mg/l (Danio rerio (Zebra fish; semistatic)) (OECD 203)

68424-38-4 Fatty acids, C16-18, sodium salts

EC50	120 mg/l (Desmodesmus subspicatus) (96 hrs)
EC50 (72 hr)	86 mg/l (Water flea (Ceriodaphnia dubia))

52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate

EC50 (24 hr)	17 mg/l (Daphnia magna) (OECD 202)
EC50	1.9 mg/l (Algae (Scenedesmus subspicatus)) (DIR 92/69/EC)
EC50 (72 hr)	0.705 mg/l (Pseudokirchneriella subcapitata)
LC50	5,290 ug/l (Fish)
	0.013 ug/l (Oncorhynchus mykiss) (OECD 203)
LC50 (48 hr)	8.58 mg/l (Daphnia magna)

2768-02-7 trimethoxyvinylsilane

EC10	1,000 (Pseudomonas Putida) (5 hours)
------	--------------------------------------

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 19 (replaces version 18)

Revision: 17.01.2023

Trade name: ASSEMBLY ADHESIVE BLACK

(Contd. of page 6)

EC50 (48 hr)	169 mg/l (Daphnia magna)
EC50 (72 hr)	210 mg/l (Selenastrum capricornutum)
	>957 mg/l (Desmodemus subspicatus) (EU Method C.3)
LC50 (96 hr)	191 mg/l (Oncorhynchus mykiss)
NOEC (72 hr)	25 mg/l (Selenastrum capricornutum)
NOEC (21 days)	28 mg/l (Daphnia magna) (Reproduction)
1333-86-4 Carbon black	
EC50 (24 hr)	>5,600 mg/l (Daphnia magna) (OECD 202)
LC50 (96 hr)	>1,000 mg/l (Brachydanio rerio) (OECD 203)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| · 14.1 UN number or ID number | |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | |
| · ADR, ADN, IMDG, IATA | |
| · Class | Void |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Maritime transport in bulk according to IMO instruments | NOT REGULATED |
| · Transport/Additional information: | Not dangerous according to the above specifications. |
| · UN "Model Regulation": | Void |

GB
(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 19 (replaces version 18)

Revision: 17.01.2023

Trade name: ASSEMBLY ADHESIVE BLACK

(Contd. of page 7)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H412 Harmful to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department
- **Abbreviations and acronyms:**
 RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1B: Skin sensitisation – Category 1B
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
- **Data compared to the previous version altered.** *

GB