

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 60 (replaces version 59)

Revision: 13.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **PROSEAL 303 BEIGE**

Article number: 85473

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kent europe.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Additional information:

Contains trimethoxyvinylsilane. May produce an allergic reaction.

Safety data sheet available on request.

2.3 Other hazards Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released during curing.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 28553-12-0 EINECS: 249-079-5 Reg.nr.: 01-2119430798-28	diisononyl phthalate substance with a Community workplace exposure limit	5-10%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	<3%
CAS: 2768-02-7 EINECS: 220-449-8 Reg.nr.: 01-2119513215-52	trimethoxyvinylsilane ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332; Skin Sens. 1B, H317	<1%

Additional information For the wording of the listed hazard phrases refer to section 16.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 60 (replaces version 59)

Revision: 13.01.2023

Trade name: PROSEAL 303 BEIGE

(Contd. of page 1)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation** Take affected persons into the open air and position comfortably
- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing**
Rinse out mouth.
In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
Use fire fighting measures that suit the environment.
CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter drainage system, surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Allow to solidify. Collect mechanically.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store in cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Protect from heat and direct sunlight.
Store in cool, dry conditions in well sealed containers.
Store container in a well ventilated position.
Protect from humidity and keep away from water.
10-35°C
- **Storage class** 10
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 60 (replaces version 59)

Revision: 13.01.2023

Trade name: PROSEAL 303 BEIGE

(Contd. of page 2)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

28553-12-0 diisononyl phthalate

WEL Long-term value: 5 mg/m³

Regulatory information WEL: EH40/2020

DNELs

471-34-1 Calcium carbonate

Inhalative Long term systemic effect 10 mg/m³ (Worker)Long term local effect 4.26 mg/m³ (Worker)

28553-12-0 diisononyl phthalate

Dermal Long term systemic effect 366 mg/kg (Worker)

Inhalative Long term systemic effect 51.72 mg/m³ (Worker)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Dermal Long term systemic effect 208 mg/kg bw/day (Worker)

Inhalative Long term systemic effect 871 mg/m³ (Worker)

52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate

Dermal Acute systemic effect 2 mg/kg bw/day (Worker)

Long term systemic effect 0.5 mg/kg bw/day (Worker)

Inhalative Long term systemic effect 0.68 mg/kg (Worker)

2768-02-7 trimethoxyvinylsilane

Dermal Long term systemic effect 3.9 mg/kg bw/day (Worker)

Inhalative Long term systemic effect 27.6 mg/m³ (Worker)

93925-43-0 Silicic acid (H₄SiO₄), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane

Oral Long term systemic effect 0.0015 mg/m³ (Worker)

Dermal Long term systemic effect 16.3 mg/kg/bw/day (Worker)

PNECs

28553-12-0 diisononyl phthalate

PNEC 30 mg/kg (Soil)

52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate

PNEC 0.018 mg/l (Aqua (freshwater))

0.0018 mg/l (Aqua (marine water))

29 mg/kg (Freshwater sediment)

2.9 mg/kg (Marine water sediment)

5.9 mg/kg (Soil)

2768-02-7 trimethoxyvinylsilane

PNEC 0.34 mg/l (Aqua (freshwater))

3.4 mg/l (Aqua (intermittent))

0.034 mg/l (Aqua (marine water))

0.27 mg/l (Freshwater sediment)

110 mg/l (Sewage treatment plant)

0.046 mg/kg (Soil)

Ingredients with biological limit values:

Additional Occupational Exposure Limit Values for possible hazards during processing:

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released during curing.

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppmLong-term value: 266 mg/m³, 200 ppm

Sk

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures Wash hands during breaks and at the end of the work.

Breathing equipment: Not necessary if room is well-ventilated.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 60 (replaces version 59)

Revision: 13.01.2023

Trade name: PROSEAL 303 BEIGE

(Contd. of page 3)

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Safety glasses (EN 166)

Body protection: Protective work clothing (EN-13034/6)**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information**

Physical state	Fluid
Colour:	Beige
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	<35 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	100 °C
Ignition temperature:	420 °C
Decomposition temperature:	Not determined.
pH	Mixture is non-polar/aprotic.
Viscosity:	
Kinematic viscosity at 20 °C	2000-4000 mPa s
dynamic:	Not determined.
Solubility	
Water:	Not miscible / difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C	1.63 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Pasty
Important information on protection of health and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 60 (replaces version 59)

Revision: 13.01.2023

Trade name: PROSEAL 303 BEIGE

(Contd. of page 4)

· Explosive properties:	Product is not explosive.
· Solvent content:	
· Organic solvents:	32 g/l VOC
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>3,000 mg/kg (Rabbit)
52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate		
Oral	LD50	>2,000 mg/kg (Rat) (OECD 423)
Dermal	LD50	>3,170 mg/kg (Rat) (OECD 402)
2768-02-7 trimethoxyvinylsilane		
Oral	LD50	7,120 mg/kg (Rat)
Sensitisation	OECD Test No. 406	Not a skin sensitiser (Guinea pig)
	OECD Test No. 405	(Rabbit) (Acute Eye irritation / corrosion: Non irritant)
93925-43-0 Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane		
Oral	LD50	>2,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 60 (replaces version 59)

Revision: 13.01.2023

Trade name: PROSEAL 303 BEIGE

(Contd. of page 5)

May cause sensitisation in susceptible persons.

Trimethoxyvinylsilane CAS 2768-02-7

OECD Test No. 406 Skin sensitisation

Dermal / Guinea pig: Not a skin sensitiser

Based on available data, the classification criteria are not met.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

471-34-1 Calcium carbonate

EC50	>1,000 mg/l (Activated sludge) (OECD 209 3 hrs)
EC50 (72 hr)	>200 mg/l (Algae)
	>14 mg/l (Desmodesmus subspicatus) (OECD 202)
NOEC	1,000 mg/l (Activated sludge) (OECD 209 3 hrs)
NOELR	14 mg/l (Desmodesmus subspicatus) (OECD 201 72 hrs)

28553-12-0 diisononyl phthalate

EC50	>88 mg/l (Algae (Scenedesmus subspicatus))
LC50 (48 hr)	>74 mg/l (Daphnia magna)
LC50 (96 hr)	>102 mg/l (Brachydanio rerio)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

EL50 (72 hr)	>1,000 mg/l (Pseudokirchneriella subcapitata)
ELO (48 hr)	1,000 mg/l (Daphnia magna)
LL50 (96 hr)	>1,000 mg/l (Oncorhynchus mykiss)
NOELR	100 mg/l (Pseudokirchneriella subcapitata) (72 hrs)

52829-07-9 Bis 2,2,6,6-tetramethyl-4-piperidyl) sebacate

EC50 (24 hr)	17 mg/l (Daphnia magna) (OECD 202)
EC50	1.9 mg/l (Algae (Scenedesmus subspicatus)) (DIR 92/69/EC)
EC50 (72 hr)	0.705 mg/l (Pseudokirchneriella subcapitata)
LC50	5,290 ug/l (Fish)
	0.013 ug/l (Oncorhynchus mykiss) (OECD 203)
LC50 (48 hr)	8.58 mg/l (Daphnia magna)

2768-02-7 trimethoxyvinylsilane

EC10	1,000 (Pseudomonas Putida) (5 hours)
EC50 (48 hr)	169 mg/l (Daphnia magna)
EC50 (72 hr)	210 mg/l (Selenastrum capricornutum)
	>957 mg/l (Desmodesmus subspicatus) (EU Method C.3)
LC50 (96 hr)	191 mg/l (Oncorhynchus mykiss)
NOEC (72 hr)	25 mg/l (Selenastrum capricornutum)
NOEC (21 days)	28 mg/l (Daphnia magna) (Reproduction)

93925-43-0 Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane

EC50 (48 hr)	331 mg/l (Daphnia magna) (OECD 202)
LC50 (96 hr)	>100 mg/l (Cyprinus carpio) (OECD 203)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 60 (replaces version 59)

Revision: 13.01.2023

Trade name: PROSEAL 303 BEIGE

(Contd. of page 6)

- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| · 14.1 UN number or ID number | |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | |
| · ADR, ADN, IMDG, IATA | |
| · Class | Void |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | Not dangerous according to the above specifications. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 60 (replaces version 59)

Revision: 13.01.2023

Trade name: PROSEAL 303 BEIGE

(Contd. of page 7)

H336 May cause drowsiness or dizziness.

· **Department issuing data specification sheet:** Environment protection department

· **Abbreviations and acronyms:**

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

· **Data compared to the previous version altered.** *

GB