

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **HS Clearcoat Anti-scratch**

Article number: 85690

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Lacquer

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

#### 1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Sens. 1A H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS02



GHS07

Signal word Warning

##### Hazard-determining components of labelling:

Benzotriazol ester/polyglycol

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate n-butyl acetate

##### Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

**Trade name: HS Clearcoat Anti-scratch**

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

Description: Mixture of the substances listed below with harmless additions.

**Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	25-50%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-10%
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-ethoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	<5%
CAS: 104810-48-2 ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76	reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) Aquatic Chronic 2, H411; Skin Sens. 1A, H317	<1%
CAS: 868-77-9 EINECS: 212-782-2 Reg.nr.: 01-2119490169-29	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	<0.25%
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	2,3-epoxypropyl neodecanoate Muta. 2, H341; Aquatic Chronic 2, H411; Skin Sens. 1, H317	<0.25%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40	reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	<0.25%

Additional information For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

After inhalation Supply fresh air; consult doctor in case of symptoms.

**After skin contact**

Instantly remove any clothing soiled by the product.

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing Do not induce vomiting; instantly call for medical help.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

**Trade name: HS Clearcoat Anti-scratch**

(Contd. of page 2)

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO<sub>2</sub>, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Do not inhale explosion gases or combustion gases.  
Wear self-contained breathing apparatus.
- **Additional information**  
Collect contaminated fire fighting water separately. It must not enter drains.  
Cool endangered containers with water spray jet.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow to enter drainage system, surface or ground water.  
Prevent material from reaching sewage system, holes and cellars.  
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**  
Store in cool location.  
Store only in the original container.
- **Information about storage in one common storage facility:** Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Protect from heat and direct sunlight.  
Store container in a well ventilated position.  
15-25°C
- **Storage class 3**
- **7.3 Specific end use(s)** No further relevant information available.

GB  
(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

Trade name: HS Clearcoat Anti-scratch

(Contd. of page 3)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Components with limit values that require monitoring at the workplace:

##### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

##### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

##### 1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

#### Regulatory information WEL: EH40/2020

#### DNELs

##### 123-86-4 n-butyl acetate

Dermal	Acute systemic effect	11 mg/kg bw/day (Worker)
	Long term systemic effect	11 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	300 mg/m <sup>3</sup> (Worker)
	Acute local effect	600 mg/m <sup>3</sup> (Worker)
	Long term local effect	300 mg/m <sup>3</sup> (Worker)
	Acute systemic effect	600 mg/m <sup>3</sup> (Worker)

##### 108-65-6 2-methoxy-1-methylethyl acetate

Dermal	Long term systemic effect	796 mg/kg/day (Worker)
Inhalative	Long term systemic effect	275 mg/m <sup>3</sup> (Worker)
	Long term local effect	550 mg/m <sup>3</sup> (Worker)

##### 1330-20-7 xylene

Dermal	Long term local effect	3,182 mg/kg/day (Worker)
Inhalative	Acute local effect	442 mg/m <sup>3</sup> (Worker)
	Long term local effect	221 mg/m <sup>3</sup> (Worker)

#### PNECs

##### 123-86-4 n-butyl acetate

PNEC 0.18 mg/l (Aqua (freshwater))  
0.36 mg/ml (Aqua (intermittent))  
0.018 mg/ml (Aqua (marine water))  
0.981 mg/kg (Freshwater sediment)  
0.0981 mg/kg (Marine water sediment)  
35.6 mg/l (Sewage treatment plant)  
0.09 mg/kg (Soil)

##### 108-65-6 2-methoxy-1-methylethyl acetate

PNEC 0.635 mg/l (Aqua (freshwater))  
1.27 mg/l (Aqua (intermittent))  
0.0127 mg/l (Aqua (marine water))  
26,670 mg/kg (Marine water sediment)  
38.3 mg/l (Sewage treatment plant)  
53,182 mg/kg (Soil)

##### 1330-20-7 xylene

PNEC 0.327 mg/l (Aqua (freshwater))  
0.327 mg/l (Aqua (marine water))  
12.46 mg/l (Freshwater sediment)  
12.46 mg/l (Marine water sediment)  
6.58 mg/l (Sewage treatment plant)  
2.31 mg/kg (Soil)

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

**Trade name: HS Clearcoat Anti-scratch**

(Contd. of page 4)

**Ingredients with biological limit values:****1330-20-7 xylene**

BMGV 650 mmol/mol creatinine  
 Medium: urine  
 Sampling time: post shift  
 Parameter: methyl hippuric acid

· **Additional information:** The lists that were valid during the compilation were used as basis.

**8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures** Wash hands during breaks and at the end of the work.

· **Breathing equipment:**

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Filter A (EN 14387)

· **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed safety glasses. (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

### SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Transparent

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

Not determined

· **Flammability**

Flammable.

· **Lower and upper explosion limit**

· **Lower:**

1.7 Vol %

· **Upper:**

7.6 Vol %

· **Flash point:**

25.5 °C (ASTM D-56)

· **Decomposition temperature:**

Not determined.

· **pH**

Mixture is non-soluble (in water).

· **Viscosity:**

· **Kinematic viscosity at 40 °C**

>500 mm<sup>2</sup>/s

· **dynamic:**

Not determined.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

Trade name: HS Clearcoat Anti-scratch

(Contd. of page 5)

· <b>Solubility</b>	
· <b>Water:</b>	Not miscible / difficult to mix
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C</b>	1.00 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density at 20 °C</b>	4.83 g/cm <sup>3</sup> (butyl acetate)
· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· <b>Solvent content:</b>	
· <b>Organic solvents:</b>	498g/l VOC (RFU)
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:**  
Strong acids and oxidizing agents  
Alkalies  
Isocyanate
- **10.6 Hazardous decomposition products:**  
Formation of toxic gases is possible during heating or in case of fire.  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)

GB  
(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

Trade name: HS Clearcoat Anti-scratch

(Contd. of page 6)

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values that are relevant for classification:

##### 123-86-4 n-butyl acetate

Oral	LD50	14,000 mg/kg (Rat)
------	------	--------------------

##### 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,500 mg/kg (Rat)
------	------	-------------------

##### 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (Rat)
------	------	-------------------

Dermal	LD50	2,000 mg/kg (Rabbit)
--------	------	----------------------

##### 868-77-9 2-hydroxyethyl methacrylate

Oral	LD50	>5,000 mg/kg (Rat)
------	------	--------------------

Dermal	LD50	>3,000 mg/kg (Rabbit)
--------	------	-----------------------

##### 26761-45-5 2,3-epoxypropyl neodecanoate

Oral	LD50	>2,000 mg/kg (Rat)
------	------	--------------------

Dermal	LD50	>2,000 mg/kg (Rat)
--------	------	--------------------

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.

· **STOT-single exposure** May cause drowsiness or dizziness.

#### 11.2 Information on other hazards

##### · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### · Aquatic toxicity:

##### 123-86-4 n-butyl acetate

EC50 (48 hr)	44 mg/l (Daphnia magna)
--------------	-------------------------

EC50 (72 hr)	674.7 mg/l (Desmodesmus subspicatus)
--------------	--------------------------------------

LC50 (48 hr)	44 mg/l (Daphnia magna)
--------------	-------------------------

LC50 (96 hr)	18 mg/l (Pimephales promelas)
--------------	-------------------------------

NOEC (72 hr)	200 mg/l (Desmodesmus subspicatus)
--------------	------------------------------------

##### 108-65-6 2-methoxy-1-methylethyl acetate

EC50 (48 hr)	>100 mg/l (Crustacea)
--------------	-----------------------

EC50 (72 hr)	>100 mg/l (Algae)
--------------	-------------------

LC50 (96 hr)	>100 mg/l (Fish)
--------------	------------------

NOEC	100 mg/l (Crustacea)
------	----------------------

	>10 mg/l (Fish)
--	-----------------

##### 1330-20-7 xylene

CE50	10 mg/l (Fish) (72h)
------	----------------------

EC50 (48 hr)	7.4 mg/l (Daphnia magna)
--------------	--------------------------

LC50 (96 hr)	3.77-13.5 mg/l (Fish)
--------------	-----------------------

##### 868-77-9 2-hydroxyethyl methacrylate

EC50	>3,000 mg/l (Pseudomonas fluorescens) (16 hr)
------	---

EC50 (48 hr)	380 mg/l (Daphnia magna)
--------------	--------------------------

EC50 (72 hr)	836 mg/l (Selenastrum capricornutum)
--------------	--------------------------------------

LC50 (96 hr)	>100 mg/l (Fish) (ORYZLAS LATIPES)
--------------	------------------------------------

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

**Trade name: HS Clearcoat Anti-scratch**



(Contd. of page 7)

- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.  
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.  
Harmful to aquatic organisms

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |                             |
|---|-----------------------------|
| <b>14.1 UN number or ID number</b>  |                             |
| · ADR, IMDG, IATA   | UN1263                      |
| <b>14.2 UN proper shipping name</b>   |                             |
| · ADR   | 1263 PAINT                  |
| · IMDG, IATA  | PAINT                       |
| <b>14.3 Transport hazard class(es)</b>  |                             |
| · ADR   |                             |
|  |                             |
| · Class   | 3 (F1) Flammable liquids.   |
| · Label   | 3                           |
|   |                             |
| · IMDG, IATA  |                             |
|  |                             |
| · Class   | 3 Flammable liquids.        |
| · Label   | 3                           |
| <b>14.4 Packing group</b>   |                             |
| · ADR, IMDG, IATA   | III                         |
| <b>14.5 Environmental hazards:</b>  |                             |
| · Marine pollutant:   | No                          |
| <b>14.6 Special precautions for user</b>  | Warning: Flammable liquids. |
| · Kemler Number:  | 30                          |
| · EMS Number:   | F-E, S-E                    |
| · Stowage Category  | A                           |
| <b>14.7 Maritime transport in bulk according to IMO instruments</b>                 | Not applicable.             |
| <b>Transport/Additional information:</b>  |                             |
|   |                             |
| · ADR   |                             |
| · Limited quantities (LQ)   | 5L                          |

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

**Trade name: HS Clearcoat Anti-scratch**

(Contd. of page 8)

· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **National regulations**
- **Technical instructions (air):**

Class	Share in %
NK	31.0

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing data specification sheet:** Environment protection department

- **Abbreviations and acronyms:**

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 82 (replaces version 81)

Revision: 18.01.2023

**Trade name: HS Clearcoat Anti-scratch**

(Contd. of page 9)

*Flam. Liq. 3: Flammable liquids – Category 3*  
*Acute Tox. 4: Acute toxicity – Category 4*  
*Skin Irrit. 2: Skin corrosion/irritation – Category 2*  
*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*  
*Skin Sens. 1: Skin sensitisation – Category 1*  
*Skin Sens. 1A: Skin sensitisation – Category 1A*  
*Muta. 2: Germ cell mutagenicity – Category 2*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*  
*Asp. Tox. 1: Aspiration hazard – Category 1*  
*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*  
*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*  
*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*  
*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**Data compared to the previous version altered. \***

GB