

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Body Finish Paint Beige**

Article number: 85989

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture **Paint**

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



health hazard

STOT RE 2

H373 May cause damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word **Danger**

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 1)

Hazard-determining components of labelling:

Acetone

Reaction mass of ethylbenzene and xylene

Hydrocarbon, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%)

Butanone

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	Dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	Propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	5-10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	Butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	5-10%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbon, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	5-10%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	<3%
CAS: 13463-67-7 EINECS: 236-675-5	Titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] substance with a Community workplace exposure limit	<3%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119486773-24	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335; STOT SE 3, H336	<3%

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 2)

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation** In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing** In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
Use fire fighting measures that suit the environment.
CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** Formation of poisonous gases during heating or in fires.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Wear self-contained breathing apparatus.
Put on breathing apparatus.
- **Additional information**
Cool endangered containers with water spray jet.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow to enter drainage system, surface or ground water.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle container with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on flames or red-hot objects.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities**Storage****Requirements to be met by storerooms and containers:**

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.**Further information about storage conditions:**

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Storage class 2 B**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:****115-10-6 Dimethyl ether**

WEL Short-term value: 958 mg/m³, 500 ppm
 Long-term value: 766 mg/m³, 400 ppm

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
 Long-term value: 1210 mg/m³, 500 ppm

67-63-0 Propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
 Long-term value: 999 mg/m³, 400 ppm

78-93-3 Butanone

WEL Short-term value: 899 mg/m³, 300 ppm
 Long-term value: 600 mg/m³, 200 ppm
 Sk, BMGV

Reaction mass of ethylbenzene and xylene

WEL Short-term value: 441 mg/m³, 100 ppm
 Long-term value: 220 mg/m³, 50 ppm
 Sk, BMGV

13463-67-7 Titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

WEL Long-term value: 10* 4** mg/m³
 *total inhalable **respirable

Regulatory information WEL: EH40/2020**DNELs****115-10-6 Dimethyl ether**

Inhalative Long term systemic effect 1,894 mg/m³ (Worker)

67-64-1 Acetone

Dermal Long term systemic effect 186 mg/kg bw/day (Worker)
 Inhalative Long term systemic effect 1,210 mg/m³ (Worker)
 Acute local effect 2,420 mg/m³ (Worker)

67-63-0 Propan-2-ol

Oral Long term systemic effect 26 mg/kg/day (Consumer)
 Dermal Long term systemic effect 319 mg/kg/day (Consumer)
 888 mg/kg bw/day (Worker)
 Inhalative Long term systemic effect 89 mg/m³ (Consumer)
 500 mg/m³ (Worker)

78-93-3 Butanone

Dermal Long term systemic effect 1,161 mg/kg bw/day (Worker)
 Inhalative Long term systemic effect 600 mg/m³ (Worker)

Hydrocarbon, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%)

Dermal Long term systemic effect 44 mg/kg bw/day (Worker)
 Inhalative Long term systemic effect 330 mg/m³ (Worker)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 4)

Reaction mass of ethylbenzene and xylene

Dermal	Long term systemic effect	180 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	77 mg/m ³ (Worker)
	Acute systemic effect	289 mg/m ³ (Worker)

100-41-4 Ethylbenzene

Dermal	Long term systemic effect	180 mg/kg/day (Worker)
Inhalative	Acute local effect	293 mg/m ³ (Worker)
	Long term local effect	77 mg/m ³ (Worker)

64742-95-6 Hydrocarbons, C9, aromatics

Dermal	Long term systemic effect	25 mg/kg/day (Worker)
Inhalative	Long term systemic effect	150 mg/m ³ (Worker)

PNECs**115-10-6 Dimethyl ether**

PNEC	0.155 mg/l (Aqua (freshwater))
	1,549 mg/l (Aqua (intermittent))
	0.016 mg/l (Aqua (marine water))
	0.681 mg/l (Freshwater sediment)
	0.069 mg/l (Marine water sediment)
	0.045 mg/l (Soil)

67-64-1 Acetone

PNEC	10.6 mg/l (Aqua (freshwater))
	21 mg/l (Aqua (intermittent))
	1.06 mg/l (Aqua (marine water))
	30.4 mg/kg (Freshwater sediment)
	3.04 mg/kg (Marine water sediment)
	29.5 mg/kg (Soil)

67-63-0 Propan-2-ol

PNEC	140.9 mg/l (Aqua (freshwater))
	140.9 mg/l (Aqua (intermittent))
	140.9 mg/l (Aqua (marine water))
	552 mg/kg (Freshwater sediment)
	552 mg/kg (Marine water sediment)
	2,251 mg/l (Sewage treatment plant) (Assessment factor 1)
	28 mg/kg (Soil)

Reaction mass of ethylbenzene and xylene

PNEC	0.327 mg/l (Aqua (freshwater))
	0.327 mg/l (Aqua (marine water))
	12.46 mg/l (Freshwater sediment)
	12.46 mg/l (Marine water sediment)
	6.58 mg/l (Sewage treatment plant)
	2.31 (Soil)

100-41-4 Ethylbenzene

PNEC	0.1 mg/l (Aqua (freshwater))
	0.1 mg/l (Aqua (intermittent))
	0.1 mg/l (Aqua (marine water))

13463-67-7 Titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

PNEC	0.184 mg/l (Aqua (freshwater))
	0.193 mg/l (Aqua (intermittent))
	0.0184 mg/l (Aqua (marine water))
	1,000 mg/kg (Freshwater sediment)
	100 mg/kg (Marine water sediment)
	100 mg/l (Sewage treatment plant)
	100 mg/kg (Soil)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 5)

Ingredients with biological limit values:**78-93-3 Butanone**

BMGV 70 µmol/L
 Medium: urine
 Sampling time: post shift
 Parameter: butan-2-one

Reaction mass of ethylbenzene and xylene

BMGV 650 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: methyl hippuric acid

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
 Take off immediately all contaminated clothing
 Wash hands during breaks and at the end of the work.
 Store protective clothing separately.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.

Breathing equipment:

Only during spraying without adequate removal by suction.
 Filter AX / P (EN 14387)

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Wear suitable gloves tested to EN 374
 Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Safety glasses (EN 166)

Body protection: Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Physical state**

Aerosol

Colour:

Beige

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

55.8-56.6 °C

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 6)

· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	0.6 Vol %
· Upper:	18.6 Vol %
· Flash point:	Not applicable, as aerosol
· Ignition temperature:	235 °C
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible / difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	5200 hPa
· Density and/or relative density	
· Density at 20 °C	0.83 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	691 g/l VOC
· Solids content:	16.8%
· Change in condition	
· Evaporation rate	Not applicable.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 7)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

67-64-1 Acetone

Oral	LD50	5,800 mg/kg (Rat)
Dermal	LD50	20,000 mg/kg (Rabbit)

67-63-0 Propan-2-ol

Oral	LD50	5,840 mg/kg (Rat)
Dermal	LD50	13,400 mg/kg (Rabbit)

78-93-3 Butanone

Oral	LD50	3,300 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rabbit)

Hydrocarbon, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%)

Oral	LD50	>5,000 mg/kg (RAT)
Dermal	LD50	>3,160 mg/kg (Rabbit)
	IC50	4.6-10 (Algae)

Reaction mass of ethylbenzene and xylene

Oral	LD50	>5,840 mg/kg (Rat)
Dermal	LD50	>2,920 mg/kg (Rabbit)
Inhalative	LC50 (4 hr)	>25 mg/l (Rat)

100-41-4 Ethylbenzene

Oral	LD50	3,500 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rabbit)

13463-67-7 Titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Oral	LD50	>20,000 mg/kg (Rat)
Dermal	LD50	>10,000 mg/kg (rbt)
	ErC 50	61 mg/l (Algae) (EPA 600/9-78-018, 72 hr)

64742-95-6 Hydrocarbons, C9, aromatics

Oral	LD50	>6,800 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (Rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to the hearing organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

78-93-3 Butanone

List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

115-10-6 Dimethyl ether

EC50 (48 hr)	>4,000 mg/l (Daphnia magna)
EL50 (48 hr)	4,001 mg/l (Daphnia magna)
LC50 (48 hr)	755,549 mg/l (Daphnia magna)
LC50 (96 hr)	154.9 mg/l (Algae)
	4,001 mg/l (Poecilia reticulata)

67-64-1 Acetone

EC50	61,150 mg/l (Activated sludge) (30 mins)
------	--

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 8)

EC50 (48 hr)	39 mg/l (Daphnia magna)
LC50 (96 hr)	8,300 mg/l (Fish)
	5,540 mg/l (Oncorhynchus mykiss)
NOEC (28 days)	2,212 mg/l (Daphnia magna)
67-63-0 Propan-2-ol	
EC50 (48 hr)	13,299 mg/l (Daphnia magna)
LC50 (24 hr)	9,714 mg/l (Daphnia magna)
LC50 (96 hr)	4,200 mg/l (FSH) (dynamic)
	9,640 mg/l (Pimephales promelas)
LOEC (8 days)	1,000 mg/l (Algae)
78-93-3 Butanone	
EC50 (48 hr)	308 mg/l (Daphnia magna)
LC50 (96 hr)	2,993 mg/l (Pimephales promelas)
Hydrocarbon, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%)	
EC50 (48 hr)	<22 mg/l (Daphnia magna)
EL50	10-22 (Daphnia magna) (48 Hr)
	4.6-10 (Pseudokirchneriella subcapitata) (72 Hr)
LC50 (96 hr)	<30 mg/l (Oncorhynchus mykiss)
LL50 (96 hr)	10-30 mg/l (Oncorhynchus mykiss)
LOEC (21 days)	0.203 mg/l (Daphnia magna)
NOEC (21 days)	0.097 mg/l (Daphnia magna)
NOELR	1 mg/l (Pseudokirchneriella subcapitata) (72 Hr)
Reaction mass of ethylbenzene and xylene	
EC50 (48 hr)	3.2-9.5 mg/l (Daphnia magna)
LC50 (96 hr)	8.9-16.4 mg/l (Pimephales promelas)
NOEC (72 hr)	0.44 mg/l (Algae)
NOEC	1.3 mg/l (Fish)
NOEC (7 days)	0.96 mg/l (Daphnia magna)
100-41-4 Ethylbenzene	
EC50	>100 mg/l (Daphnia magna)
LC50 (96 hr)	>10 mg/l (Fish)
13463-67-7 Titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	
LC50 (48 hr)	5.5 mg/l (Crustacea)
LC50 (96 hr)	>100 mg/l (Oncorhynchus mykiss) (= OECD 203)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)



Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 9)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Kemler Number:	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 10)

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations**
- **Technical instructions (air):**

Class	Share in %
NK	58.0

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H220 Extremely flammable gas.
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H280 Contains gas under pressure; may explode if heated.
 - H304 May be fatal if swallowed and enters airways.
 - H312 Harmful in contact with skin.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H372 Causes damage to organs through prolonged or repeated exposure.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H411 Toxic to aquatic life with long lasting effects.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
- **Department issuing data specification sheet:** Environment protection department
- **Abbreviations and acronyms:**
 - RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (UK REACH)
 - PNEC: Predicted No-Effect Concentration (UK REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Gas 1A: Flammable gases – Category 1A
 - Aerosol 1: Aerosols – Category 1
 - : Aerosols – Category 3
 - Press. Gas (Comp.): Gases under pressure – Compressed gas
 - Flam. Liq. 2: Flammable liquids – Category 2
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 12)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 91 (replaces version 90)

Revision: 18.01.2023

Trade name: Body Finish Paint Beige

(Contd. of page 11)

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Data compared to the previous version altered. *

GB