

Page 1/7

Revision: 11.01.2023

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 74 (replaces version 73)

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: Underbody Wax Black
- · Article number: 86156
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

· Application of the substance / the mixture

Surface protection Anti-corrosion additive

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd Forsyth House Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

**KY11 8US** 

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

#### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 2)

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 74 (replaces version 73) Revision: 11.01.2023

Trade name: Underbody Wax Black

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. of page 1)

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

٠ ا	Dan	aei	rous	com	noa	ents:
-----	-----	-----	------	-----	-----	-------

zangereae compensation		
		25-50%
Reg.nr.: 01-2119463258-33	🊸 Flam. Liq. 3, H226; 🗞 Asp. Tox. 1, H304; 🗘 STOT SE 3, H336	
CAS: 61789-77-3	Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides	<1%
EINECS: 263-087-6	Skin Corr. 1B, H314; 🌢 Aquatic Acute 1, H400; Aquatic Chronic 2, H411; 🕚 Acute Tox. 4, H302	
Reg.nr.: 01-2119486994-16		

#### Additional information

Note P is applicable for the product on one or more of its components. Benzene concentration is <0.1% (w/w%) For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- · After inhalation Take affected persons into the open air and position comfortably
- · After skin contact If skin irritation continues, consult a doctor.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents CO2, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 3)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 74 (replaces version 73) Revision: 11.01.2023

Trade name: Underbody Wax Black

(Contd. of page 2)

#### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

Prevent formation of aerosols.

#### · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Storage
- Requirements to be met by storerooms and containers: Store in cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Protect from heat and direct sunlight.

Store container in a well ventilated position.

Store in cool, dry conditions in well sealed containers.

- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

#### DNELs

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Dermal Long term systemic effect 208 mg/kg bw/dy (Worker)
Inhalative Long term systemic effect 871 mg/m3 (Worker)

Additional information: The lists that were valid during the compilation were used as basis.

#### 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures Wash hands during breaks and at the end of the work.
- · Breathing equipment:

Filter A (EN 14387)

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.12 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 74 (replaces version 73) Revision: 11.01.2023

Trade name: Underbody Wax Black

(Contd. of page 3)

#### · Eye/face protection



Tightly sealed safety glasses. (EN 166)

Body protection: Protective work clothing (EN-13034/6)

#### SECTION 9: Physical and chemical properties

o. i illioilliation on pasic priysical and chellical propertic	9.1 Information on	basic ph	vsical and o	chemical p	roperties
--	--------------------	----------	--------------	------------	-----------

General Information

Physical state
Colour:
Odour:
Characteristic

Odour threshold:

Melting point/freezing point:

Boiling point or initial boiling point and boiling range

130 °C

Flammability Flammable.

Lower and upper explosion limit

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

· Flash point: 37 °C (DIN 53213) · Ignition temperature: >200 °C

Decomposition temperature: Not determined.

· **pH** Mixture is non-polar/aprotic.

Viscosity:

\* Kinematic viscosity Not determined.

dynamic at 20 °C: 350 mPas

Solubility

Water: Fully miscible
 Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 3 hPa

Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 Not determined.
 Not determined.

9.2 Other information

· Appearance:

Form: Aerosol

Important information on protection of health and

environment, and on safety.

Self-inflammability: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/steam

mixtures is possible.

· Solvent content:

 Organic solvents:
 424 g/l VOC

 Solids content:
 50 % (DIN 53216)

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

• Flammable liquids Flammable liquid and vapour.

· Flammable solids Void
· Self-reactive substances and mixtures Void
· Pyrophoric liquids Void

(Contd. on page 5)

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 74 (replaces version 73) Revision: 11.01.2023

Trade name: Underbody Wax Black

(Contd. of page 4)

Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamma	ble gases
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

#### **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Oral LD50 >5,000 mg/kg (Rat)

Dermal LD50 >3,000 mg/kg (Rabbit)

- STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

Aquatic toxicity:

# Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

EL50 (72 hr) >1,000 mg/l (Pseudokirchneriella subcapitata)

ELO (48 hr) 1,000 mg/l (Daphnia magna)

LL50 (96 hr) >1,000 mg/l (Oncorhynchus mykiss)

NOELR 100 mg/l (Pseudokirchneriella subcapitata) (72 hrs)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- \* 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

(Contd. on page 6)

# according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 74 (replaces version 73) Revision: 11.01.2023

Trade name: Underbody Wax Black

Danger to drinking water if even extremely small quantities leak into soil.

(Contd. of page 5)

### SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- \* Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN1139
14.2 UN proper shipping name ADR IMDG, IATA	1139 COATING SOLUTION COATING SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids. F-E, <u>S-E</u> A
14.7 Maritime transport in bulk according	a to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR Remarks:	Void according to 2.2.3.1.5
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1139 COATING SOLUTION, 3

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 7)

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 74 (replaces version 73) Revision: 11.01.2023

Trade name: Underbody Wax Black

(Contd. of page 6)

- · National regulations
- · Water hazard class: Water danger class 3 (Self-assessment): extremely hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

#### · Department issuing data specification sheet: Environment protection department

#### Abbreviations and acronyms:

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

PB1: Persistent, Bioaccumulative and Toxic VPVB: very Persistent and very Bioaccumulative Flam. Lig. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 18: Skin corrosion/irritation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Data compared to the previous version altered. \*