

Page 1/9

Revision: 12.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 42 (replaces version 41)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: DPF Cleaner Foam
- · Article number: 86547
- 1.2 Relevant identified uses of the substance or mixture and uses advised against FOR PROFESSIONAL AND INDUSTRIAL USE ONLY
- · Application of the substance / the mixture Cleaning agent / Cleaner
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KENT (United Kingdom) Ltd Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079 SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms





GHS02

GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

2-aminoethanol

Alcohol Ethoxylate (C9-11)

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 42 (replaces version 41) Revision: 12.01.2023

Trade name: DPF Cleaner Foam

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P280 Wear eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsina.

Immediately call a POISON CENTER/doctor. P310

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· Description: Mixture of the substances listed below with harmless additions.

Dangerous components	D:	
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	10-25%
CAS: 74-98-6		5-10%
CAS: 106-97-8 butane, pure 5- EINECS: 203-448-7 Reg.nr.: 01-2119474691-32		5-10%
CAS: 141-43-5 EINECS: 205-483-3 Reg.nr.: 01-2119486455-28 Z-aminoethanol Skin Corr. 1B, H314; ↑ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Aquatic Chronic 3, H412 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %		<5%
CAS: 7320-34-5 tetrapotassium pyrophosphate		<3%
CAS: 68439-45-2 Polymer	Alcohol Ethoxylate (C9-11) © Eye Dam. 1, H318; O Acute Tox. 4, H302	<3%
Regulation (EC) No 648	/2004 on detergents / Labelling for contents	
Aliphatic hydrocarbons		≥5 - <15%
Non-ionic surfactants, Phosp	phates, (R)-p-mentha-1,8-diene	<5%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information Instantly remove any clothing soiled by the product.
- After inhalation In case of unconsciousness bring patient into stable side position for transport.
- After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing Drink copious amounts of water and provide fresh air. Instantly call for doctor.
- * 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 42 (replaces version 41) Revision: 12.01.2023

Trade name: DPF Cleaner Foam

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- Additional information Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter drainage system, surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Protect from heat and direct sunlight.

Store container in a well ventilated position.

- · **Storage class** 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm

Sk

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 42 (replaces version 41)

Trade name: DPF Cleaner Foam

Printing date 23.01.2023

(Contd. of page 3)

Revision: 12.01.2023

Regulatory Information V	NEL: EH40/2020
·DNELs	

34590-94-8 Dipropylene glycol monomethyl ether		
Dermal	Long term systemic effect	283 mg/kg/day (Worker)
Inhalative	Long term systemic effect	308 mg/m3 (Worker)
141-43-5 2-aminoethanol		

Dermal	Long term systemic effect	1 mg/kg bw/d (Worker)
Inhalative	Long term systemic effect	3.3 mg/m³ (Worker)
	Long term systemic effect Long term systemic effect Long term local effect	3.3 mg/m³ (Worker)

7320-34-5 tetrapotassium pyrophosphate

Inhalative Long term systemic effect 2.79 mg/m³ (Worker)

PNECs

34590-94-8 Dipropylene glycol monomethyl ether

PNEC 19 mg/l (Aqua (freshwater))

190 mg/l (Aqua (intermittent))

19 mg/l (Aqua (marine water))

70.2 mg/kg (Freshwater sediment)

7.02 mg/kg (Marine water sediment)

4,168 mg/l (Sewage treatment plant)

2.74 mg/kg (Soil)

141-43-5 2-aminoethanol

PNEC 0.085 mg/l (Aqua (freshwater))

0.025 mg/l (Aqua (intermittent))

0.0085 mg/l. (Aqua (marine water))

0.425 mg/kg (Freshwater sediment)

0.0425 mg/kg (Marine water sediment)

100 mg/l (Sewage treatment plant)

0.035 mg/kg (Soil)

7320-34-5 tetrapotassium pyrophosphate

PNEC 0.05 mg/l (Aqua (freshwater))

0.005 mg/l (Aqua (marine water))

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

Only during spraying without adequate removal by suction.

Filter A / P2 (EN 14387)

AX P2 (EN 14387)

· Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 42 (replaces version 41) Revision: 12.01.2023

Trade name: DPF Cleaner Foam

(Contd. of page 4)

· Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Safety glasses (EN 166)

Body protection: Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Aeroso

• Colour: According to product specification • Odour: According to product specification Characteristic

Odour threshold: Not determined.

• Melting point/freezing point:

Not determined.

Not determined.

Boiling point or initial boiling point and boiling range Not applicable, as aerosol Flammability Not applicable.

· Flammability · Lower and upper explosion limit

Lower: 1.1 Vol %

Upper: 14.0 Vol %

Flash point: Not applicable, as aerosol

· Ignition temperature: 270 °C
· Decomposition temperature: Not determined.

pH at 20 °C 1

Viscosity:

Kinematic viscosity
 dynamic:
 Solubility

Not determined.
Not determined.

• Water: Not miscible / difficult to mix

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 Not determined.
 23 hPa

Density and/or relative density

Density at 20 °C
Relative density
Not determined.
Vapour density
Not determined.

9.2 Other information

Appearance:

Form: Aerosol

· Important information on protection of health and

environment, and on safety.

Self-inflammability: Product is not selfigniting.

· Explosive properties: Not determined.

Solvent content:

• Organic solvents: 264 g/l VOC • Solids content: 1%

Change in condition

· Evaporation rate Not applicable.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void

Aerosols Extremely flammable aerosol. Pressurised container: May burst if

heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 42 (replaces version 41) Revision: 12.01.2023

Trade name: DPF Cleaner Foam

		(Contd. of page 5)		
· Flammable solids	Void			
Self-reactive substances and mixtures	Void			
· Pyrophoric liquids	Void			
Pyrophoric solids	Void			
Self-heating substances and mixtures	Void			
· Substances and mixtures, which emit flammable gases				
in contact with water	Void			
· Oxidising liquids	Void			
· Oxidising solids	Void			
Organic peroxides	Void			
· Corrosive to metals	Void			
Desensitised explosives	Void			

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid Heat. Hot surfaces. Sources of ignition. Flames.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:			
34590-94-	34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	5,135 mg/kg (Rat)	
Dermal	LD50	9,500 mg/kg (Rat)	
74-98-6 Pi	74-98-6 Propane liquefied		
	ErC 50	19.37 mg/l (Algae) (96 hr)	
106-97-8 L	106-97-8 butane, pure		
Inhalative	LC50 (4 hr)	658 mg/l (Rat)	
	ErC 50	19.37 mg/l (Algae) (96 hr)	
141-43-5 2	141-43-5 2-aminoethanol		
Oral	LD50	2,050 mg/kg (Rat)	
Dermal	LD50	1,000 mg/kg (rbt)	

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

12.1 TOXICILY		
· Aquatic toxicity:		
34590-94-8 Dipropylene glycol monomethyl ether		
EC50	1,919 mg/l (Daphnia magna)	
74-98-6 Propane liquefied		
EC50 (48 hr)	69.43 mg/l (Daphnia magna)	
LC50 (96 hr)	49.9 mg/l (Fish)	
	(Contd. on page 7)	

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 42 (replaces version 41) Revision: 12.01.2023

Trade name: DPF Cleaner Foam

	(Contd. of pa	age
106-97-8 butane		
EC50 (48 hr)	69.43 mg/l (Daphnia magna)	
LC50 (96 hr)	49.9 mg/l (Fish)	
141-43-5 2-amin	oethanol	
EC50 (24 hr)	140 mg/l (Daphnia magna) (OECD 202)	
EC50	>1,000 mg/l (Activated sludge) (OECD 209, aquatic)	
	110 mg/l (Pseudomonas Putida) (16 hr - DIN 38412 Part 8)	
EC50 (48 hr)	65 mg/l (Daphnia magna) (RL 84/449/EWG, C.2)	
EC50 (72 hr)	2.5 mg/l (Algae) (OECD 201)	
	22 mg/l (Algae (Scenedesmus subspicatus)) (RL 92/69/EWG, C.3)	
LC50 (96 hr)	170 mg/l (Fish)	
	150 mg/l (Oncorhynchus mykiss)	
	2,070 mg/l (Pimephales promelas)	
NOEC (21 days)	0.85 mg/l (Daphnia magna) (OECD 211)	
7320-34-5 tetrap	otassium pyrophosphate	
LC50	>750 ug/l (Fish)	
	>750 ug/l (Leuciscus Idus) (48 hour)	

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- DDT: N / " //
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- * 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

<u> </u>		
14.1 UN number or ID number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	

according to 1907/2006/EC, Article 31

Revision: 12.01.2023 Printing date 23.01.2023 Version number 42 (replaces version 41)

Trade name: DPF Cleaner Foam

(Contd. of page 7)

· 14.3 Transport hazard class(es)

· ADR



2 5F Gases. · Class Label

· IMDG, IATA



· Class 2.1 Gases. · Label

14.4 Packing group ADR, IMDG, IATA

Void

14.5 Environmental hazards:

· Marine pollutant: No

14.6 Special precautions for user Warning: Gases.

· Kemler Number: · EMS Number: F-D.S-U

· Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A.

For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for

division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Transport category Tunnel restriction code

· Limited quantities (LQ) Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS

(Contd. on page 9)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 42 (replaces version 41) Revision: 12.01.2023

Trade name: DPF Cleaner Foam

(Contd. of page 8)

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations
- · Technical instructions (air):

Class	Share in %
Wasser	50.0
NK	29.1

- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Department issuing data specification sheet: Environment protection department

Abbreviations and acronyms:

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols - Category 1

Action 1. Actions – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Data compared to the previous version altered. *