



# Rubber Guard

A heavy duty, coarse textured under-seal that protects against corrosion and stone chipping.



## Features

- Heavy bodied
- Unique blend of resins
- Easy aerosol application
- Excellent adhesion
- Does not contain bitumen
- Wide temperature range -40° C to +135° C
- Over paintable

## Benefits

- Excellent coverage, even with one coat
- Does not harden or crack
- Can be used anywhere
- Does not require primer
- No discoloring & no cracking
- Withstands extreme conditions
- Compatible with most paint systems

Part No.	Description	Packaging
50110	577ml	Aerosol

## Application

Rubber Guard is designed as an alternative for underbody sealants and stone chip coatings which have to be applied by air gun. Rubber Guard is able to give different styles of finish according to thickness of coat and distance sprayed from. It is particularly good at recreating the light stone chip finish found on the lower edge of sill & front panels on many vehicles. It is also good as a sealant for covering welding repairs and it withstands harsh treatments in wheel arches and underbody areas. For a safe over painting, apply several layers and allow to flash off in between.

## Instructions

1. Remove rust, dirt, oil and other contaminants. The surface must be clean and dry.
2. Shake vigorously until mixing ball breaks loose. Then shake for one minute. Repeat shake procedure after each one minute of spraying.
3. Hold can approximately 30 cm from surface and spray with a sweeping motion, building with light coats. Allow previous coat to flash off before applying new one.
4. After each use, clean valve by turning can upside down and spray until clear.
5. Clean off overspray with KENT's Acrysol (ABS).
6. If over painting, Rubber Guard must be fully dried before applying paint (minimum 2-3 hours, preferably overnight).



## Technical Information

<b>Part Number:</b>	50110
<b>Stock Code:</b>	SRU
<b>Description:</b>	Rubber Guard Aerosol
<b>Volume:</b>	577 ml
<b>Colour:</b>	Black
<b>Shelf Life:</b>	24 months
<b>Selling Unit:</b>	EA
<b>VOC:</b>	555 g/L
<b>Customs Tariff Code:</b>	3210 00 0000
<b>Coat depth:</b>	100-125 microns
<b>Wet on wet:</b>	No
<b>Operating Temperature:</b>	5 - 35°C
<b>Resin base:</b>	Synthetic Rubber
<b>Temperature Range:</b>	-40° C to +135° C
<b>Over-paintability:</b>	Yes, but product has to be fully cured (minimum 2-3 hours, preferably over night)



**SDS available on [www.kenteurope.com](http://www.kenteurope.com)**

### Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd

**Registered Office:** Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ  
All rights reserved.

**KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US**  
**Tel :** 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.  
For out of hours queries please **Fax** us on 01383 735829 or **Email:** [kentinfo.uk@kenteurope.com](mailto:kentinfo.uk@kenteurope.com)

Rev: 2/3/2017