



Anti Seize

KENT Anti Seize is a redemption and assembly paste, which containing very small copper particles in non-melting Bentone base grease together with very strong anti-corrosion and anti-oxidation inhibitors to provide protection against corrosion and seizure.



Features & Benefits

- Withstands extremes of temperature between -40° C and +1100° C
- Reduces noise caused by friction
- Reduces fretting corrosion and seizure – improves performance
- Does not readily wash off – lengthens part/vehicle life
- Will not be affected by acids, alkaline or salts

Part N°: 83972 - Anti-Seize

Applications

Anti-Seize protects motor parts, exhaust systems, battery poles and terminals. It also prevents seized bearings, rusted nuts and bolts and is ideal for reducing friction on brakes, bolts, glides, moving parts in couplings and connecting rods.

At elevated temperatures of 800-1000°C the product forms oxide deposits which are very effective in preventing seizure.

Applications

- * Lubricated bearings
- * Mechanical hoist, conveyor systems
- * Water pumps and generators
- * Fork lifts in refrigerated environments
- * Textile equipment

Instructions

1. Shake can well before each spraying.
2. Spray directly onto the area to be treated.



Technical Information

Part number: 83972

Description: Anti-Seize

Shelf life: 30 months

Selling Unit: Each

VOC 467 g/L

Customs Tariff code: 3405 30 00

SDS: yes

Colour: Copper

Consistency: Smooth Paste

Application temperature: 15-25 ° C

Water Resistance: Excellent

Base: Fine copper particles in Bentone Grease

Base Oil: Mineral

Consistency: NLGI Class 3 (DIN 51818)

Drop point None (ASTM D-566)

Worked Penetration (25 ° C and 60 strokes IP50) :

Recommended op temp range, ° C :-40 – 1100

Propellant: Propane/Butane

Density: 0,675g/ml (20 ° C),

Pressure: 3 bar (20 ° C),

Delivery rate: 1,7g/sec (20 ° C),



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US

Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.

For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenteurope.com

Rev: 7/3/2017