



Chain Lube 2

Chain Lube 2 is a high tack lubricant for use under conditions of heavy loads, and in dusty and contaminated environments and will reduce friction noises and general wear and tear of the chain.



Part N°: 84182 - Chain Lube 2 - 400ml

Features & Benefits

- Long term performance provides extended lubrication intervals - Increase longevity of chain
Very high adhesion to chain - does not fling
- Excellent capillary action - Easily penetrates areas with difficult access
- Contains extreme pressure and anti-wear additives - improved durability under heavily loaded applications
- Contains water repellent additives - Resistant to high pressure wash

Application

Chain Lube 2 is high quality, performance lubricant, formulated to deliver a longer lubricant life, higher temperature stability and better resistance to water.

Chain lube 2 sprays on and sets up like a grease to give continued protection and lubrication against rust and corrosion.

Contains water repellent additives and extreme pressure and anti-wear additives for improved durability under heavily loaded applications.

Instructions

1. Shake well before use.
2. Remove old lubricants and any surface contamination.
3. Spray in a well ventilated area from a distance of 15-20cm. Allow to penetrate.
4. Use the extension tube for difficult to reach areas.
5. Re-apply as necessary.



Technical Information

Part N°:	84182	Water Washout:	<1% Max ASTM D1264 at 38° C [Fully dried]
Description:	Chain lube 2	NLGI grade:	2
Shelf Life:	24 months	Penetration worked:	265-295 units
Selling Unit:	EA	Drop point:	>300°C
VOC:	497g/l	Density :	0.774g/ml
Tariff Code:	3409 99 10	Four ball test (welding):	400 kg IP239 weld load
SDS:	Yes	Corrosion test (EMCOR):	0 – 0
Size:	400ml	Cont op temp:	-50° C to +165° C.
Appearance:	Ivory white smooth grease		



SDS available on www.kenturope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US
Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.
For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenturope.com

Rev: 17/3/2017