

# No Edge Blending Tape & Flexi No Edge Blending Tape

Foamed masking tape.



### **Features & Benefits**

- Seamless blending from old to new paintwork avoids unnecessary rework
- Available in two versions to cover all applications
- Ideal for body swage lines (NEBT) and curved style lines/ panel edges (FNEBT)
- No paint edges
- Non stretch (NEBT)
- Absorbent

P/N	Product	S/C	Packaging
85387	No Edge Blending Tape	NEBT	Single roll dispensing box
86437	Flexi No Edge Blending Tape	FNEBT	Multiple roll dispensing box

# **Application**

**No Edge Blending Tape** is a foam combined with a crepe masking tape and a rubber based pressure sensitive adhesive. The product is designed for the masking of swage lines (like door departures) and panel edges to blend from old to new paintwork. NEBT assures a quick lay down, no residue on de-masking. Suitable for IR.

**Flexi No Edge Blending Tape** is a flexible foam with a rubber based pressure sensitive adhesive but without a crepe masking tape which gives this tape much more flexibility compared to NEBT. The product is designed for masking of curved style lines (like wheel arches) and panel edges to blend from old to new paintwork. FNEBT assures a quick lay down, no residue on de-masking.

#### Instructions

- 1. Apply the tape on the panel next to the swage line ensuring that edge is level with the panel bend, then push the tape to secure into place.
- 2. Mask the surrounding area as normal and spray the panel as normal.
- 3. Remove tape before or after drying, depending on preference.
- 4. Remove the masking material exposing a seamless transition between the old and new paintwork.
- 5. This will now result in a perfect blending of the paintwork along the swage line edge avoiding any unnecessary rework.



## **Technical Information**

No Edge Blending Tape:

Flexi No Edge Blending Tape:

Part number: 85387 Stock Code: NFBT

Size per roll: 20 mm x 5m

**Product Packaging:** 1 roll per box

Shelf life: 1 year (at room temp.)

**Custom Tariff Code:** 39 21 90 90

Thickness: 3 mm

Width: 20 mm (+/- 1mm)

Length: 5 m (+/- 0.1m)

Colour: White

Tensile strength: > 87.5 N/cm

Elongation at break: > 9%

Temperature Resistance: 150 °C (30-80 min. on

cooling after bake cycle)

Part number: 86437

Stock Code: **FNEBT** 

Size per roll: 15 mm x 5m

**Product Packaging:** 5 rolls per box

(5 \* 15 mm x 5 m)

25 m (+/- 0.5m)

Shelf life: 1 year (at room temp.)

**Custom Tariff Code:** 39 21 90 90

Thickness: 4 mm (+/- 0.5mm)

Width: 15 mm (+/- 2mm)

Length:

Colour: White

Tensile strength: min. 16 N/cm

Elongation at break: min. 250%

95 °C Temperature Resistance:



#### SDS available on www.kenteurope.com

#### Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd., or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd.

All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Way, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel: 0800 136925 or 01383 723344 between 08:30-17:30

Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383

735829 or Email: KENTsales.UK@kenteurope.com

REV: 24/10/2017