



Primer Shield Foam Masking Tape

Two foam masking products designed to radically improve efficiency for primer masking



85917 Primer Shield
85918 Primer Shield L

Features & Benefits

- Dramatically reduces process times
- Seals and protects from overspray
- Precise fingertip adjustment of masking position
- Easy to apply – self locating
- No primer build-up on Panel Edges

Applications

It is a specially developed non-adhesive foam extrusion, with a figure-of-eight profile, for the masking of gaps between panels. The product will self-locate into panel gaps and prevent paint build up on the panel edges or ingress past the panel gap. After masking the surrounding area's as normal, the correct length of Primer Shield strip is cut from the pack; the smaller profile is pushed into the gap to form an interference fit and then the strip is fingertip adjusted to give the correct protection. Only a quick check is required to ensure the strip is located firmly in all the gaps and that panel edges sit in the groove of the product. The product allows very fast masking of A post, B post, C post, bonnet, boot, petrol cap, sunroof and lights to body gaps. Finally, the Primer Shield can be removed after flash cure of the primer by simply pulling the strip out of the gap. The comparison between traditional methods of masking and the new Primer Shield product indicate significant savings in time, making the Bodyshop more efficient and **more profitable**.

The product is supplied as strips in a cardboard box dispenser:

Primer Shield 15mm x 21m (7 strips of 3m)

Primer Shield L 22mm x 15m (5 strips of 3m)

Primer Shield L is designed for larger vehicles (eg SUV's), bottom sills and hatchbacks



Technical Information

Part number: 85917 Primer Shield

85918 Primer Shield L

Description: Primer Shield Foam Masking Tape

Shelf life: One year @ 22C and 50% RH

Selling Unit: PCE

Product colour: White

Packaging: Box

Label codes: 33

Stock Code: PFT and PLFT

Customs Tariff Code: 3921 1310

SDS: no

Unit of measure: PCE

Thickness: 10mm x (15mm or 22mm)

Density: 30Kg/m³ +/- 4Kg/m³

Environmental: limited UV Resistance



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US

Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.

For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenteurope.com

Rev: 25/10/2017