



Aerosol Spray Paint

A range of General Purpose Acrylic based paints



- | | |
|----------|-------------|
| 86243 33 | Gloss Black |
| 86244 33 | Satin Black |
| 86245 33 | Matt Black |
| 86246 33 | Gloss White |

Features

- Excellent covering power
- Excellent durability
- Excellent resistance to sunlight and colour fade
- Excellent adhesion to primed surfaces

Benefits

- Spray can cover large area – cost efficient
- Good resistance to wear – long life
- Does not require touch up due to effects of fading
- Good consistent surface coating

Applications

Can be used on all types of metals and rigid plastic surfaces when used in conjunction with the appropriate primers.

On surfaces treated with unknown primers, or if the use of a primer isn't certain, it is advised to trial a test panel first.

Prepare the primed surface to be treated, ensuring freedom from dust, grime, greases, oils, etc.; use Acrysol or similar cleaner and dry thoroughly. If the primed surface needs flattening, use 1200 grade abrasive paper and then clean as above.

Instructions

1. Shake the can thoroughly for at least two minutes. Repeat shaking at regular intervals during use.
2. Apply lightly from a distance of 20-25 cm. Apply 2 to 3 light coats to achieve coverage. Leave 10 to 15 minutes drying between coats.
3. Allow to fully harden for at least 24 hours after application of final coating.
4. On completion of use, invert can and depress actuator for a few seconds to clear the nozzle.



Technical Information

Part number:	86243 Gloss Black GBSP 86244 Satin Black SBSP 86245 Matt Black MBSP 86246 Gloss White WSP	Volume	500ml
Shelf life:	24 Months	Customs Tariff Code:	3208 90 91
Selling Unit:	Each	SDS:	Yes
Packaging:	500ml Aerosol	VOC:	GB 651g/l; SB 656g/l MB 652g/l; GW 621g/l
Service Temperature:	up to 80°C	Specific Gravity:	0.94 to 1.09 g/ml
Colour:	Black = RAL 9005 (same shade, various degrees of gloss) White = RAL 9003	Viscosity:	up to 1,500 cPs
		Application Temperature:	15 to 25°C



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US
Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.
For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenteurope.com

Rev: 9/3/2017