



# Injector Release Agent

A powerful release agent for the removal of seized injectors.



## Features & Benefits

- Fast acting release of seized injectors – reduces amount of work and thus costs
- Very slow solvent evaporation – provides intensive penetration
- Slide-active PTFE particles – assists removal of the components
- Freezes the material down to -30 °C – faster acting
- 20 cm extension straw – easy application
- Free of acid and silicones – bodyshop safe

P/N	Product	S/C	Packaging
86313	Injector Release Agent	KIRA	500 ml aerosol & 20 cm extension straw

## Application

KENT Injector Release Agent enables a non-destructive removal of seized injectors from diesel engines and effectively removes carbon deposits, oil residues, gumming etc. The specific formulation of the active substances entails a cold shock down to -30 °C. This extreme cooling causes microcracks on the injector's sealing ring and permits the active agent, with its very slow evaporation solvent components, to penetrate faster and deeper. Existing rust crystals, moisture and any deposits will be infiltrated due to special additives. Glide-active PTFE particles ensure a good gliding property and ease the injector removal. KENT Injector Release Agent can also be used for the removal of seized spark plugs and glow plugs.

## Instructions

1. Shake well before use.
2. Remove coarse surface dirt accumulation mechanically, then spray liberally on the seat of the injector and allow to soak for approx. 30 - 45 minutes.
3. Repeat the procedure as required and remove loosened dirt by using compressed air and a cloth.
4. Remove parts with suitable tool.



## Technical Information

<b>Base:</b>	PTFE / hydrocarbon
<b>Consistency:</b>	Liquid
<b>Colour:</b>	Colourless, slightly cloudy
<b>Shelf life:</b>	36 months
<b>Custom tariff code:</b>	3403 19 90
<b>VOC:</b>	568 g/l

---

<b>Specific gravity:</b>	0.8 g/l
<b>Four ball weld :</b>	1500 – 1600 N
<b>Additives / thickener:</b>	PTFE as anti-friction additive; dewatering additive
<b>Temp resistance:</b>	
<b>Continuous:</b>	To 150 °C
<b>Temporary:</b>	To 250 °C



SDS available on [www.kenteurope.com](http://www.kenteurope.com)

### Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of name KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd.

**Registered Office:** Amber House,  
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ  
*All rights reserved*

**KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US** Tel : 0800 136925 or 01383 723344 between 08:30-17:30  
Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: [kentinfo.uk@kenteurope.com](mailto:kentinfo.uk@kenteurope.com)

REV: 12/05/2017