



# Spot Primer

A quick drying, universal aerosol primer suitable for small sanded-through spots.



## Features & Benefits

- Fast drying, excellent adhesion, easy sandability.
- Good filling properties, good flexibility, good hardness.
- Due to the use of zinc phosphate in KENT Spot Primer, it can be used directly on metal.
- KENT Spot Primer has good anticorrosion properties.
- KENT Spot Primer can also be used on polyester putties, topcoat, wash primers and fillers.
- KENT Spot Primer is ideal for small areas, such as sanded-through spots.
- KENT Spot Primer can be over painted with most modern paints, best results achieved if lightly sanded before applying top coat.

Part No.	Description	Packaging
86334	Black	400ml - aerosol
86335	Grey	400ml - aerosol
86336	White	400ml - aerosol

## Application

A quick-drying universal aerosol primer that has been developed to make small spot repairs on virtually any surface, easier and faster to carry out. It is highly cost-effective as paint waste is reduced and time is saved.

Application on sanded through spots on:

- Steel
- Existing finishes
- Wash primers and wash fillers
- Surfacer
- Glass Reinforced Polyester laminates
- Polyester bodyfillers
- Primer surfacer

## Instructions

1. Remove any surface contamination prior to the application of KENT Surfacer using Acrysol or Panel Degreaser (*where bodyfiller is exposed, avoid contact with water or waterborne degreaser!*)
2. Shake can for several minutes after the mixing ball has loosened.
3. Spray with a distance of approx. 25-30 cm, cross wise, 2 or 3 even coats.
5. Allow for a 3-5 minutes flash-off time between the coats, at 20°C.
6. Invert aerosol and depress nozzle after use for 2-3 seconds, to allow the propellant to clean the nozzle.
7. Allow 10-15 minutes at 20°C before sanding.
8. Sand slightly before application of the topcoat, with P500 grit dry or P1000 grit wet.
9. Recoat with a topcoat.



## Technical Information

**Part N°:** 86334 – 86335 – 86336  
**Colours:** Black – Grey – White  
**Stock Code:** SPBII – SPGII – SPWII  
**Shelf Life:** 18 months, unopened and stored in a dry place between 10& 25° C  
**Hazard info:** Irritant; Extremely Flammable  
**VOC:** 86334 – Black – 679 g/ l  
86335 – Grey – 672 g/ l  
86336 – White – 672 g/ l

**Film thickness:** 10-15 µ per coat

**Drying time:** at 20° C depending on thickness and ventilation:

Dust free: ca. 5-10 minutes

Sandable: ca. 10-15 minutes

Overpaintable: ca. 20 minutes

**VOC Markings:** 2004/42/IIB(e)(840)679, 2004/42/IIB(e)(840)672, 2004/42/IIB(e)(840)672



**SDS available on [www.kenturope.com](http://www.kenturope.com)**

### Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

**Registered Office:** Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ  
All rights reserved.

**KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US**

**Tel :** 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.

For out of hours queries please **Fax** us on 01383 735829 or **Email:** [kentinfo.uk@kenturope.com](mailto:kentinfo.uk@kenturope.com)

Rev: 2/3/2017