



Multi Seal Tape

An excellent alternative to liquid sealants. Instant leak sealing of trailer roof seams, rain gutters, flashing and vents, metal enclosures, skylights.



P/N
86386

S/C
KMST

Colour
Translucent

Dimensions
38 mm x 5 m

Features & benefits

- Adheres to many metals and plastics
- No drying time, immediately paintable
- No caulking gun needed, no waste of cartridges
- Accommodates to irregular surfaces, contours, edges, rivets and screw heads
- Looks neat and precise for an improved appearance
- No cracking or crumbling
- Over-paintable immediately after application
- Extreme weather resistance
- Excellent resistance to most industrial solvents
- Excellent resistance to abrasion and high pressure cleaning
- Stays flexible to compensate for vibration and thermal expansion/contraction

Applications

Trailer and caravan roofs, metal enclosures, skylights, awnings, trailer home roofs, metal storage buildings, vent stacks and vent windows, gutters and downspouts, skylights, outdoor sign/display, leak patching and repairs.

Instructions

1. Ensure surface is clean of any contaminants. Use Soft Surface Cleaner or Acrysol and allow to dry.
2. Lay tape down so that it covers all areas meant to be sealed. Press tape with a soft roller (such as a medium nap paint roller). Remove release liner (file cleaning brush can help). Press tape again insisting on the most irregular parts (rivets, screw heads, etc.)
3. In order to provide a robust seal, the tape must cover all points of water intrusion (e.g. rivets). If required, it is possible to overlap KMST onto itself. The tapes should overlap at least 2 cm. Firm pressure should be applied to all points of overlap between the two tapes to join the adhesives and create a robust seal.



Technical Information

Colour	Milky/Translucent
Adhesive	Pressure sensitive acrylic
Carrier	Ionomer acrylic film
Liner	Polyester
Length	5 m
Width	38 mm
Thickness	1 mm
Initial tack	87.5 N/25mm

90° Peel Adhesion 100 N/25mm

Tensile Strength 37.5 N/25mm

NB: The tape generally reaches full bond strength after 24 hours but provides a seal immediately.

Elongation at break 350%

UV resistance Excellent

Moisture resistance Excellent

Thermal shock resistance Excellent

High pressure water resistance Excellent

Chemical resistance Very good

Temperature resistance -30°C to +90°C (+150°C for 1 hour)

Application temperature +10°C to +30°C

Shelf life 12 months at room temperature

Customs Tariff Code 392050



SDS available on www.kenturope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US

Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.

For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenturope.com

Rev: 24/05/2017