



23.01.2023

Kit components

Product code	Description
--------------	-------------

86184	FAST BLACK PRIMER FILLER EVO KIT
--------------	---

Components:

85814	Self Guide Primer Filler EVO Black
-------	------------------------------------

86181	Self Guide Primer Filler EVO FAST HARDENER
-------	--

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Self Guide Primer Filler EVO Black**

Article number: 85814

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture

Priming

Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07

Signal word Warning

Hazard-determining components of labelling:

n-butyl acetate

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO Black

(Contd. of page 1)

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards
Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<5%
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-ethoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	<5%

Additional information

Note P is applicable for the product on one or more of its components. Benzene concentration is <0.1% (w/w%)

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact Instantly remove any clothing soiled by the product.
- After eye contact Rinse opened eye for several minutes under running water.
- After swallowing In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing agents CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

 Nitrogen oxides (NO_x)

Formation of poisonous gases during heating or in fires.

5.3 Advice for firefighters
Protective equipment:

- Do not inhale explosion gases or combustion gases.
- Wear self-contained breathing apparatus.
- Wear full protective suit.
- Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO Black

(Contd. of page 2)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Keep away from ignition sources
- Ensure adequate ventilation
- Put on breathing apparatus.
- Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

- Do not allow to enter drainage system, surface or ground water.
- Prevent material from reaching sewage system, holes and cellars.

6.3 Methods and material for containment and cleaning up:

- Send for recovery or disposal in suitable containers.
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose of contaminated material as waste according to item 13.
- Ensure adequate ventilation.

6.4 Reference to other sections

- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- Keep away from heat and direct sunlight.
- Information about protection against explosions and fires:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

- Store in cool location.
- Store only in the original container.
- Information about storage in one common storage facility:** Do not store together with oxidising and acidic materials.
- Further information about storage conditions:**
- Keep container tightly sealed.
- Protect from heat and direct sunlight.
- Store container in a well ventilated position.
- <25°C

Storage class 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

Regulatory information WEL: EH40/2020

DNELs

123-86-4 n-butyl acetate

Dermal	Acute systemic effect	11 mg/kg bw/day (Worker)
	Long term systemic effect	11 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	300 mg/m ³ (Worker)
	Acute local effect	600 mg/m ³ (Worker)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO Black

(Contd. of page 3)

	Long term local effect	300 mg/m ³ (Worker)
	Acute systemic effect	600 mg/m ³ (Worker)
1330-20-7 xylene		
Dermal	Long term local effect	3,182 mg/kg/day (Worker)
Inhalative	Acute local effect	442 mg/m ³ (Worker)
	Long term local effect	221 mg/m ³ (Worker)
100-41-4 Ethylbenzene		
Dermal	Long term systemic effect	180 mg/kg/day (Worker)
Inhalative	Acute local effect	293 mg/m ³ (Worker)
	Long term local effect	77 mg/m ³ (Worker)
64742-95-6 Hydrocarbons, C9, aromatics		
Dermal	Long term systemic effect	25 mg/kg/day (Worker)
Inhalative	Long term systemic effect	150 mg/m ³ (Worker)

· PNECs**123-86-4 n-butyl acetate**

PNEC	0.18 mg/l (Aqua (freshwater))
	0.36 mg/ml (Aqua (intermittent))
	0.018 mg/ml (Aqua (marine water))
	0.981 mg/kg (Freshwater sediment)
	0.0981 mg/kg (Marine water sediment)
	35.6 mg/l (Sewage treatment plant)
	0.09 mg/kg (Soil)

1330-20-7 xylene

PNEC	0.327 mg/l (Aqua (freshwater))
	0.327 mg/l (Aqua (marine water))
	12.46 mg/l (Freshwater sediment)
	12.46 mg/l (Marine water sediment)
	6.58 mg/l (Sewage treatment plant)
	2.31 mg/kg (Soil)

100-41-4 Ethylbenzene

PNEC	0.1 mg/l (Aqua (freshwater))
	0.1 mg/l (Aqua (intermittent))
	0.1 mg/l (Aqua (marine water))

· Ingredients with biological limit values:**1330-20-7 xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
Wash hands during breaks and at the end of the work.
Do not inhale gases / fumes / aerosols.

· Breathing equipment:

Filter A (EN 141)

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO Black

(Contd. of page 4)

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection


Tightly sealed safety glasses. (EN 166)

Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties
General Information
Physical state

Fluid

Colour:

Black

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

Not determined

Flammability

Flammable.

Lower and upper explosion limit
Lower:

1.1 Vol %

Upper:

7.0 Vol %

Flash point:

25 °C (ASTM D-56)

Decomposition temperature:

Not determined.

pH

Mixture is non-soluble (in water).

Viscosity:
Kinematic viscosity at 20 °C

40s creep time (ISO 2431)

dynamic:

Not determined.

Solubility
Water:

Not miscible / difficult to mix

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure:

Not determined.

Density and/or relative density
Density at 20 °C
1.58 g/cm³
Relative density

Not determined.

Vapour density at 20 °C
3.66 g/cm³ (butyl acetate)
9.2 Other information
Appearance:
Form:

Viscous

Important information on protection of health and environment, and on safety.
Self-inflammability:

Product is not selfigniting.

Explosive properties:

Product is not explosive. However, formation of explosive air/steam mixtures is possible.

Solvent content:
Organic solvents:

480g/l VOC (RFU)

Change in condition
Evaporation rate

Not determined.

Information with regard to physical hazard classes
Explosives

Void

Flammable gases

Void

Aerosols

Void

Oxidising gases

Void

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO Black

(Contd. of page 5)

· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Stable at ambient temperature
To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:**
Strong acids and oxidizing agents
Alkalis
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide
Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

123-86-4 n-butyl acetate

Oral	LD50	14,000 mg/kg (Rat)
------	------	--------------------

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)

100-41-4 Ethylbenzene

Oral	LD50	3,500 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rabbit)

64742-95-6 Hydrocarbons, C9, aromatics

Oral	LD50	>6,800 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (Rabbit)

- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

GB
(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO Black

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

123-86-4 n-butyl acetate

EC50 (48 hr)	44 mg/l (Daphnia magna)
EC50 (72 hr)	674.7 mg/l (Desmodesmus subspicatus)
LC50 (48 hr)	44 mg/l (Daphnia magna)
LC50 (96 hr)	18 mg/l (Pimephales promelas)
NOEC (72 hr)	200 mg/l (Desmodesmus subspicatus)

1330-20-7 xylene

CE50	10 mg/l (Fish) (72h)
EC50 (48 hr)	7.4 mg/l (Daphnia magna)
LC50 (96 hr)	3.77-13.5 mg/l (Fish)

100-41-4 Ethylbenzene

EC50	>100 mg/l (Daphnia magna)
LC50 (96 hr)	>10 mg/l (Fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

· **ADR, IMDG, IATA** UN1263

14.2 UN proper shipping name

· **ADR** 1263 PAINT
· **IMDG, IATA** PAINT

14.3 Transport hazard class(es)

· **ADR**



· **Class** 3 (F1) Flammable liquids.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO Black

(Contd. of page 7)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations

· Technical instructions (air):

Class	Share in %
NK	29.5

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 69 (replaces version 68)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO Black

(Contd. of page 8)

H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing data specification sheet:** Environment protection department

· **Abbreviations and acronyms:**

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1

· **Data compared to the previous version altered.** *

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Self Guide Primer Filler EVO FAST HARDENER**

Article number: 86181

1.2 Relevant identified uses of the substance or mixture and uses advised against
FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Hardening agent / curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 1)

- **Signal word** Warning

- **Hazard-determining components of labelling:**

Aliphatic polyisocyanate
xylene
n-butyl acetate
hexamethylene diisocyanate

- **Hazard statements**

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/attention if you feel unwell.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.
Contains isocyanates. May produce an allergic reaction.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of the substances listed below with harmless additions.

- **Dangerous components:**

CAS: 28182-81-2 EC number: 931-274-8 Reg.nr.: 01-2119485796-17	Aliphatic polyisocyanate ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-15%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	5-10%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37	hexamethylene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	<0.25%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 2)

- **After inhalation**
Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing** Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)
Formation of poisonous gases during heating or in fires.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Wear self-contained breathing apparatus.
Wear full protective suit.
- **Additional information** Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow to enter drainage system, surface or ground water.
Prevent material from reaching sewage system, holes and cellars.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Keep away from heat and direct sunlight.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store in cool location.
- **Information about storage in one common storage facility:** Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed containers.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 3)

Protect from heat and direct sunlight.

15-25°C

· **Storage class 3**· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

822-06-0 hexamethylene diisocyanate

WEL	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

· **Regulatory information** WEL: EH40/2020

DNELs

28182-81-2 Aliphatic polyisocyanate

Inhalative	Acute local effect	1 mg/m ³ (Worker)
	Long term local effect	0.5 mg/m ³ (Worker)

123-86-4 n-butyl acetate

Dermal	Acute systemic effect	11 mg/kg bw/day (Worker)
	Long term systemic effect	11 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	300 mg/m ³ (Worker)
	Acute local effect	600 mg/m ³ (Worker)
	Long term local effect	300 mg/m ³ (Worker)
	Acute systemic effect	600 mg/m ³ (Worker)

1330-20-7 xylene

Dermal	Long term local effect	3,182 mg/kg/day (Worker)
Inhalative	Acute local effect	442 mg/m ³ (Worker)
	Long term local effect	221 mg/m ³ (Worker)

108-65-6 2-methoxy-1-methylethyl acetate

Dermal	Long term systemic effect	796 mg/kg/day (Worker)
Inhalative	Long term systemic effect	275 mg/m ³ (Worker)
	Long term local effect	550 mg/m ³ (Worker)

PNECs

28182-81-2 Aliphatic polyisocyanate

PNEC	0.127 mg/l (Aqua (freshwater))
	1.27 mg/l (Aqua (intermittent))
	0.0127 mg/l (Aqua (marine water))
	266,700 mg/kg (Freshwater sediment)
	26,670 mg/kg (Marine water sediment)
	38.3 mg/l (Sewage treatment plant)
	53,182 mg/kg (Soil)

123-86-4 n-butyl acetate

PNEC	0.18 mg/l (Aqua (freshwater))
	0.36 mg/ml (Aqua (intermittent))
	0.018 mg/ml (Aqua (marine water))

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 4)

	0.981 mg/kg (Freshwater sediment) 0.0981 mg/kg (Marine water sediment) 35.6 mg/l (Sewage treatment plant) 0.09 mg/kg (Soil)
1330-20-7 xylene	
PNEC	0.327 mg/l (Aqua (freshwater)) 0.327 mg/l (Aqua (marine water)) 12.46 mg/l (Freshwater sediment) 12.46 mg/l (Marine water sediment) 6.58 mg/l (Sewage treatment plant) 2.31 mg/kg (Soil)
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC	0.635 mg/l (Aqua (freshwater)) 1.27 mg/l (Aqua (intermittent)) 0.0127 mg/l (Aqua (marine water)) 26,670 mg/kg (Marine water sediment) 38.3 mg/l (Sewage treatment plant) 53,182 mg/kg (Soil)
822-06-0 hexamethylene diisocyanate	
PNEC	0.0774 mg/l (Aqua (freshwater)) 0.774 mg/l (Aqua (intermittent)) 0.00774 mg/l (Aqua (marine water)) 0.01334 mg/kg (Freshwater sediment) 0.001344 mg/kg (Marine water sediment) 8.42 mg/l (Sewage treatment plant) 0.0026 mg/kg (Soil)
Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
822-06-0 hexamethylene diisocyanate	
BMGV	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Filter A (EN 141)

· **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection**



Tightly sealed safety glasses. (EN 166)

- **Body protection:** Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Fluid

- **Colour:**

Colourless

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Not determined

- **Boiling point or initial boiling point and boiling range**

Not determined

- **Flammability**

Flammable.

- **Lower and upper explosion limit**

- **Lower:**

1.7 Vol %

- **Upper:**

7.6 Vol %

- **Flash point:**

27.5 °C (UNI EN ISO 3680:2005)

- **Ignition temperature:**

> 240 °C

- **Decomposition temperature:**

Not determined.

- **pH**

Mixture is non-soluble (in water).

- **Viscosity:**

- **Kinematic viscosity**

> 180 mm²/s

- **dynamic at 20 °C:**

>30 s (creep time ISO 2431)

- **Solubility**

- **Water:**

Not miscible / difficult to mix

- **Partition coefficient n-octanol/water (log value)**

Not determined.

- **Vapour pressure:**

Not determined.

- **Density and/or relative density**

- **Density at 20 °C**

0.990 g/cm³

- **Relative density**

Not determined.

- **Vapour density at 20 °C**

4.83 g/cm³ (Butyl acetate)

- **9.2 Other information**

- **Appearance:**

- **Form:**

Fluid

- **Important information on protection of health and environment, and on safety.**

- **Self-inflammability:**

Product is not selfigniting.

- **Explosive properties:**

Product is not explosive. However, formation of explosive air/steam mixtures is possible.

- **Change in condition**

- **Evaporation rate**

Not determined.

- **Information with regard to physical hazard classes**

- **Explosives**

Void

- **Flammable gases**

Void

- **Aerosols**

Void

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 6)

· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:**
Strong acids and oxidizing agents
Alkalis
Alcohols, amines, aqueous acids and alkalis
Water / humidity
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

28182-81-2 Aliphatic polyisocyanate		
Oral	LD50	>2,500 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
123-86-4 n-butyl acetate		
Oral	LD50	14,000 mg/kg (Rat)
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,500 mg/kg (Rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 7)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

28182-81-2 Aliphatic polyisocyanate

EC10	>100 /48 hr (Daphnia magna) (OECD 202)
EC50 (72 hr)	3,828 mg/l (Activated sludge) (OECD 209)
LC50 (96 hr)	>100 mg/l (Brachydanio rerio)

123-86-4 n-butyl acetate

EC50 (48 hr)	44 mg/l (Daphnia magna)
EC50 (72 hr)	674.7 mg/l (Desmodesmus subspicatus)
LC50 (48 hr)	44 mg/l (Daphnia magna)
LC50 (96 hr)	18 mg/l (Pimephales promelas)
NOEC (72 hr)	200 mg/l (Desmodesmus subspicatus)

1330-20-7 xylene

CE50	10 mg/l (Fish) (72h)
EC50 (48 hr)	7.4 mg/l (Daphnia magna)
LC50 (96 hr)	3.77-13.5 mg/l (Fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50 (48 hr)	>100 mg/l (Crustacea)
EC50 (72 hr)	>100 mg/l (Algae)
LC50 (96 hr)	>100 mg/l (Fish)
NOEC	100 mg/l (Crustacea)
	>10 mg/l (Fish)

822-06-0 hexamethylene diisocyanate

EC50 (48 hr)	≥89.1 mg/l (Daphnia magna)
EC50 (72 hr)	>77.4 mg/l (Desmodesmus subspicatus)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

· **ADR, IMDG, IATA** UN1263

14.2 UN proper shipping name

· **ADR** 1263 PAINT RELATED MATERIAL
· **IMDG, IATA** PAINT RELATED MATERIAL

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 8)

14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.
 · Label 3

· IMDG, IATA



· Class 3 Flammable liquids.
 · Label 3

14.4 Packing group

· ADR, IMDG, IATA III

14.5 Environmental hazards:

· Marine pollutant: No

14.6 Special precautions for user

· Warning: Flammable liquids.
 · Kemler Number: 30
 · EMS Number: F-E, S-E
 · Stowage Category A

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L
 · Excepted quantities (EQ) Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· Transport category 3
 · Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L
 · Excepted quantities (EQ) Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 57 (replaces version 56)

Revision: 18.01.2023

Trade name: Self Guide Primer Filler EVO FAST HARDENER

(Contd. of page 9)

- **National regulations**

- **Technical instructions (air):**

Class	Share in %
I	0.2
NK	45.0

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH204 Contains isocyanates. May produce an allergic reaction.

- **Department issuing data specification sheet:** Environment protection department

- **Abbreviations and acronyms:**

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 2: Acute toxicity – Category 2
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1

- **Data compared to the previous version altered. ***