

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 18.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Primer DC**

Article number: 86532

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Priming

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kent europe.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 18.01.2023

Trade name: Primer DC

(Contd. of page 1)

Signal word Danger**Hazard-determining components of labelling:**

XYLENE Mixture ethylbenzene, m-Xylene and p-Xylene
 bis[4-(2,3-epoxypropoxy)phenyl]propane
 3-aminopropyltriethoxysilane
 n-butyl acetate
 butyl acrylate

Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280 Wear protective gloves / eye protection / face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P331 Do NOT induce vomiting.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

· **Description:** Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	25-50%
EC number: 905-562-9 Reg.nr.: 01-2119555267-33	XYLENE Mixture ethylbenzene, m-Xylene and p-Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 141-32-2 EINECS: 205-480-7	butyl acrylate ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-10%
CAS: 919-30-2 EINECS: 213-048-4 Reg.nr.: 01-2119480479-24	3-aminopropyltriethoxysilane ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317	<3%
CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	<3%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	Methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<1%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****After inhalation**

Supply fresh air and call for doctor for safety reasons.
 In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly wash with water and soap and rinse thoroughly.
 Generally the product is not skin irritating.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 18.01.2023

Trade name: Primer DC

(Contd. of page 2)

- **After eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing** In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store in cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
- **Storage class** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

141-32-2 butyl acrylate

WEL Short-term value: 26 mg/m³, 5 ppm
Long-term value: 5 mg/m³, 1 ppm

80-62-6 Methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm
Long-term value: 208 mg/m³, 50 ppm

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 18.01.2023

Trade name: Primer DC

(Contd. of page 3)

Regulatory information WEL: EH40/2020**DNELs****123-86-4 n-butyl acetate**

Dermal	Acute systemic effect	11 mg/kg bw/day (Worker)
	Long term systemic effect	11 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	300 mg/m ³ (Worker)
	Acute local effect	600 mg/m ³ (Worker)
	Long term local effect	300 mg/m ³ (Worker)
	Acute systemic effect	600 mg/m ³ (Worker)

XYLENE Mixture ethylbenzene, m-Xylene and p-Xylene

Dermal	Long term local effect	3,182 mg/kg/day (Worker)
Inhalative	Acute local effect	442 mg/m ³ (Worker)
	Long term local effect	221 mg/m ³ (Worker)

919-30-2 3-aminopropyltriethoxysilane

Dermal	Acute systemic effect	8.3 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	59 mg/m ³ (Worker)
	Acute systemic effect	59 mg/m ³ (Worker)

80-62-6 Methyl methacrylate

Dermal	Long term local effect	1.5 mg/m ² (Worker)
	Acute local effect	1.5 mg/cm ³ (Worker)
	Long term systemic effect	13.7 mg/kg bw/dy (Worker)
Inhalative	Long term systemic effect	208 mg/m ³ (Worker)
	Long term local effect	208 mg/m ³ (Worker)

PNECs**123-86-4 n-butyl acetate**

PNEC	0.18 mg/l (Aqua (freshwater))
	0.36 mg/ml (Aqua (intermittent))
	0.018 mg/ml (Aqua (marine water))
	0.981 mg/kg (Freshwater sediment)
	0.0981 mg/kg (Marine water sediment)
	35.6 mg/l (Sewage treatment plant)
	0.09 mg/kg (Soil)

XYLENE Mixture ethylbenzene, m-Xylene and p-Xylene

PNEC	0.25 mg/l (Aqua (freshwater))
	0.327 mg/kg (Aqua (intermittent))
	0.25 mg/l (Aqua (marine water))
	14.33 mg/l (Freshwater sediment)
	14.33 mg/l (Marine water sediment)
	6.58 mg/l (Sewage treatment plant)
	2.41 mg/kg (Soil)

919-30-2 3-aminopropyltriethoxysilane

PNEC	0.34 mg/ml (Aqua (freshwater))
	0.033 mg/ml (Aqua (marine water))

80-62-6 Methyl methacrylate

PNEC	0.94 mg/l (Aqua (freshwater))
	0.94 mg/l (Aqua (intermittent))
	0.94 mg/l (Aqua (marine water))
	5.74 mg/kg (Freshwater sediment)
	1.47 mg/kg (Soil)

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 18.01.2023

Trade name: Primer DC

(Contd. of page 4)

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Filter A2 / P3 (EN 14387)· **Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**

Tightly sealed safety glasses. (EN 166)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

According to product specification

Odour:

Light

Odour threshold:

Not determined.

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

>65 °C

Flammability

Highly flammable.

Lower and upper explosion limit

Lower:

0.9 Vol %

Upper:

36.5 Vol %

Flash point:

4 °C

Ignition temperature:

420 °C

Decomposition temperature:

Not determined.

pH

Mixture is non-polar/aprotic.

Viscosity:

Kinematic viscosity

Not determined.

dynamic:

Not determined.

Solubility

Water:

Not miscible / difficult to mix

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure at 20 °C:

31 hPa

Density and/or relative density

Density

Not determined

Relative density

Not determined.

Vapour density

Not determined.

9.2 Other information

Appearance:

Form:

Fluid

Important information on protection of health and environment, and on safety.

Self-inflammability:

Product is not selfigniting.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 18.01.2023

Trade name: Primer DC

(Contd. of page 5)

· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· Solvent content:	
· Organic solvents:	52.0 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	14,000 mg/kg (Rat)
------	------	--------------------

XYLENE Mixture ethylbenzene, m-Xylene and p-Xylene

Oral	LD50	4,300 mg/kg (Rat)
------	------	-------------------

Dermal	LD50	2,000 mg/kg (rbt)
--------	------	-------------------

141-32-2 butyl acrylate

Oral	LD50	900 mg/kg (Rat)
------	------	-----------------

Dermal	LD50	2,000 mg/kg (rbt)
--------	------	-------------------

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 18.01.2023

Trade name: Primer DC

(Contd. of page 6)

11.2 Information on other hazards**Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****123-86-4 n-butyl acetate**

EC50 (48 hr)	44 mg/l (Daphnia magna)
EC50 (72 hr)	674.7 mg/l (Desmodesmus subspicatus)
LC50 (48 hr)	44 mg/l (Daphnia magna)
LC50 (96 hr)	18 mg/l (Pimephales promelas)
NOEC (72 hr)	200 mg/l (Desmodesmus subspicatus)

XYLENE Mixture ethylbenzene, m-Xylene and p-Xylene

CE50	10 mg/l (Fish) (72h)
EC50 (48 hr)	7.4 mg/l (Daphnia magna)
LC50	1,300 µg/l (Fish)
LC50 (96 hr)	3.77-13.5 mg/l (Fish)
NOEC (72 hr)	0.44 mg/l (Pseudokirchneriella subcapitata)
NOEC	>1.3 mg/l (Oncorhynchus mykiss) (56 days)
NOEC (21 days)	1.57 mg/l (Daphnia magna)

919-30-2 3-aminopropyltriethoxysilane

EC10	>1,000 (Pseudokirchneriella subcapitata) (OECD 201)
EC50 (48 hr)	331 mg/l (Crustacea) (OECD 202)
	331 mg/l (Daphnia magna) (OECD TG 202)
EC50 (72 hr)	>1,000 mg/l (Desmodesmus subspicatus) (OECD TG 201)
	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50 (96 hr)	>934 mg/l (Brachydanio rerio) (OECD TG 203)
	>934 mg/l (Fish) (OECD 203)

80-62-6 Methyl methacrylate

EC50 (48 hr)	69 mg/l (Daphnia magna) (OECD 202)
EC50 (72 hr)	>110 mg/l (Selenastrum capricornutum) (OECD 201)
LC50 (96 hr)	>79 mg/l (Oncorhynchus mykiss) (OECD 203)
NOEC	9.4 mg/l (Danio rerio (Zebra fish; semistatic)) (OECD 210)
NOEC (21 days)	37 mg/l (Daphnia magna) (OECD 202-2)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects**Additional ecological information:****General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)



Revision: 18.01.2023

Trade name: Primer DC

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR	1263 PAINT RELATED MATERIAL, special provision 640D
· IMDG, IATA	PAINT RELATED MATERIAL
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number:	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640D, 3, II

GB

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 18.01.2023

Trade name: Primer DC

(Contd. of page 8)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations

· Technical instructions (air):

Class	Share in %
NK	52.0

- Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing data specification sheet: Environment protection department

· Abbreviations and acronyms:

- ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1

· Data compared to the previous version altered. *