

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Contact Spray Adhesive**

Article number: 86593

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Adhesive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Skin Irrit. 2

H315 Causes skin irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acetone

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

Trade name: Contact Spray Adhesive

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures**· **Description:** Mixture of the substances listed below with harmless additions.**Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8	Dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	50-75%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	<5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****After inhalation**

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air; consult doctor in case of symptoms.

After skin contact

Instantly remove any clothing soiled by the product.

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.**After swallowing**

Rinse out mouth.

In case of persistent symptoms consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**· **Suitable extinguishing agents** CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters**Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

Trade name: Contact Spray Adhesive

(Contd. of page 2)

Wear full protective suit.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage
7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on flames or red-hot objects.

7.2 Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and containers:

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Protect from heat and direct sunlight.

Storage class 2
7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Components with limit values that require monitoring at the workplace:
67-64-1 Acetone
WEL Short-term value: 3620 mg/m³, 1500 ppmLong-term value: 1210 mg/m³, 500 ppm
Regulatory information WEL: EH40/2020

DNELs
115-10-6 Dimethyl ether
Inhalative Long term systemic effect 1,894 mg/m³ (Worker)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral Long term systemic effect 699 mg/kg bw/day (Consumer)

Dermal Long term systemic effect 699 mg/kg bw/day (Consumer)

773 mg/kg bw/day (Worker)

Inhalative Long term systemic effect 608 mg/m³ (Consumer)2,035 mg/m³ (Worker)
67-64-1 Acetone

Dermal Long term systemic effect 186 mg/kg bw/day (Worker)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

Trade name: Contact Spray Adhesive

(Contd. of page 3)

Inhalative	Long term systemic effect	1,210 mg/m ³ (Worker)
	Acute local effect	2,420 mg/m ³ (Worker)
8050-26-8 Resin acids and Rosin acids, esters with pentaerythritol		
Dermal	Long term systemic effect	6.3 mg/kg/day (Worker)
Inhalative	Long term systemic effect	44.6 mg/m ³ (Worker)
6683-19-8 Pentaerythritol tetrakis (3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate)		
Dermal	Long term systemic effect	89.2 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	9.5 mg/m ³ (Worker)
PNECs		
115-10-6 Dimethyl ether		
PNEC	0.155 mg/l (Aqua (freshwater))	
	1,549 mg/l (Aqua (intermittent))	
	0.016 mg/l (Aqua (marine water))	
	0.681 mg/l (Freshwater sediment)	
	0.069 mg/l (Marine water sediment)	
	0.045 mg/l (Soil)	
67-64-1 Acetone		
PNEC	10.6 mg/l (Aqua (freshwater))	
	21 mg/l (Aqua (intermittent))	
	1.06 mg/l (Aqua (marine water))	
	30.4 mg/kg (Freshwater sediment)	
	3.04 mg/kg (Marine water sediment)	
	29.5 mg/kg (Soil)	
8050-26-8 Resin acids and Rosin acids, esters with pentaerythritol		
PNEC	0.027 mg/l (Aqua (freshwater))	
	0.27 mg/l (Aqua (intermittent))	
	0.003 mg/l (Aqua (marine water))	
	625.79 mg/kg (Freshwater sediment)	
	62.58 mg/kg (Marine water sediment)	
	2 mg/l (Sewage treatment plant)	
	125 mg/kg (Soil)	
6683-19-8 Pentaerythritol tetrakis (3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate)		
PNEC	0.04 mg/l (Aqua (freshwater))	
	0.86 mg/l (Aqua (intermittent))	
	0.004 mg/l (Aqua (marine water))	
	1 mg/ml (Sewage treatment plant)	
	798,000 mg/kg (Soil)	

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
Keep away from foodstuffs, beverages and food.
Take off immediately all contaminated clothing
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
Only during spraying without adequate removal by suction.
Filter AX / P (EN 14387)
- **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

Trade name: Contact Spray Adhesive

(Contd. of page 4)

Material of gloves

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Safety glasses (EN 166)

Body protection: Protective work clothing (EN-13034/6)**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information**

· Physical state	Aerosol
· Colour:	Light yellow
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	55 °C (@ 1013 hPa)
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.0 Vol %
· Upper:	13 Vol %
· Flash point:	Not applicable, as aerosol
· Ignition temperature:	275 °C
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	~300 cps
· Solubility	
· Water:	Not miscible / difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density	Not determined
· Relative density at 20 °C	0.68
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Self-flammability:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	607 g/l VOC
· Solids content:	~ 30%
· Change in condition	
· Evaporation rate	Not applicable.

Information with regard to physical hazard classes

· Explosives	Void
---------------------	------

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

Trade name: Contact Spray Adhesive

(Contd. of page 5)

· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:** Strong acids and oxidizing agents
- **10.6 Hazardous decomposition products:** Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5,840 mg/kg (Rat)
Dermal	LD50	>2,920 mg/kg (Rabbit)
Inhalative	LC50 (4 hr)	>25.2 mg/l (Rat)

67-64-1 Acetone

Oral	LD50	5,800 mg/kg (Rat)
Dermal	LD50	20,000 mg/kg (Rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

115-10-6 Dimethyl ether

EC50 (48 hr)	>4,000 mg/l (Daphnia magna)
EL50 (48 hr)	4,001 mg/l (Daphnia magna)
LC50 (48 hr)	755,549 mg/l (Daphnia magna)
LC50 (96 hr)	154.9 mg/l (Algae)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

Trade name: Contact Spray Adhesive

(Contd. of page 6)

	4,001 mg/l (Poecilia reticulata)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
EL50 (48 hr)	3 mg/l (Daphnia magna)
EL50 (72 hr)	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50	11.4 mg/l (Oncorhynchus mykiss) (96 hr)
LOEC (21 days)	0.32 mg/l (Daphnia magna)
NOEC (21 days)	0.17 mg/l (Daphnia magna)
NOELR	3 mg/l (Pseudokirchneriella subcapitata) (72 hr)
67-64-1 Acetone	
EC50	61,150 mg/l (Activated sludge) (30 mins)
EC50 (48 hr)	39 mg/l (Daphnia magna)
LC50 (96 hr)	8,300 mg/l (Fish)
	5,540 mg/l (Oncorhynchus mykiss)
NOEC (28 days)	2,212 mg/l (Daphnia magna)
6683-19-8 Pentaerythritol tetrakis (3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate)	
EC50 (72 hr)	>100 mg/l (Desmodesmus subspicatus)
LC50 (96 hr)	>100 mg/l (Danio rerio (Zebra fish; semistatic)) (OECD 203)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
- Do not allow product to reach ground water, water bodies or sewage system.
- Danger to drinking water if even small quantities leak into soil.
- Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane), MARINE POLLUTANT
- **IATA** AEROSOLS, flammable

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

Trade name: Contact Spray Adhesive

(Contd. of page 7)

14.3 Transport hazard class(es)

ADR



· Class 2 5F Gases.
· Label 2.1

IMDG



· Class 2.1 Gases.
· Label 2.1

IATA



· Class 2.1 Gases.
· Label 2.1

14.4 Packing group

· ADR, IMDG, IATA Void

14.5 Environmental hazards:

· Marine pollutant: Product contains environmentally hazardous substances: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Symbol (fish and tree)

· Special marking (ADR): Symbol (fish and tree)

14.6 Special precautions for user

· Warning: Gases.

· Kemler Number: -

· EMS Number: F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A.
For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· Segregation Code

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR

· Limited quantities (LQ) 1L
· Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity

· Transport category 2

· Tunnel restriction code D

IMDG

· Limited quantities (LQ) 1L

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 32 (replaces version 31)

Revision: 18.01.2023

Trade name: Contact Spray Adhesive

(Contd. of page 8)

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category P3a** FLAMMABLE AEROSOLS· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t· **National regulations**· **Technical instructions (air):**

Class	Share in %
NK	58.0

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing data specification sheet:** Environment protection department

· **Abbreviations and acronyms:**

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **Data compared to the previous version altered.** *