

Page 1/7

Revision: 13.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: Performance Compound 2
- · Article number: 86606
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

- · Application of the substance / the mixture Polishing compound
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079 SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:

Silicic acid, sodium salt

Fatty amine ethoxylate

· Hazard statements

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 4 (replaces version 3) Revision: 13.01.2023

Trade name: Performance Compound 2

(Contd. of page 1)

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· Description: Mixture of the substances listed below with harmless additions.

| Dangerous components | S: | |
|---|--|--------|
| CAS: 1344-28-1 EINECS: 215-691-6 Reg.nr.: 01-2119529248-35 | Aluminium oxide substance with a Community workplace exposure limit | 25-50% |
| CAS: 64742-47-8 EINECS: 265-149-8 Reg.nr.: 01-2119484819-18 | Distillates (petroleum), hydrotreated light Asp. Tox. 1, H304, EUH066 | 5-10% |
| EC number: 934-956-3 Reg.nr.: 01-2119827000-58 | Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0,03 % aromatic ❖ Asp. Tox. 1, H304 | 5-10% |
| CAS: 1344-09-8 EINECS: 215-687-4 Reg.nr.: 01-2119448725-31 | Silicic acid, sodium salt ♦ Acute Tox. 3, H331; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315 | <5% |
| CAS: 61791-26-2 NLP: 500-153-8 | Fatty amine ethoxylate ♦ Eye Dam. 1, H318; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315 | <5% |
| EC number: 918-668-5 Reg.nr.: 01-2119455851-35 | Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335; STOT SE 3, H336 | <5% |

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly wash with water and soap and rinse thoroughly.

Generally the product is not skin irritating.

- After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- · After swallowing In case of persistent symptoms consult doctor.
- * 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents CO2, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions: Inform respective authorities in case product reaches water or sewage system.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 4 (replaces version 3) Revision: 13.01.2023

Trade name: Performance Compound 2

(Contd. of page 2)

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| | · Components with | limit values ti | hat require | monitorina | at the workplace: |
|--|-------------------|-----------------|-------------|------------|-------------------|
|--|-------------------|-----------------|-------------|------------|-------------------|

1344-28-1 Aluminium oxide

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

Regulatory information WEL: EH40/2020

DNELs

1344-09-8 Silicic acid, sodium salt

Dermal Long term systemic effect 1.59 mg/kg/day (Worker)
Inhalative Long term systemic effect 5.61 mg/m3 (Worker)

Hydrocarbons, C9, aromatics

Dermal Long term systemic effect 25 mg/kg bw/day (Worker)
Inhalative Long term systemic effect 100 mg/m3 (Worker)

PNECs

1344-09-8 Silicic acid, sodium salt

PNEC 7.5 mg/l (Aqua (freshwater))

7.5 mg/l (Aqua (intermittent))

1 mg/l (Aqua (marine water))

348 mg/l (Sewage treatment plant)

- · Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment: Filter A2 / P3 (EN 14387)

(Contd. on page 4)

(Contd. of page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 4 (replaces version 3) Revision: 13.01.2023

Trade name: Performance Compound 2

· Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Not applicable.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Safety glasses (EN 166)

Tightly sealed safety glasses. (EN 166)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: White

Odour: CharacteristicOdour threshold: Not determined.

• Melting point/freezing point:
• Boiling point or initial boiling point and boiling range

100 °C

Flammability

· Lower and upper explosion limit · Lower: Not determined.

· Upper: 10.6 Vol %
· Flash point: 65 °C
· Ignition temperature: 230 °C

• Decomposition temperature: Not determined.

pH at 20 °C 9.5

Viscosity:

Kinematic viscosity
 dynamic:
 Solubility
 Not determined.

• Water: Not miscible / difficult to mix • Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C: 100 Value) Not determine the value of the

Density and/or relative density

Density at 20 °C 1.104 g/cm³
Relative density Not determined.
Vapour density Not determined.

9.2 Other information

· Appearance:

· Form: Viscous

Important information on protection of health and

environment, and on safety.

Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

· Change in condition

Evaporation rate Not determined.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 4 (replaces version 3) Revision: 13.01.2023

Trade name: Performance Compound 2

(Contd. of page 4) Information with regard to physical hazard classes Explosives Void Flammable gases Void · Aerosols Void Oxidising gases Void Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void Organic peroxides Void · Corrosive to metals Void Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- * 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification:

64742-47-8 Distillates (petroleum), hydrotreated light

LD50 >5,000 mg/kg (Rat) Oral

Dermal LD50 >5,000 mg/kg (Rabbit)

Hydrocarbons, C9, aromatics

Oral LD50 >2,000-≤5,000 mg/kg (Rat) Dermal LD50 >2,000 mg/kg (Rabbit)

- Serious eye damage/irritation Causes serious eye irritation.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

| Λα | uatic | toxicity | <i>,</i> . |
|----|-------|----------|------------|
| 74 | uauc | LUXICIL | 7 . |

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0,03 % aromatic

ERL50 >1,000 mg/l (Algae) (72 hrs)

LL50 (96 hr) >1,028 mg/l (Fish)

1150 >3,193 mg/l (Daphnia magna) (48 hrs)

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 4 (replaces version 3) Revision: 13.01.2023

Trade name: Performance Compound 2

| | (Contd. of page 5) |
|--------------|--|
| 1344-09-8 Si | licic acid, sodium salt |
| EC50 (48 hr) | 0.28-0.57 mg/l (Water flea (Ceriodaphnia dubia)) |
| LC50 (96 hr) | 1,800 mg/l (Gambusia affinis) |
| Hydrocarboi | ns, C9, aromatics |
| EL50 (48 hr) | 3.2 mg/l (Daphnia magna) |
| LL50 (96 hr) | 9.2 mg/l (Oncorhynchus mykiss) |
| NOEC (72 hr | 1 mg/l (Pseudokirchneriella subcapitata) |

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport information | |
|---|--|
| 14.1 UN number or ID number ADR, IMDG, IATA | Void |
| 14.2 UN proper shipping name ADR, IMDG, IATA | Void |
| 14.3 Transport hazard class(es) | |
| ADR, ADN, IMDG, IATA Class | Void |
| 14.4 Packing group ADR, IMDG, IATA | Void |
| 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user | Not applicable. |
| 14.7 Maritime transport in bulk according instruments | to IMO Not applicable. |
| Transport/Additional information: | Not dangerous according to the above specifications. |
| UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 4 (replaces version 3) Revision: 13.01.2023

Trade name: Performance Compound 2

(Contd. of page 6)

- · National regulations
- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing data specification sheet: Environment protection department

Abbreviations and acronyms:

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard — Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

Data compared to the previous version altered. *

GB