Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 16 (replaces version 15) Revision: 19.01.2023

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· **Trade name: NEW SELF GUIDE HARDENER**

· **Article number:** 86770

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

· **Application of the substance / the mixture** Hardening agent / curing agent

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

KENT (United Kingdom) Ltd
Forsyth House
Pitreavie Drive
Pitreavie Business Park
Dunfermline
Fife
KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm
Fax: +44 1383 620079
SDS@kenteurope.com

· 1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

*

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**

flame

Flam. Liq. 3	H226 Flammable liquid and vapour.

Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

Aliphatic polyisocyanate
n-butyl acetate
xylene

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 16 (replaces version 15) Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 1)

Hydrocarbons, C9, aromatics

· **Hazard statements**
H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**
EUH066 Repeated exposure may cause skin dryness or cracking.
Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of the substances listed below with harmless additions.

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	50-75%
CAS: 28182-81-2 EC number: 931-274-8 Reg.nr.: 01-2119485796-17	Aliphatic polyisocyanate Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335; STOT SE 3, H336	<5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

*
SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation**
Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.

· **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

· **After eye contact** Rinse opened eye for several minutes under running water.

· **After swallowing** Do not induce vomiting; instantly call for medical help.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 16 (replaces version 15) Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 2)

· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*
SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents** CO2, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
· **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
· **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide
Nitrogen oxides (NOx)
· **5.3 Advice for firefighters**
· **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Wear self-contained breathing apparatus.
Wear full protective suit.
· **Additional information** Cool endangered containers with water spray jet.

*
SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources
Wear protective equipment. Keep unprotected persons away.
· **6.2 Environmental precautions:**
Do not allow to enter drainage system, surface or ground water.
Prevent material from reaching sewage system, holes and cellars.
Inform respective authorities in case product reaches water or sewage system.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

*
SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Keep away from heat and direct sunlight.
· **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage**
· **Requirements to be met by storerooms and containers:** Store in cool location.
· **Information about storage in one common storage facility:** Do not store together with oxidising and acidic materials.
· **Further information about storage conditions:**
Store in cool, dry conditions in well sealed containers.
Protect from heat and direct sunlight.
15-25ºC
· **Storage class** 3
· **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 *Version number 16 (replaces version 15)* *Revision: 19.01.2023*

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 3)

*

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Components with limit values that require monitoring at the workplace:**	
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
1330-20-7 xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

· **Regulatory information** WEL: EH40/2020

· **DNELs**		
123-86-4 n-butyl acetate		
Dermal	Acute systemic effect	11 mg/kg bw/day (Worker)
	Long term systemic effect	11 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	300 mg/m3 (Worker)
	Acute local effect	600 mg/m³ (Worker)
	Long term local effect	300 mg/m³ (Worker)
	Acute systemic effect	600 mg/m³ (Worker)
28182-81-2 Aliphatic polyisocyanate		
Inhalative	Acute local effect	1 mg/m3 (Worker)
	Long term local effect	0.5 mg/m3 (Worker)
1330-20-7 xylene		
Dermal	Long term local effect	3,182 mg/kg/day (Worker)
Inhalative	Acute local effect	442 mg/m3 (Worker)
	Long term local effect	221 mg/m3 (Worker)
Hydrocarbons, C9, aromatics		
Dermal	Long term systemic effect	25 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	100 mg/m3 (Worker)

· **PNECs**	
123-86-4 n-butyl acetate	
PNEC	0.18 mg/l (Aqua (freshwater)) 0.36 mg/ml (Aqua (intermittent)) 0.018 mg/ml (Aqua (marine water)) 0.981 mg/kg (Freshwater sediment) 0.0981 mg/kg (Marine water sediment) 35.6 mg/l (Sewage treatment plant) 0.09 mg/kg (Soil)
28182-81-2 Aliphatic polyisocyanate	
PNEC	0.127 mg/l (Aqua (freshwater)) 1.27 mg/l (Aqua (intermittent)) 0.0127 mg/l (Aqua (marine water)) 266,700 mg/kg (Freshwater sediment) 26,670 mg/kg (Marine water sediment) 38.3 mg/l (Sewage treatment plant) 53,182 mg/kg (Soil)
1330-20-7 xylene	
PNEC	0.327 mg/l (Aqua (freshwater)) 0.327 mg/l (Aqua (marine water)) 12.46 mg/l (Freshwater sediment) 12.46 mg/l (Marine water sediment) 6.58 mg/l (Sewage treatment plant) 2.31 mg/kg (Soil)

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 16 (replaces version 15) Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 4)

· **Ingredients with biological limit values:**

1330-20-7 xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see item 7.
· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures**
Keep away from foodstuffs, beverages and food.
Take off immediately all contaminated clothing
Wash hands during breaks and at the end of the work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
· **Breathing equipment:**
Filter A (EN 141)
In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
· **Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Wear suitable gloves tested to EN 374
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· **Penetration time of glove material**
Value for the permeation: Level 6 > 480 minutes
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye/face protection**

Tightly sealed safety glasses. (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

*
SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**
· **General Information**

· **Physical state**	Fluid
· **Colour:**	Colourless
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **Melting point/freezing point:**	Not determined
· **Boiling point or initial boiling point and boiling range**	Not determined
· **Flammability**	Flammable.
· **Lower and upper explosion limit**	
· **Lower:**	1.7 Vol %
· **Upper:**	7.6 Vol %
· **Flash point:**	27 °C (ISO 3680:2005)
· **Decomposition temperature:**	Not determined.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 16 (replaces version 15) Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 5)

· **pH**	Mixture is non-soluble (in water).
· **Viscosity:**	
· **Kinematic viscosity at 20 °C**	> 180 mm2/s
· **dynamic:**	Not determined.
· **Solubility**	
· **Water:**	Not miscible / difficult to mix
· **Partition coefficient n-octanol/water (log value)**	Not determined.
· **Vapour pressure:**	Not determined.
· **Density and/or relative density**	
· **Density at 20 °C**	0.975 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.

· **9.2 Other information**

· **Appearance:**	
· **Form:**	Fluid
· **Important information on protection of health and environment, and on safety.**	
· **Self-inflammability:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· **Change in condition**	
· **Evaporation rate**	Not determined.

· **Information with regard to physical hazard classes**	
· **Explosives**	Void
· **Flammable gases**	Void
· **Aerosols**	Void
· **Oxidising gases**	Void
· **Gases under pressure**	Void
· **Flammable liquids**	Flammable liquid and vapour.
· **Flammable solids**	Void
· **Self-reactive substances and mixtures**	Void
· **Pyrophoric liquids**	Void
· **Pyrophoric solids**	Void
· **Self-heating substances and mixtures**	Void
· **Substances and mixtures, which emit flammable gases in contact with water**	Void
· **Oxidising liquids**	Void
· **Oxidising solids**	Void
· **Organic peroxides**	Void
· **Corrosive to metals**	Void
· **Desensitised explosives**	Void

*
SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known
· **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
· **10.5 Incompatible materials:**
Strong acids and oxidizing agents
Alkalis
Alcohols, amines, aqueous acids and alkalis
· **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 *Version number 16 (replaces version 15)* *Revision: 19.01.2023*

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 6)

*
SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Harmful if inhaled.

· LD/LC50 values that are relevant for classification:		
123-86-4 n-butyl acetate		
Oral	LD50	14,000 mg/kg (Rat)
28182-81-2 Aliphatic polyisocyanate		
Oral	LD50	>2,500 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)
Hydrocarbons, C9, aromatics		
Oral	LD50	>2,000-≤5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)

· **Skin corrosion/irritation** Causes skin irritation.
· **Respiratory or skin sensitisation** May cause an allergic skin reaction.
· **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
· **11.2 Information on other hazards**

· Endocrine disrupting properties
None of the ingredients is listed.

*
SECTION 12: Ecological information

· **12.1 Toxicity**

· Aquatic toxicity:	
123-86-4 n-butyl acetate	
EC50 (48 hr)	44 mg/l (Daphnia magna)
EC50 (72 hr)	674.7 mg/l (Desmodesmus subspicatus)
LC50 (48 hr)	44 mg/l (Daphnia magna)
LC50 (96 hr)	18 mg/l (Pimephales promelas)
NOEC (72 hr)	200 mg/l (Desmodesmus subspicatus)
28182-81-2 Aliphatic polyisocyanate	
EC10	>100 /48 hr (Daphnia magna) (OECD 202)
EC50 (72 hr)	3,828 mg/l (Activated sludge) (OECD 209)
LC50 (96 hr)	>100 mg/l (Brachydanio rerio)
1330-20-7 xylene	
CE50	10 mg/l (Fish) (72h)
EC50 (48 hr)	7.4 mg/l (Daphnia magna)
LC50 (96 hr)	3.77-13.5 mg/l (Fish)
Hydrocarbons, C9, aromatics	
EL50 (48 hr)	3.2 mg/l (Daphnia magna)
LL50 (96 hr)	9.2 mg/l (Oncorhynchus mykiss)
NOEC (72 hr)	1 mg/l (Pseudokirchneriella subcapitata)

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
· **12.7 Other adverse effects**
· **Remark:** Harmful to fish

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 *Version number 16 (replaces version 15)* *Revision: 19.01.2023*

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 7)

· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.
Harmful to aquatic organisms

*
SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:** Disposal must be made according to official regulations.

*
SECTION 14: Transport information

· **14.1 UN number or ID number**	
· **ADR, IMDG, IATA**	UN1263
· **14.2 UN proper shipping name**	
· **ADR**	1263 PAINT RELATED MATERIAL
· **IMDG, IATA**	PAINT RELATED MATERIAL
· **14.3 Transport hazard class(es)**	
· **ADR**	

· **Class**	3 (F1) Flammable liquids.
· **Label**	3
· **IMDG, IATA**	

· **Class**	3 Flammable liquids.
· **Label**	3
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	III
· **14.5 Environmental hazards:**	
· **Marine pollutant:**	No
· **14.6 Special precautions for user**	Warning: Flammable liquids.
· **Kemler Number:**	30
· **EMS Number:**	F-E,S-E
· **Stowage Category**	A
· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **Transport category**	3

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 *Version number 16 (replaces version 15)* *Revision: 19.01.2023*

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 8)

· **Tunnel restriction code**	D/E
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **UN "Model Regulation":**	UN 1263 PAINT RELATED MATERIAL, 3, III

*
SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations**

· **Technical instructions (air):**

Class	Share in %
NK	65.0

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing data specification sheet:** Environment protection department
· **Abbreviations and acronyms:**
RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2023 *Version number 16 (replaces version 15)* *Revision: 19.01.2023*

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 9)

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· ***Data compared to the previous version altered.*** *