



23.01.2023

**Kit components**

Product code	Description
--------------	-------------

<b>86776</b>	<b>NEW SELF GUIDE Black Kit</b>
--------------	---------------------------------

Components:

86768	NEW SELF GUIDE Black
-------	----------------------

86770	NEW SELF GUIDE HARDENER
-------	-------------------------

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **NEW SELF GUIDE Black**

Article number: 86768

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

#### Application of the substance / the mixture

Priming  
Filler and surfacer

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

KENT (United Kingdom) Ltd  
Forsyth House  
Pitreavie Drive  
Pitreavie Business Park  
Dunfermline  
Fife  
KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

#### 1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS02



GHS07

Signal word *Warning*

##### Hazard-determining components of labelling:

*n*-butyl acetate

2-ethoxy-1-methylethyl acetate

fatty acids, C18, unsatd., dimers, reaction products with *N,N*-dimethyl-1,3-propanediamine and 1,3-propanediamine

ethylene bis(3-mercaptopropionate)

##### Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

**Trade name: NEW SELF GUIDE Black**

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

Description: Mixture of the substances listed below with harmless additions.

**Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	10-25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<5%
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-ethoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	<5%
CAS: 162627-17-0 EC number: 605-296-0 Reg.nr.: 01-2119970640-38	fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine ⚠ Skin Sens. 1A, H317	<0.1%
CAS: 22504-50-3 EINECS: 245-044-3 Reg.nr.: 01-2120775145-52	ethylene bis(3-mercaptopropionate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319; Skin Sens. 1A, H317	<0.1%

Additional information For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

After inhalation Supply fresh air; consult doctor in case of symptoms.

**After skin contact**

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Do not induce vomiting; instantly call for medical help.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**Suitable extinguishing agents CO<sub>2</sub>, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Nitrogen oxides (NOx)

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

Trade name: **NEW SELF GUIDE Black**

(Contd. of page 2)

### 5.3 Advice for firefighters

#### Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

Wear full protective suit.

#### Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Prevent material from reaching sewage system, holes and cellars.

### 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep away from heat and direct sunlight.

### Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

#### Requirements to be met by storerooms and containers:

Store in cool location.

Store only in the original container.

#### Information about storage in one common storage facility: Do not store together with oxidising and acidic materials.

#### Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store container in a well ventilated position.

15-25°C

#### Storage class 3

### 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Components with limit values that require monitoring at the workplace:

#### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppmLong-term value: 724 mg/m<sup>3</sup>, 150 ppm

#### 1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppmLong-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

**Trade name: NEW SELF GUIDE Black**

(Contd. of page 3)

**Regulatory information WEL: EH40/2020****DNELs****123-86-4 n-butyl acetate**

Dermal	Acute systemic effect	11 mg/kg bw/day (Worker)
	Long term systemic effect	11 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	300 mg/m <sup>3</sup> (Worker)
	Acute local effect	600 mg/m <sup>3</sup> (Worker)
	Long term local effect	300 mg/m <sup>3</sup> (Worker)
	Acute systemic effect	600 mg/m <sup>3</sup> (Worker)

**1330-20-7 xylene**

Dermal	Long term local effect	3,182 mg/kg/day (Worker)
Inhalative	Acute local effect	442 mg/m <sup>3</sup> (Worker)
	Long term local effect	221 mg/m <sup>3</sup> (Worker)

**110-43-0 heptan-2-one**

Dermal	Long term systemic effect	54.27 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	394.25 mg/m <sup>3</sup> (Worker)
	Acute systemic effect	1,516 mg/m <sup>3</sup> (Worker)

**PNECs****123-86-4 n-butyl acetate**

PNEC	0.18 mg/l (Aqua (freshwater))
	0.36 mg/ml (Aqua (intermittent))
	0.018 mg/ml (Aqua (marine water))
	0.981 mg/kg (Freshwater sediment)
	0.0981 mg/kg (Marine water sediment)
	35.6 mg/l (Sewage treatment plant)
	0.09 mg/kg (Soil)

**1330-20-7 xylene**

PNEC	0.327 mg/l (Aqua (freshwater))
	0.327 mg/l (Aqua (marine water))
	12.46 mg/l (Freshwater sediment)
	12.46 mg/l (Marine water sediment)
	6.58 mg/l (Sewage treatment plant)
	2.31 mg/kg (Soil)

**110-43-0 heptan-2-one**

PNEC	0.0982 mg/l (Aqua (freshwater))
	0.982 mg/l (Aqua (intermittent))
	0.00982 mg/l (Aqua (marine water))
	1.89 mg/kg (Freshwater sediment)
	0.189 mg/kg (Marine water sediment)
	12.5 mg/l (Sewage treatment plant)
	0.321 mg/kg (Soil)

**Ingredients with biological limit values:****1330-20-7 xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

**Additional information:** The lists that were valid during the compilation were used as basis.

**8.2 Exposure controls**

**Appropriate engineering controls** No further data; see item 7.

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures** Wash hands during breaks and at the end of the work.

**Breathing equipment:**

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Filter A (EN 141)

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

**Trade name: NEW SELF GUIDE Black**

(Contd. of page 4)

**Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.7$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection**

Tightly sealed safety glasses. (EN 166)

**Body protection:** Protective work clothing (EN-13034/6)

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Physical state**

Fluid

**Colour:**

Black

**Odour:**

Characteristic

**Odour threshold:**

Not determined.

**Melting point/freezing point:**

Not determined

**Boiling point or initial boiling point and boiling range**

Not determined

**Flammability**

Flammable.

**Lower and upper explosion limit****Lower:**

1.1 Vol %

**Upper:**

7.0 Vol %

**Flash point:**

25 °C (ASTM D-56)

**Decomposition temperature:**

Not determined.

**pH**

Mixture is non-soluble (in water).

**Viscosity:****Kinematic viscosity**

Not determined.

**dynamic at 40 °C:**> 1500 mm<sup>2</sup>/s**Solubility****Water:**

Not miscible / difficult to mix

**Partition coefficient n-octanol/water (log value)**

Not determined.

**Vapour pressure:**

Not determined.

**Density and/or relative density****Density at 20 °C**1.46 g/cm<sup>3</sup>**Relative density**

Not determined.

**Vapour density at 20 °C**3.66 g/cm<sup>3</sup> (butyl acetate)**9.2 Other information****Appearance:****Form:**

Viscous

**Important information on protection of health and environment, and on safety.****Self-inflammability:**

Product is not selfigniting.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

Trade name: **NEW SELF GUIDE Black**

(Contd. of page 5)

· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· <b>Solvent content:</b>	
· <b>Organic solvents:</b>	446 g/l VOC (RFU)
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
Stable at ambient temperature  
To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:**  
Strong acids and oxidizing agents  
Alkalis  
Peroxides  
Isocyanate  
Anhydrides
- **10.6 Hazardous decomposition products:**  
Formation of toxic gases is possible during heating or in case of fire.  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values that are relevant for classification:

<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	14,000 mg/kg (Rat)
<b>1330-20-7 xylene</b>		
Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)

- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause drowsiness or dizziness.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

Trade name: **NEW SELF GUIDE Black**

(Contd. of page 6)

### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

##### 123-86-4 n-butyl acetate

EC50 (48 hr)	44 mg/l (Daphnia magna)
EC50 (72 hr)	674.7 mg/l (Desmodesmus subspicatus)
LC50 (48 hr)	44 mg/l (Daphnia magna)
LC50 (96 hr)	18 mg/l (Pimephales promelas)
NOEC (72 hr)	200 mg/l (Desmodesmus subspicatus)

##### 1330-20-7 xylene

CE50	10 mg/l (Fish) (72h)
EC50 (48 hr)	7.4 mg/l (Daphnia magna)
LC50 (96 hr)	3.77-13.5 mg/l (Fish)

##### 110-43-0 heptan-2-one

EC50 (72 hr)	98.2 mg/l (Pseudokirchneriella subcapitata)
LC50 (96 hr)	131 mg/l (Pimephales promelas)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.  
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT

(Contd. on page 8)

GB



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

Trade name: **NEW SELF GUIDE Black**

(Contd. of page 7)

**14.3 Transport hazard class(es)**

· ADR



· Class 3 (F1) Flammable liquids.  
 · Label 3

· IMDG, IATA



· Class 3 Flammable liquids.  
 · Label 3

**14.4 Packing group**

· ADR, IMDG, IATA III

**14.5 Environmental hazards:**

· Marine pollutant: No

**14.6 Special precautions for user**

· Warning: Flammable liquids.

· EMS Number: F-E, S-E

· Stowage Category A

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category 3

· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations

· Technical instructions (air):

Class	Share in %
NK	25.5

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 9)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 15 (replaces version 14)

Revision: 19.01.2023

Trade name: **NEW SELF GUIDE Black**

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing data specification sheet:** Environment protection department

· **Abbreviations and acronyms:**

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Skin Sens. 1A: Skin sensitisation – Category 1A  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· **Data compared to the previous version altered.** \*

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **NEW SELF GUIDE HARDENER**

Article number: 86770

**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

**Application of the substance / the mixture** Hardening agent / curing agent

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

#### 1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**



GHS02



GHS07

**Signal word** Warning

**Hazard-determining components of labelling:**

Aliphatic polyisocyanate

n-butyl acetate

xylene

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

**Trade name: NEW SELF GUIDE HARDENER**

(Contd. of page 1)

Hydrocarbons, C9, aromatics

**Hazard statements**

- H226 Flammable liquid and vapour.
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing mist/vapours/spray.
- P280 Wear protective gloves / eye protection / face protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

- EUH066 Repeated exposure may cause skin dryness or cracking.
- Contains isocyanates. May produce an allergic reaction.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

- **Description:** Mixture of the substances listed below with harmless additions.

**Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	<i>n</i> -butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	50-75%
CAS: 28182-81-2 EC number: 931-274-8 Reg.nr.: 01-2119485796-17	Aliphatic polyisocyanate ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335; STOT SE 3, H336	<5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**
**General information**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation**

Supply fresh air and call for doctor for safety reasons.  
In case of unconsciousness bring patient into stable side position for transport.

**After skin contact**

Instantly wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.

**After eye contact** Rinse opened eye for several minutes under running water.

**After swallowing** Do not induce vomiting; instantly call for medical help.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

**Trade name: NEW SELF GUIDE HARDENER**

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO<sub>2</sub>, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Do not inhale explosion gases or combustion gases.  
Wear self-contained breathing apparatus.  
Wear full protective suit.
- **Additional information** Cool endangered containers with water spray jet.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow to enter drainage system, surface or ground water.  
Prevent material from reaching sewage system, holes and cellars.  
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Keep away from heat and direct sunlight.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store in cool location.
- **Information about storage in one common storage facility:** Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed containers.  
Protect from heat and direct sunlight.  
15-25°C
- **Storage class 3**
- **7.3 Specific end use(s)** No further relevant information available.

GB  
(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 3)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Components with limit values that require monitoring at the workplace:

##### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

##### 1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

#### Regulatory information WEL: EH40/2020

#### DNELs

##### 123-86-4 n-butyl acetate

Dermal	Acute systemic effect	11 mg/kg bw/day (Worker)
	Long term systemic effect	11 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	300 mg/m <sup>3</sup> (Worker)
	Acute local effect	600 mg/m <sup>3</sup> (Worker)
	Long term local effect	300 mg/m <sup>3</sup> (Worker)
	Acute systemic effect	600 mg/m <sup>3</sup> (Worker)

##### 28182-81-2 Aliphatic polyisocyanate

Inhalative	Acute local effect	1 mg/m <sup>3</sup> (Worker)
	Long term local effect	0.5 mg/m <sup>3</sup> (Worker)

##### 1330-20-7 xylene

Dermal	Long term local effect	3,182 mg/kg/day (Worker)
Inhalative	Acute local effect	442 mg/m <sup>3</sup> (Worker)
	Long term local effect	221 mg/m <sup>3</sup> (Worker)

#### Hydrocarbons, C9, aromatics

Dermal	Long term systemic effect	25 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	100 mg/m <sup>3</sup> (Worker)

#### PNECs

##### 123-86-4 n-butyl acetate

PNEC 0.18 mg/l (Aqua (freshwater))  
0.36 mg/ml (Aqua (intermittent))  
0.018 mg/ml (Aqua (marine water))  
0.981 mg/kg (Freshwater sediment)  
0.0981 mg/kg (Marine water sediment)  
35.6 mg/l (Sewage treatment plant)  
0.09 mg/kg (Soil)

##### 28182-81-2 Aliphatic polyisocyanate

PNEC 0.127 mg/l (Aqua (freshwater))  
1.27 mg/l (Aqua (intermittent))  
0.0127 mg/l (Aqua (marine water))  
266,700 mg/kg (Freshwater sediment)  
26,670 mg/kg (Marine water sediment)  
38.3 mg/l (Sewage treatment plant)  
53,182 mg/kg (Soil)

##### 1330-20-7 xylene

PNEC 0.327 mg/l (Aqua (freshwater))  
0.327 mg/l (Aqua (marine water))  
12.46 mg/l (Freshwater sediment)  
12.46 mg/l (Marine water sediment)  
6.58 mg/l (Sewage treatment plant)  
2.31 mg/kg (Soil)

(Contd. on page 5)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 4)

### Ingredients with biological limit values:

#### 1330-20-7 xylene

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists that were valid during the compilation were used as basis.

### 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Filter A (EN 141)

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed safety glasses. (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Colourless

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

Not determined

· **Flammability**

Flammable.

· **Lower and upper explosion limit**

· **Lower:**

1.7 Vol %

· **Upper:**

7.6 Vol %

· **Flash point:**

27 °C (ISO 3680:2005)

· **Decomposition temperature:**

Not determined.

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 5)

· <b>pH</b>	Mixture is non-soluble (in water).
· <b>Viscosity:</b>	
· <b>Kinematic viscosity at 20 °C</b>	> 180 mm <sup>2</sup> /s
· <b>dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>Water:</b>	Not miscible / difficult to mix
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C</b>	0.975 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
<b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.
<b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:**  
Strong acids and oxidizing agents  
Alkalis  
Alcohols, amines, aqueous acids and alkalis
- **10.6 Hazardous decomposition products:**  
Formation of toxic gases is possible during heating or in case of fire.  
Carbon monoxide and carbon dioxide

GB  
(Contd. on page 7)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 6)

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

123-86-4 n-butyl acetate		
Oral	LD50	14,000 mg/kg (Rat)
28182-81-2 Aliphatic polyisocyanate		
Oral	LD50	>2,500 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)
Hydrocarbons, C9, aromatics		
Oral	LD50	>2,000-≤5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)

· **Skin corrosion/irritation** Causes skin irritation.

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.

· **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

#### 11.2 Information on other hazards

· **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

#### 12.1 Toxicity

· **Aquatic toxicity:**

123-86-4 n-butyl acetate		
EC50 (48 hr)	44 mg/l	(Daphnia magna)
EC50 (72 hr)	674.7 mg/l	(Desmodesmus subspicatus)
LC50 (48 hr)	44 mg/l	(Daphnia magna)
LC50 (96 hr)	18 mg/l	(Pimephales promelas)
NOEC (72 hr)	200 mg/l	(Desmodesmus subspicatus)
28182-81-2 Aliphatic polyisocyanate		
EC10	>100 /48 hr	(Daphnia magna) (OECD 202)
EC50 (72 hr)	3,828 mg/l	(Activated sludge) (OECD 209)
LC50 (96 hr)	>100 mg/l	(Brachydanio rerio)
1330-20-7 xylene		
CE50	10 mg/l	(Fish) (72h)
EC50 (48 hr)	7.4 mg/l	(Daphnia magna)
LC50 (96 hr)	3.77-13.5 mg/l	(Fish)
Hydrocarbons, C9, aromatics		
EL50 (48 hr)	3.2 mg/l	(Daphnia magna)
LL50 (96 hr)	9.2 mg/l	(Oncorhynchus mykiss)
NOEC (72 hr)	1 mg/l	(Pseudokirchneriella subcapitata)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

#### 12.7 Other adverse effects

· **Remark:** Harmful to fish

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

Trade name: NEW SELF GUIDE HARDENER

(Contd. of page 7)

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Harmful to aquatic organisms

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN1263

· **14.2 UN proper shipping name**

· **ADR** 1263 PAINT RELATED MATERIAL

· **IMDG, IATA** PAINT RELATED MATERIAL

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.

· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.

· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

· **Warning:** Flammable liquids.

· **Kemler Number:** 30

· **EMS Number:** F-E, S-E

· **Stowage Category** A

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L

· **Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category** 3

(Contd. on page 9)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

Trade name: **NEW SELF GUIDE HARDENER**

(Contd. of page 8)

· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT RELATED MATERIAL, 3, III

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

#### · National regulations

#### · Technical instructions (air):

Class	Share in %
NK	65.0

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Department issuing data specification sheet: Environment protection department

#### · Abbreviations and acronyms:

- RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 16 (replaces version 15)

Revision: 19.01.2023

**Trade name: NEW SELF GUIDE HARDENER**

(Contd. of page 9)

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**Data compared to the previous version altered. \***

GB