

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **PLAZ TEX BLACK**

Article number: 86735

1.2 Relevant identified uses of the substance or mixture and uses advised against
FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Coating compound / Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



health hazard

STOT RE 2

H373 May cause damage to organs through prolonged or repeated exposure.



environment

Aquatic Acute 1

H400 Very toxic to aquatic life.

Aquatic Chronic 1

H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4

H332 Harmful if inhaled.

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

Lact.

H362 May cause harm to breast-fed children.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: PLAZ TEX BLACK

(Contd. of page 1)

Hazard pictograms

GHS02 GHS07 GHS08 GHS09

Signal word Danger**Hazard-determining components of labelling:**

xylene
3-(isodecyloxy)propylammonium acetate
Alkanes, C14-17, chloro

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H362 May cause harm to breast-fed children.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe mist/vapours/spray.
P262 Do not get in eyes, on skin, or on clothing.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:**

85535-85-9 Alkanes, C14-17, chloro

vPvB:

85535-85-9 Alkanes, C14-17, chloro

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Description:** Mixture of the substances listed below with harmless additions.**Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	Dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%
CAS: 85535-85-9 EINECS: 287-477-0 Reg.nr.: 01-2119519269-33	Alkanes, C14-17, chloro ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362, EUH066 PBT; vPvB	10-25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 28701-67-9 EINECS: 249-166-8	3-(isodecyloxy)propylammonium acetate ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317; STOT SE 3, H335	<5%

Additional information For the wording of the listed hazard phrases refer to section 16.GB
(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: **PLAZ TEX BLACK**

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly remove any clothing soiled by the product.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Rinse out mouth.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Open and handle container with care.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on flames or red-hot objects.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: PLAZ TEX BLACK

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

 Not required.

Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Storage class 2 B

7.3 Specific end use(s)

 No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

115-10-6 Dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm
	Long-term value: 766 mg/m ³ , 400 ppm

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

Regulatory information

 WEL: EH40/2020

DNELs

115-10-6 Dimethyl ether

Inhalative	Long term systemic effect	1,894 mg/m ³ (Worker)
------------	---------------------------	----------------------------------

85535-85-9 Alkanes, C14-17, chloro

Dermal	Long term systemic effect	47.9 mg/kg/day (Worker)
Inhalative	Long term systemic effect	1.6 mg/m ² (Worker)

1330-20-7 xylene

Dermal	Long term local effect	3,182 mg/kg/day (Worker)
Inhalative	Acute local effect	442 mg/m ³ (Worker)
	Long term local effect	221 mg/m ³ (Worker)

PNECs

115-10-6 Dimethyl ether

PNEC	0.155 mg/l (Aqua (freshwater))
	1,549 mg/l (Aqua (intermittent))
	0.016 mg/l (Aqua (marine water))
	0.681 mg/l (Freshwater sediment)
	0.069 mg/l (Marine water sediment)
	0.045 mg/l (Soil)

85535-85-9 Alkanes, C14-17, chloro

PNEC	0.001 mg/l (Aqua (freshwater))
	0.0002 mg/l (Aqua (marine water))
	5 mg/kg (Freshwater sediment)
	1 mg/kg (Marine water sediment)
	80 mg/l (Sewage treatment plant)
	10.5 mg/kg (Soil)

1330-20-7 xylene

PNEC	0.327 mg/l (Aqua (freshwater))
	0.327 mg/l (Aqua (marine water))
	12.46 mg/l (Freshwater sediment)
	12.46 mg/l (Marine water sediment)
	6.58 mg/l (Sewage treatment plant)
	2.31 mg/kg (Soil)

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: PLAZ TEX BLACK

(Contd. of page 4)

Ingredients with biological limit values:**1330-20-7 xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Only during spraying without adequate removal by suction.

Filter AX / P (EN 14387)

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses (EN 166)

Tightly sealed safety glasses. (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· **General Information**

· **Physical state**

Aerosol

· **Colour:**

According to product specification

· **Odour:**

Light

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

1.8 Vol %

· **Upper:**

9.5 Vol %

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: PLAZ TEX BLACK

(Contd. of page 5)

· Flash point:	Not applicable, as aerosol
· Ignition temperature:	410 - 580 °C
· Decomposition temperature:	Not determined.
· pH	Mixture is non-polar/aprotic.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible / difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C	0.887 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	675g/l VOC
· Change in condition	
· Evaporation rate	Not applicable.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: **PLAZ TEX BLACK**

Carbon monoxide and carbon dioxide

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)

· **Skin corrosion/irritation** Causes skin irritation.

· **Serious eye damage/irritation** Causes serious eye irritation.

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.

· **Reproductive toxicity** May cause harm to breast-fed children.

· **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.

11.2 Information on other hazards

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

· **Aquatic toxicity:**

115-10-6 Dimethyl ether

EC50 (48 hr)	>4,000 mg/l (Daphnia magna)
EL50 (48 hr)	4,001 mg/l (Daphnia magna)
LC50 (48 hr)	755,549 mg/l (Daphnia magna)
LC50 (96 hr)	154.9 mg/l (Algae)
	4,001 mg/l (Poecilia reticulata)

1330-20-7 xylene

CE50	10 mg/l (Fish) (72h)
EC50 (48 hr)	7.4 mg/l (Daphnia magna)
LC50 (96 hr)	3.77-13.5 mg/l (Fish)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

85535-85-9 Alkanes, C14-17, chloro

· **vPvB:**

85535-85-9 Alkanes, C14-17, chloro

· **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:** Very toxic for fish

· **Additional ecological information:**

· **General notes:**

Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: **PLAZ TEX BLACK**

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· **ADR, IMDG, IATA** UN1950

· 14.2 UN proper shipping name

· **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
 · **IMDG** AEROSOLS (Alkanes, C14-17, chloro chlorinated paraffins, C14-17, 3-(isodecyloxy)propylammonium acetate), MARINE POLLUTANT
 · **IATA** AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· **ADR**



· **Class** 2 5F Gases.
 · **Label** 2.1

· **IMDG**



· **Class** 2.1 Gases.
 · **Label** 2.1

· **IATA**



· **Class** 2.1 Gases.
 · **Label** 2.1

· 14.4 Packing group

· **ADR, IMDG, IATA** Void

· 14.5 Environmental hazards:

· **Marine pollutant:** Product contains environmentally hazardous substances: Alkanes, C14-17, chloro
 · **Special marking (ADR):** Symbol (fish and tree)
Symbol (fish and tree)

· 14.6 Special precautions for user

· **Warning:** Gases.
 · **Kemler Number:** -
 · **EMS Number:** F-D,S-U
 · **Stowage Code** SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A.
 For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: PLAZ TEX BLACK

(Contd. of page 8)

· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

· **Transport category** 2

· **Tunnel restriction code** D

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E1 Hazardous to the Aquatic Environment

P3a FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **National regulations**

· **Technical instructions (air):**

Class	Share in %
NK	42.0

· **Water hazard class:** Water danger class 3 (Self-assessment): extremely hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H362 May cause harm to breast-fed children.
H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 21 (replaces version 20)

Revision: 12.01.2023

Trade name: PLAZ TEX BLACK

(Contd. of page 9)

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing data specification sheet:** Environment protection department

· **Abbreviations and acronyms:**

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Lact.: Reproductive toxicity – effects on or via lactation

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· **Data compared to the previous version altered.** *