



Anti-Slip Tape

Very thin mineral-coated tape with high adhesion for anti-slip protection on smooth and slippery surfaces.



Features & Benefits

- Durable mineral coating - Withstands light to heavy shoe-traffic for a long time
- Water and UV-resistant - Can be used indoors and outdoors
- Very thin - Low profile reduces trip hazards
- High adhesion - Bonds on most surfaces
- Over paintable - Will not lose its rubbing properties

P/N	Product	S/C	Packaging
86880	Anti-Slip Tape black/yellow	ASTBY	50 mm x 18 m roll
86881	Anti-Slip Tape black	ASTB	25 mm x 18 m roll
86882	Anti-Slip Tape translucent	ASTT	25 mm x 18 m roll

Application

For all areas where anti-slip protection is important and where safety is priority. The KENT Anti-Slip Tape has a 60 grid mineral coating, which creates a durable rough surface to prevent slips and falls.

KENT Anti-Slip Tape tape can be used both indoors and outdoors - on stairs, ramps, ladders, building entrances, hotel lobbies, reception areas, around swimming pools, boat decks and all slippery surfaces in workshops and production facilities.

Black/yellow version can be used both for marking and prevention of slipping. Black and translucent are optimal for dark or light flooring.

Instructions

1. Clean surface with KENT Soft Surface Cleaner. Ensure surfaces to dry and free from dust and grease.
2. Cut to the desired length and remove the carrier. Avoid touching the exposed adhesive surface of the tape. Apply to surface.
3. Ensure that tape is firmly pressed down at maximum pressure level.
4. The full strength will be reached after 24 hrs at +23° C.



Technical Information

General info

Carrier:	PVC film
Adhesive layer:	Acrylic solvent based
Length:	18 m
Width:	25 mm / 50 mm
Thickness:	0.90 mm
Shelf life:	24 months
Custom tariff code:	68053000
VOC:	0

Adhesive strength:	15 N / 25 mm
Tensile strength:	> 40 N / 25 mm
Elongation:	> 25%
Application temperature:	0° C to +35° C
Service temperature:	+5° C to +50° C



SDS available on www.kent europe.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd., or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House,
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel : 0800 136925 or 01383 723344 between 08:30-17:30
Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: KENTsales.UK@kent europe.com

REV: 18/08/2020