



Dual Trim Masking Tape

A masking tape that improves the efficiency of the process without leaving paint lines.

Features & Benefits

- Seals and protects vehicle insides from overspray - the safest application when masking
- Versatile use on vehicles – one tape for almost all applications
- Simplifies the masking process - can halve the time required
- Leaves no hard paint edges - no rework necessary



| P/N | Product | S/C | Packaging |
|-------|------------------------|------|-----------|
| 86760 | Dual Trim Masking Tape | DTMT | Each |

Application

Dual Trim Masking Tape is the perfect product for masking and protecting the insides of the vehicle from overspray when painting roof rails, door shuts/ jams, boot/trunk, bonnets/hoods and wing/ fender/guard. Having adhesive on adjacent sides improves the efficiency of the process without leaving paint lines, in addition the rigid edge allows masking of individual panels as well as enabling easy removal after use.

Instructions

1. Stick the tape to the underside of the roof rail by removing the liner from the narrow section of tape and repeat.
2. Press Dual Trim Masking Tape firmly and then close the door.
3. Remove the protective film from the adhesive surface and pull it over the rubber seal.

N.B.: To mask along a straight section tear off a section no longer than 20cm and slide in and leaver back the trim so that a small gap is created. Make sure that the next piece overlaps the last piece



Technical Information

General info:

| | |
|---------------------------|------------|
| Part number: | 86760 |
| Stock Code: | DTMT |
| Size per roll: | 75mm x 20m |
| Product Packaging: | each |

| | |
|--------------------------------|--|
| Shelf life: | 12 months |
| Custom Tariff Code: | 48084000 |
| Thickness: | 0,285µm |
| Width: | 75 mm (+/- 1mm) |
| Length: | 20m |
| Tensile strength: | > 50 N/cm AFERA 5004 |
| Elongation at break: | > 10% AFERA 5004 |
| Temperature Resistance: | 80° C for 1 hour |
| Adhesive: | Rubber |
| Carrier: | Crepe paper, PE film and PES lifting tab |



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of Barnes Group KENT Ltd. This data sheet and its contents (the "Information") belong to the Barnes Group KENT Ltd or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of Barnes Group KENT Ltd.

Registered Office: Barnes Group KENT Ltd. Registered in England. Pitreavie Crescent, Pitreavie Business Park, Dunfermline Fife KY11 8UQ. Registered in England N°: 1164516
VAT Registration N°: 887 1228 94
All rights reserved.

Barnes Group KENT Ltd. Registered in England. Pitreavie Crescent, Pitreavie Business Park, Dunfermline Fife KY11 8UQ. **Tel :** Freephone 0800 136925 or 01383 737172 between 08:30-17:00. For out of hours queries please Fax us on 01383 735829 or **Email:** KENTsales.UK@kenteurope.com

Rev: 23.03.20