



NST Rapid Sand

NST Rapid Sand is a styrene-free multifunctional and user friendly bodyfiller for different surfaces

Features & Benefits

- 0% Styrene – prevents bad smells and reduces health risks caused by styrene
- Extraordinary drying properties – no time loss compared to other styrene-free putties
- Suitable for all sheet metal surfaces – multifunctional applicable
- Creamy texture – provides a perfect pinhole-free coating with good flexibility
- No tacky surface - easy sanding without clogging sandpaper



P/N	Product	Content	Packaging
86744	NST Rapid Sand Green	1000 g	Can
86989	NST Rapid Sand Green	1500 g	Cartridge

Application

NST Rapid Sand is a styrene-free, user friendly bodyfiller. Characterized by creamy texture and easy sanding without clogging sandpaper. Suitable for filling up dents and other imperfections on all sheet metal surfaces, as well on zinc-coated and aluminum.

Instructions

1. The surface must be clean, dry, degreased and matted with abrasives (P80 – P120)
2. Thoroughly mix putty by weight with 2-3%
3. Apply within 4 - 6 minutes at 20C
4. Allow 30 minutes to dry before sanding
5. Sanding/ dry the filled area with P120-P240



Technical Information

General Info:

Consistency:	Smooth non-sag paste
Colour:	Green
Shelf Life (months):	12
Customs Tariff Code:	32141010
VOC:	250 g/l
Accessories:	Spatula in lid & hardener
Pieces per unit:	1

Working time:	3-5 min
Drying time:	30 min 20°C, 5 min IR short waves distance 80 cm, max. temp. 80°C or special drying programme of the IR unit
Dry film thickness:	Product can be applied in multiple layers but never over 4mm total dry thickness.
Wet on wet:	No
Shore D hardness:	80 (24 h/20°C)
Application temperature (min.):	10 °C
Application temperature (max.):	30 °C
Temperature resistance (max.):	80 °C
Temperature resistance (min.):	-20 °C
Solid content:	94-95 wt.% (comp. A+B)

Higher temperature can reduce the pot life and accelerates the drying time. Not to be used on: Thermoplastic parts, especially PP, PE, PTFE, wash primers, 1K acrylic or nitrocellulose products



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of name KENT (United Kingdom) Ltd.
This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was

aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd.
Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Way, Pitreavie Business Park, Dunfermline, Fife KY11 8US
Tel.: 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'.
For out of hours queries please Fax us on 01383 735829 or Email: KENTsales.UK@kenteurope.com

2022-06-08