

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 41 (replaces version 40)

Revision: 19.01.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **Tyre Dressing**

Article number: 86952

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

#### Application of the substance / the mixture

Cleaning agent / Cleaner

Surface protection

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

#### 1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

#### Hazard pictograms



GHS02

#### Signal word Danger

#### Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Additional information:

Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]. May produce an allergic reaction.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 41 (replaces version 40)

Revision: 19.01.2023

**Trade name: Tyre Dressing**

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

· **Description:** Mixture of the substances listed below with harmless additions.

##### Dangerous components:

CAS: 68476-85-7 EINECS: 270-704-2	Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)). ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-25%
CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 01-2119456816-28	Ethane-1,2-diol ⚠ STOT RE 2, H373; ⚠ Acute Tox. 4, H302	0-<5%
CAS: 166736-08-9	OXIRANE, 2-METHYL-, POLYMER WITH OXIRANE, MONO(2-PROPYLHEPTYL) ETHER ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302	0-<3%
CAS: 7632-00-0 EINECS: 231-555-9 Reg.nr.: 01-2119471836-27	Sodium nitrite ⚠ Ox. Sol. 3, H272; ⚠ Acute Tox. 3, H301; ⚠ Aquatic Acute 1, H400	0-<0.25%

##### Regulation (EC) No 648/2004 on detergents / Labelling for contents

Aliphatic hydrocarbons	≥5 - <15%
preservation agents (1,2-BENZOISOTHIAZOL-3(2H)-ONE, mixture of 5-Chloro-2-methyl-isothiazol-3(2H)-one and 2-Methylisothiazol-3(2H)-one with magnesium chloride and magnesium nitrate.), Non-ionic surfactants	<5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- **After inhalation** Supply fresh air and call for doctor for safety reasons.
- **After skin contact**  
Instantly wash with water and soap and rinse thoroughly.  
Generally the product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing**  
Rinse out mouth.  
Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.  
Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Do not inhale explosion gases or combustion gases.  
Wear self-contained breathing apparatus.
- **Additional information** Cool endangered containers with water spray jet.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources

(Contd. on page 3)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 41 (replaces version 40)

Revision: 19.01.2023

**Trade name: Tyre Dressing**

(Contd. of page 2)

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

**6.3 Methods and material for containment and cleaning up:**

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on flames or red-hot objects.

**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:**

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Store container in a well ventilated position.

Protect from heat and direct sunlight.

5-35°C

**Storage class 2 B****7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:****68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).**

WEL Short-term value: 2180 mg/m<sup>3</sup>, 1250 ppm  
 Long-term value: 1750 mg/m<sup>3</sup>, 1000 ppm  
 Carc (if LPG contains > 0.1% of buta-1.3-diene)

**107-21-1 Ethane-1,2-diol**

WEL Short-term value: 104\*\* mg/m<sup>3</sup>, 40\*\* ppm  
 Long-term value: 10\* 52\*\* mg/m<sup>3</sup>, 20\*\* ppm  
 Sk \*particulate \*\*vapour

**Regulatory information** WEL: EH40/2020**DNELs****107-21-1 Ethane-1,2-diol**

Dermal	Long term systemic effect	106 mg/kg/day (Worker)
Inhalative	Long term local effect	35 mg/m <sup>3</sup> (Worker)

**137-16-6 SODIUM LAUROYL SARCOSINATE**

Dermal	Long term systemic effect	20 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	70.53 mg/m <sup>3</sup> (Worker)

**7632-00-0 Sodium nitrite**

Inhalative	Long term systemic effect	2 mg/m <sup>3</sup> (Worker)
	Acute systemic effect	2 mg/m <sup>3</sup> (Worker)

**PNECs****107-21-1 Ethane-1,2-diol**

PNEC	10 mg/l (Aqua (freshwater))
------	-----------------------------

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 41 (replaces version 40)

Revision: 19.01.2023

**Trade name: Tyre Dressing**

(Contd. of page 3)

10 mg/l (Aqua (intermittent))  
 1 mg/l (Aqua (marine water))  
 20.9 mg/kg (Freshwater sediment)  
 3.7 mg/kg (Marine water sediment)  
 199.5 mg/l (Sewage treatment plant)  
 1.53 mg/l (Soil)

**137-16-6 SODIUM LAUROYL SARCOSINATE**

PNEC 8.91 µg/l (Aqua (freshwater))  
 89.1 µg/l (Aqua (intermittent))  
 891 µg/l (Aqua (marine water))  
 3 mg/l (Sewage treatment plant)

**7632-00-0 Sodium nitrite**

PNEC 0.005 mg/ml (Aqua (freshwater))  
 0.006 mg/ml (Aqua (marine water))  
 0.019 mg/kg (Freshwater sediment)  
 0.022 mg/kg (Marine water sediment)  
 21 mg/l (Sewage treatment plant)  
 0.001 mg/kg (Soil)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Take off immediately all contaminated clothing  
 Wash hands during breaks and at the end of the work.

· **Breathing equipment:**

Only during spraying without adequate removal by suction.  
 Filter A2 / P2 (EN 14387)

· **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Wear suitable gloves tested to EN 374  
 Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

· **General Information**

· **Physical state**

Aerosol

· **Colour:**

Whitish

(Contd. on page 5)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 41 (replaces version 40)

Revision: 19.01.2023

**Trade name: Tyre Dressing**

(Contd. of page 4)

· <b>Odour:</b>	Mild
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Not determined
· <b>Boiling point or initial boiling point and boiling range</b>	Not applicable, as aerosol
· <b>Flammability</b>	Not applicable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	Not determined.
· <b>Upper:</b>	Not determined.
· <b>Flash point:</b>	Not applicable, as aerosol
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>Water:</b>	Emulsifiable
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density and/or relative density</b>	
· <b>Density</b>	Not determined
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Aerosol
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Not determined.
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not applicable.

· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 41 (replaces version 40)

Revision: 19.01.2023

**Trade name: Tyre Dressing**

(Contd. of page 5)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Formation of toxic gases is possible during heating or in case of fire.  
Carbon monoxide and carbon dioxide

### SECTION 11: Toxicological information

#### · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values that are relevant for classification:

##### 107-21-1 Ethane-1,2-diol

Oral LD50 5,840 mg/kg (Rat)

Dermal LD50 9,530 mg/kg (rbt)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

#### · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### 68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).

EC50 (96 hr) 12.32 mg/l (Algae) ((Q)SAR calculation method)

LC50 (48 hr) 69.43 mg/l (Daphnia magna) ((Q)SAR calculation method)

LC50 (96 hr) 49.47 mg/l (Fish) ((Q)SAR calculation method)

##### 107-21-1 Ethane-1,2-diol

EC50 (96 hr) 6.5-13 mg/l (Algae)

6,500-13,000 mg/l (Selenastrum capricornutum)

EC50 (48 hr) &gt;100 mg/l (Daphnia magna)

LC50 (96 hr) 40,761 mg/l (Fish)

72,860 mg/l (Pimephales promelas)

NOEC (21 days) 15,380 mg/l (Pimephales promelas)

##### 137-16-6 SODIUM LAUROYL SARCOSINATE

EC50 (48 hr) 29.7 mg/l (Crustacea)

EC50 (72 hr) 79 mg/l (Algae)

- **12.2 Persistence and degradability** Biodegradable
- **12.3 Bioaccumulative potential** Does not accumulate in organisms
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water.  
Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

(Contd. on page 7)

GB



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 41 (replaces version 40)

Revision: 19.01.2023

**Trade name: Tyre Dressing**

Danger to drinking water if even extremely small quantities leak into soil.

(Contd. of page 6)

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information****14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN1950

**14.2 UN proper shipping name**

· **ADR** 1950 AEROSOLS  
 · **IMDG** AEROSOLS  
 · **IATA** AEROSOLS, flammable

**14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.  
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1 Gases.  
 · **Label** 2.1

**14.4 Packing group**

· **ADR, IMDG, IATA** Void

**14.5 Environmental hazards:**

· **Marine pollutant:** No

**14.6 Special precautions for user**

· **EMS Number:** Warning: Gases.  
 F-D, S-U  
 SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A.  
 For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
 SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
 For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.  
 For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Segregation Code**

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 41 (replaces version 40)

Revision: 19.01.2023

**Trade name: Tyre Dressing**

(Contd. of page 7)

**· Transport/Additional information:****· ADR****· Limited quantities (LQ)**

1L

**· Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

**· Transport category**

2

**· Tunnel restriction code**

D

**· IMDG****· Limited quantities (LQ)**

1L

**· Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

**· UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information****· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****· Directive 2012/18/EU****· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category P3a** FLAMMABLE AEROSOLS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**· National regulations****· Water hazard class:** Water danger class 3 (Self-assessment): extremely hazardous for water.**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

H220 Extremely flammable gas.

H272 May intensify fire; oxidiser.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

**· Department issuing data specification sheet:** Environment protection department**· Abbreviations and acronyms:**

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Ox. Sol. 3: Oxidizing solids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

**· Data compared to the previous version altered.** \*