



# Belt Dressing

A grip improver and re-conditioner for drive belts. Restores flexibility and improves power transmission



## Features & Benefits

- Fast action and non-corrosive product
- A unique formulation of polymeric resins and conditioning compounds reduces belt glaze
- Elastomeric conditioners protect the belt from oxidation, drying and hardening
- Improves power transmission by halting belt slippage.
- Anti-slip frictioner provides positive gripping action between the belt and pulley

P/N	Product	S/C	Packaging
86502	Belt Dressing	SBD	400 ml aerosol

## Application

KENT Belt Dressing is designed for use on all types of drive belt including round, flat, V, leather, rubber or combination of materials.

It is particularly effective for belts used on power steering units, alternators, hydraulic pumps, camshafts and refrigeration units.

## Instructions

1. Check belt for wear, do not use on worn belts. Adjust belt tension.
2. Shake can well before use.
3. Spray a light even coat with the belt running slowly. Allow to penetrate for 1 minute.
4. Switch off belt and allow to dry for 15 minutes.

NB Spray is flammable, for machines where high voltage is involved (24V or more) the machine should be switched off and when applying Belt Dressing. After evaporation switch current on.



## Technical Information

<b>Base:</b>	Mineral oil
<b>Appearance/colour:</b>	Clear golden liquid
<b>Odour:</b>	Solvent distillate
<b>Specific gravity (25 °C):</b>	0.770 g/l
<b>pH:</b>	Not applicable
<b>Dilution ratio:</b>	Not applicable
<b>Solubility in water:</b>	Unsoluble
<b>Application temp:</b>	10 - 25 °C
<b>Drying time:</b>	Not determined
<b>Flash point:</b>	Not applicable, as aerosol
<b>VOC:</b>	588 g/l
<b>Shelf life:</b>	24 months
<b>Custom tariff code:</b>	3403 99 00



SDS available on [www.kent europe.com](http://www.kent europe.com)

### Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd.

**Registered Office:** Amber House,  
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ  
*All rights reserved.*

**KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US** Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: [KENTsales.UK@kent europe.com](mailto:KENTsales.UK@kent europe.com)

REV: 25/01/2017