



Xtreme Force Tape

Reinforced double-sided tape with strong and immediate bonding on smooth and rough surfaces.



Features & Benefits

- 100% adhesion – bonds to mostly everything, also for hard-to-bond plastics, incl. PE & PP
- Extremely high power - Will not get loose
- Immediate adhesion - No need to clamp or hold the bonded element
- Reinforcement mesh inside the tape - Will not tear

P/N	Product	S/C	Packaging
86665	Xtreme Force Tape	XFT	19 mm x 10 m roll

Application

Unique, double-sided adhesive tape with extreme hold on many different materials including glass, metal, ceramics, glass fiber reinforced plastic, wood, brick and plastics that are difficult to bond, such as polypropylene and polyethylene. Xtreme Force Tape is particularly resistant to solvents, chemicals and UV light.

Xtreme Force Tape can be used for emblems, name tags, signs, mirrors, mounting rails, exhibition stand construction, sensors, safety signs etc., in workshops, hospitals, retirement homes, daycare centers, schools, shopping centers, hotels, sign manufacturers, property management, technical departments, etc.

Instructions

1. Clean and degrease both surfaces with either KENT Acrysol or KENT Soft Surface Cleaner.
2. Cut suitable length of tape and apply first to the substrate which is hardest to bond, ensuring 100% contact. Press firmly.
3. Remove the liner. Avoid touching exposed adhesive surface of the tape, as this impairs the performance.
4. Align pieces and firmly press into position.



Technical Information

General info:

Adhesive:	Synthetic rubber
Carrier material:	Polyester fabric
Liner:	Polypropylene
Colour:	Translucent
Width:	19 mm
Length:	10 m
Thickness:	0,80 mm (Tape: 0,73 mm)
Shelf life:	12 months
Custom tariff code:	3919 10 80

Tensile strength:	70 N / 25mm
Adhesive strength:	open side: 55 N / 25 mm covered side: 40 N / 25 mm
Shear strength:	168 hrs
Full strength achieved:	24 hours
Elongation:	30 %
Temp resistance:	- 40° C to + 50° C
Application temperature:	+ 15° C to + 30° C



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd., or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House,
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: KENTsales.UK@kenteurope.com

REV: 30/06/2021