



Plaz Tex Black

Allows the replication of the molded texturing on modern plastic bumpers, dashboards and other plastic fittings.



Features & Benefits

- Coarse textured paint – 2 nozzle variants to match OEM finishes
- Suitable for most plastics – versatile applications
- Excellent coverage with each coat – time and cost saving
- Compatible with most leading paint systems – use with confidence, no comeback

P/N	Product	S/C	Content	Packaging
86735	Plaz Tex Black Black	PTB	400 ml	Aerosol

Application

Plaz Tex Black is designed for retexturing plastics after a plastic repair has been undertaken. Thanks to the two different spray heads, almost any finish can be achieved, even to restore weathered surfaces to a rich, black matt. Plaz Tex Black can be used for cosmetic repairs to bumpers, spoilers, air vents, side skirts, mirror housings and plastic wheel covers, holes in dashboards, centre consoles, plastic door panels and dashboard trim, can also be used on metal parts. Applications will include plastic repair customers, body shops, SMART repair specialists, used vehicle preparation sites, fleet repair specialists.

Instructions

1. Thoroughly clean the area to be painted.
2. Choose the desired spray head and shake the can thoroughly before using.
3. If necessary, mask off area to be sprayed.
4. Spray light coats from a distance of 50 - 55 cm.
5. Allow minimum of 5 - 10 minutes between coats.
6. Repeat steps 3 - 4 until desired finish is achieved.
7. It will be necessary to blend / feather the edges of the repair with the natural texture of the plastic.
8. Turn can upside down and spray after use to prevent clogging.

N.B.: Variation in spraying distance from the surface will produce finer or coarser textures.



Technical Information

General Info:

Consistency:	Aerosol
Odour:	Solvent
Shelf Life (months):	24
Customs Tariff Code:	3208 20 10
VOC:	575 g/l
Pieces per unit:	1

Application distance:	depends on the desired finish cm
Drying time:	5 - 15 min at 20°C
Dry film thickness:	40 – 70 microns
Coverage:	0.5 – 1.0 m ² per can
Number of coats:	As required
Dry time between coats:	5 - 10 min at 20°C min
Temperature resistance (max.):	+50 °C
Temperature resistance (min.):	-10 °C



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of name KENT (United Kingdom) Ltd.
This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was

aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd.
Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Way, Pitreavie Business Park, Dunfermline, Fife KY11 8US
Tel.: 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.
For out of hours queries please Fax us on 01383 735829 or Email: KENTsales.UK@kenteurope.com

2021-07-22