

Silicone Grease

A high quality 100% silicone grease for lubrication and moisture protection.



Features & Benefits

- No fatty acids will not harm rubber, plastic or nylon
- · Does not run stays where it is applied
- Leaves a greasy film isolates & protects against moisture oxidation
- High dielectric breakdown voltage prevents arcing on electrics
- Will not dry out or harden provides protection under most adverse conditions
- Lubricates & feeds rubber promotes longer life on rubber components
- · Water resistant will not wash off
- · Resists UV prevents weather-strips cracking

P/N	Product	S/C	Packaging	
34920	Silicone Grease	SGA	400 ml aerosol	

Application

Mainly purchased as a protection for electrical connections, KENT Silicone Grease is suitable for coating terminals prior to assembly, therefore providing permanent protection against water penetration and oxidation.

Being 100% pure silicone, with no bulking agents, it is totally safe on sensitive materials such as gold plated terminals used on many vehicles such as Fords, as well as plastic & nylon connection blocks found on most vehicles. Provides good lubrication and protection of brake, steering and gear change components.

It is also a first class lubricant and is suitable for specialized areas such as curtain sided truck runners and roller door guides on emergency vehicles. Additionally, as a protection against UV and premature aging, when used on rubber items such as door weather-strips. The high viscosity makes it suitable as a valve and pump packing lubricant with lasting qualities. Can be used also for process instruments and as a lubricant for ground glass joints and stop-cocks under vacuum conditions.

Instructions

- 1. Shake can well before use.
- 2. Spray directly on to the area where the coating is required.
- N.B.: For best results the product should be used at room temperature, approx. 18 °C and the surface has to be free from dust, dirt, oxidation and old grease.



Technical Information

Base: Silicone

Consistency: Slightly viscous liquid Colour: Clear/translucent Odour: Characteristic Shelf life: 24 months

Custom tariff code: 3403 9910 VOC: 540 g/l

Specific gravity: 0.747 g/ml

Flash point: Not applicable, as aerosol

Penetration worked: Not determined Penetration unworked: Not determined Temp range: -75 °C to +260 °C Dielectric strength: 400 volts / mil 25 °C

1.0 x 1015 Ohm-cm 25 °C Volume resistivity:



SDS available on www.kenteurope.com

Terms and Condition

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products information included or omitted. Liability for loss or damage
resulting from any reliance on the Information or use of it (including

All rights reserved.

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline,

Fife KY11 8US Tel: 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or

Email: KENTsales.UK@kenteurope.com

REV: 25/01/2017