



2K Crystal Clear

A crystal clear, extremely durable, chip and UV-resistant film



Features & Benefits

- 2K ready to use technology - no activation required
- No pot life - no wasted paint
- Extremely durable - chemical, UV and scratch resistant
- Wide field of application - OEM finish, old paints, bare aluminum, bare & galvanized steel, wood
- High and hard dry film thickness - great polishability
- Forms a deep and shiny surface - without the risk of dripping

P/N	Product	Content	Packaging
86892	2K Crystal Clear	400 ml	Aerosol

Application

KENT 2K Crystal Clear is a 2-component polyurethane mixture that forms a chip- and UV-resistant film that is not only resistant to chemicals but can also be used on a wide variety of substrates such as water- and solvent-based paints, bare aluminum, bare and galvanized steel, and wood. Its high film thickness, durability and excellent polishability make 2K Crystal Clear the product of choice when it comes to part painting or spot repair. Due to its special formulation 2K Crystal Clear provides an instant deep and high gloss OEM level finish without material run-off.

Instructions

1. Shake well before use at least 3 minutes
2. Test the spray pattern on another surface
3. Application in 2-3 spray coats with a distance of 15-25 cm and a flash-off time between coats of 5 min
4. Final flash-off time 30min
5. Drying time: 30 min at 60°C, 12hrs at 20°C or specify IR drying program
6. To avoid nozzle clogging turn aerosol upside down and spray for 5 seconds



Technical Information

General Info:

Consistency:	Aerosol
Base material:	Special solvent-based 2K polyurethane
Odour:	Solvent
Shelf Life (months):	36
Customs Tariff Code:	32089091
VOC:	625 g/l
Pieces per unit:	1

Application distance:	15-25 cm
Drying time:	30 min at 60°C, 12 hrs at 20°C, Specific IR drying system
Dry film thickness:	30-40µm
Coverage:	3m ²
Number of coats:	2-3
Dry time between coats:	5 min
Application temperature (min.):	18 °C
Application temperature (max.):	25 °C
Temperature resistance (max.):	150 °C

Information valid at 20°C (68°F), relative air humidity 35% - 75%. No to be used on Styrofoam or alkyd paints. Final hardness & chemical resistance: 8-10 days.



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of name KENT (United Kingdom) Ltd.

This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was

aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House,
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Way, Pitreavie Business Park, Dunfermline, Fife KY11 8US

Tel.: 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'.

For out of hours queries please Fax us on 01383 735829 or **Email:** KENTsales.UK@kenteurope.com

2024-02-24