

# **Performance Compound 2**

Performance Compound 2 is an ultra-fine compound which is ideal for blending in, matching of gloss levels and general paint restoration. It polishes out paint imperfections on all paint finishes and residual swirlmarks and holograms.



#### Features & Benefits

- No water necessary no mess, easy application
- No silicones bodyshop / paintshop safe
- Removal of scratches, no hiding of imperfections better finish and gloss
- Contains lubricants easier running of pad; no greasy film and extends life of foam mop
- Can be used on all automotive paint systems one product for all paint systems
- Especially formulated for professional market time saving products
- Creates extra deep gloss excellent finish on surface

P/N	Product	S/C	Packaging
86606	Performance Compound	2 RC2	1 kg bottle

## **Application**

KENT Performance Compound 2 can be used on all automotive paint systems, including cellulose, single component and 2-pack acrylic clearcoats, MS / HS paint systems, ceramic clear coats, UV clear coats and waterborne clear coats. A specially formulated ultra fine compound designed to polish out paint imperfections on all paint finishes and residual swirl marks and holograms on dark coloured paint finishes. Does not hide imperfections with cosmetic oil but removes scratches completely. Contains lubricants, which assist in a smoother, easier running of the polishing pad without leaving a greasy film and extending life of foam mop. The non-spray formula is especially developed to be used without water reducing clean-up time.

The Performance range will achieve an excellent showroom finish:

Artificial light in showrooms will always show scratches underneath the polished surface.

Scratches underneath polished surface will cause light scattering; meaning less glossy finish.

Surfaces prepared with Performance products won't show any underneath scratches as these are polished out by the product.

## Instructions

- 1.For best results use with KENT Compounding polishing pad. Machine speed: 1000 2000 rpm (no load). Possible Options are Lambswool (P/N 85920) for extra cut (P1500-P2000), orange foam pad (P/N 85924) for P3000 Swirl removal, black foam pad (P/N 85925) for Hologram removal.
- 2.Never use excessive compound. It completely removes nibs and fine flatting paint scratches if used with the lambswool pad,
- 3.On soft or sensitive paint or where heat build-up may be a problem, the addition of water mist to avoid any friction burn, particularly with new pads, may assist in the polishing process. But avoid using too much water.
- 4.Once a Polishing pad is activated with water, no additional water needs to be used once the pad has been impregnated with product.
- 5. For hand or machine application



### **Technical Information**

General info:

Base: Emulsion base with inert inorganic micro-abrasives, solvents and surfactants

Appearance / colour: White viscous cream

Odour: Vanilla

Specific gravity: 1.104 g/ml
pH: 9.5 +/- 0.5

Solubility in water: Miscible
Application temp: Ambient

VOC: 185 g/l

Shelf life: 24 months

## **Additional Info**

Custom tariff code:

For swirl & hologram removal it is essential to keep polishing pads clean, and separate from compounding pads. Any dust or compounding residue must be washed off vehicle before polishing.

3405 3000





#### SDS available on www.kenteurope.com

#### Terms and Condition

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Way, Pitreavie Business Park, Dunfermline,

Fife KY11 8US Tel: 0800 136925 or 01383 723344 between 08:30-17:30

Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383

735829 or Email: KENTsales.UK@kenteurope.com

REV: 23/05/2018