



SL85 / SL 500

A fast acting, penetrating grease for lubrication of general moving components subjected to high pressure, impact and vibration.



Features & Benefits

- Special formulation – thin while “spraying” for a good penetration and thick after “flash off” for a good protection and lubrication
- Excellent penetrant – gets to where lubricant is required
- Transparent appearance – invisible protection
- Moisture repellent – protects against corrosion
- High adhesion – stays where it is needed
- High lubricity – reduces wear and friction

P/N	Product	S/C	Packaging
83688	SL85	KSL85	85 ml aerosol
84339	SL500	KSL	500 ml aerosol

Application

KENT SL85/SL500 is a lubricant based on a mixture of synthetic oil, mineral oil, tackifiers, anti wear-, anti oxidation-, anti corrosion additives and PTFE.

It's a spray grease with excellent penetrating ability and very high adhesion and designed for lubricating general moving components during the service schedule, such as:

Door hinges, check straps, door locks, bonnet and boot hinges and catches, pedal pivots, fuel cap locks, seat rails, control linkages, cables, chains (O/X/Z-ring) and much more.

Once the propellant has flashed off, it leaves a high degree of both protection and lubricating properties.

Instructions

1. Shake well before use.
2. Clean the moving parts before application with a KENT degreaser (e.g. Soft Surface Cleaner or Acrysol) and dry with a cloth.
3. Spray from a short distance directly onto the moving parts of the component requiring lubricating.
4. Allow the product to flow and let the solvents evaporate.
5. Remove excess of lubrication.



Technical Information

Base:	PTFE based lubricant
Consistency:	Gel-like liquid
Colour:	Yellow-clear
Shelf life:	30 months
Custom tariff code:	3403 19 19
VOC:	410 g/l
<hr/>	
Specific gravity (20 °C):	0.68 g/ml
Timken OK load (ASTM D 2782):	> 50
Penetration IP 50:	Not determined
Worked:	Not determined
Unworked:	Not determined
NLGI grease grade:	Not determined
Drop point:	Not determined
Four ball wear:	Scar diameter / 1500rpm / 1 h /200N: 0.30
Four ball weld:	EP: 1500 rpm, OK load: 2200 N, welding load: 2300 N
Water separation/demulsifying:	40-40-0
Additives / thickener:	Anti wear-, anti-oxidation- and anti-corrosion additives
Temp resistance:	-30 °C to 200 °C
Continuous:	Not determined
Temporary:	Not determined
Application temperature:	10 °C to 35 °C
Copper corrosion:	3h / 200 °C: 1-b
Corrosion ASTM D 665:	Part A: Distilled water - no corrosion Part B: Sea water - no corrosion
Dielectric strength:	Not determined
Volume resistivity:	Not determined



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: KENTsales.UK@kenteurope.com

REV: 24/06/2016